

AS ISO 6015:2021  
ISO 6015:2006



STANDARDS  
Australia



# Earth-moving machinery — Hydraulic excavators and backhoe loaders — Methods of determining tool forces



AS ISO 6015:2021

This Australian Standard® was prepared by ME-063, Earthmoving Equipment. It was approved on behalf of the Council of Standards Australia on 22 March 2021.

This Standard was published on 1 April 2021.

The following are represented on Committee ME-063:

- Australian Industry Group
- Better Regulation Division — SafeWork NSW
- Construction and Mining Equipment Industry Group
- Department of Natural Resources, Mines and Energy, Qld
- Department of Regional NSW
- Engineers Australia
- Institute of Instrumentation, Control and Automation Australia
- Minerals Council of Australia
- Mining Electrical and Mining Mechanical Engineering Society
- University of Queensland

This Standard was issued in draft form for comment as DR AS ISO 6015:2020.

**Keeping Standards up-to-date**

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

[www.standards.org.au](http://www.standards.org.au)

ISBN 978 1 76113 255 1

# Earth-moving machinery — Hydraulic excavators and backhoe loaders — Methods of determining tool forces

First published as AS ISO 6015:2021.

## **COPYRIGHT**

© ISO 2021 — All rights reserved  
© Standards Australia Limited 2021

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

## Preface

This Standard was prepared by the Standards Australia Committee ME-063, Earthmoving Equipment.

The objective of this document is to specify methods for measuring and calculating the tool forces of earth-moving attachments fitted to hydraulic excavators and the hoe equipment of backhoe loaders. It is applicable to hydraulic excavators and backhoe loaders as defined in ISO 6165.

This document is identical with, and has been reproduced from, ISO 6015:2006, *Earth-moving machinery — Hydraulic excavators and backhoe loaders — Methods of determining tool forces*.

As this document has been reproduced from an International Standard, the following applies:

- (a) In the source text “this International Standard” should read “this document”.
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

# Contents

<b>Preface</b> .....	<b>ii</b>
<b>Foreword</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Measurement methods</b> .....	<b>3</b>
4.1 Test site and general.....	3
4.2 Test apparatus.....	3
4.3 Preparation for testing.....	3
4.4 Requirement during testing.....	7
4.5 Limit conditions.....	7
4.6 Pivot positions.....	7
4.7 Outriggers.....	7
4.8 Measurement procedure.....	7
4.8.1 General.....	7
4.8.2 Arm cylinder tool force.....	8
4.8.3 Bucket cylinder tool force.....	8
4.8.4 Crowd tool force.....	9
4.8.5 Grab/clamshell closing force.....	9
4.9 Test report.....	9
<b>5 Calculation methods</b> .....	<b>10</b>
5.1 General.....	10
5.2 Rated tool forces and closing force.....	11
5.2.1 Arm cylinder tool force.....	11
5.2.2 Bucket cylinder tool force.....	11
5.2.3 Crowd tool force.....	11
5.2.4 Grab/clamshell closing force.....	11
<b>6 Verification of rated tool and closing forces</b> .....	<b>14</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 6015 was prepared by Technical Committee ISO/TC 127, *Earth-moving machinery*, Subcommittee SC 1, *Test methods relating to machine performance*.

This second edition cancels and replaces the first edition (ISO 6015:1989), which has been technically revised.

# Australian Standard®

## Earth-moving machinery — Hydraulic excavators and backhoe loaders — Methods of determining tool forces

### 1 Scope

This International Standard specifies methods for measuring and calculating the tool forces of earth-moving attachments fitted to hydraulic excavators and the hoe equipment of backhoe loaders. It is applicable to hydraulic excavators and backhoe loaders as defined in ISO 6165.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6016:1998, *Earth-moving machinery — Methods of measuring the masses of whole machines, their equipment and components*

ISO 6165, *Earth-moving machinery — Basic types — Identification and terms and definitions*

ISO 6746-1:2003, *Earth-moving machinery — Definitions of dimensions and codes — Part 1: Base machine*

ISO 7135:1993, *Earth-moving machinery — Hydraulic excavators — Terminology and commercial specifications*

ISO 7451:1997, *Earth-moving machinery — Volumetric ratings for hydraulic excavator buckets and backhoe loader buckets*

ISO 7546:1983, *Earth-moving machinery — Loader and front loading excavator buckets — Volumetric ratings*

ISO 9248:1992, *Earth-moving machinery — Units for dimensions, performance and capacities, and their measurement accuracies*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

#### 3.1

##### **tool force**

force generated at the bucket lip or cutting edge, but not at the tips of the teeth, when operating the bucket or arm cylinders independently

#### 3.2

##### **arm cylinder tool force**

force generated at the bucket lip with the arm cylinder positioned to provide a rotating moment around the arm pivot

Note 1 to entry: The bucket lip moves towards the base machine when hoe equipment is used.

#### 3.3

##### **arm cylinder tool force at level crowd**

(shovel equipment) horizontal arm cylinder tool force generated by the arm cylinder at the bucket lip when the bucket's attitude is level and maintained parallel to the ground line and the lip is at the ground line

**3.4****bucket cylinder tool force**

tool force generated at the bucket lip with the bucket cylinder(s) positioned to provide a rotating moment to the bucket around its pivot

Note 1 to entry: The bucket lip moves towards the base machine when hoe equipment is used and away from it when shovel equipment is used.

**3.5****crowd tool force**

(hydraulic excavators with telescoping boom) tool force generated at the bucket lip when the telescoping boom is retracted

**3.6****rated tool force**

tool force, measured or calculated, that the manufacturer publishes

**3.7****actual tool force**

measured tool force generated at the bucket without tipping or sliding occurring

**3.8****maximum [arm cylinder] [bucket cylinder] [crowd] tool force**

largest measured or calculated tool force

**3.9****grab [clamshell] closing force**

force generated between the grab [clamshell] cutting edges or teeth tips when closing

**3.10****maximum grab [clamshell] closing force**

largest measured or calculated grab [clamshell] closing force

**3.11****arm force radius**

*A*

radius of the arc that passes through the bucket lip and whose centre is located at the arm pivot

Note 1 to entry: See [Figure 5](#)

**3.12****bucket force radius**

*B*

radius of the arc that passes through the bucket lip and whose centre is located at the bucket pivot

Note 1 to entry: See [Figure 6](#)

**3.13****grab [clamshell] force radius**

*C*

radius of the arc that passes through the grab or clamshell lip and whose centre is located at the grab or clamshell pivot

Note 1 to entry: See [Figure 7](#)

**3.14****operating mass**

**OM**

mass of the base machine with equipment and empty attachment as specified by the manufacturer, and with the operator (75 kg), full fuel tank and all fluid systems at the levels specified by the manufacturer

[SOURCE: ISO 6016:1998, definition 3.2.1]

**3.15****working circuit hydraulic pressure**

normal operating pressure applied to the specific circuit by the pump(s)

**3.16****maximum relief circuit hydraulic pressure**

maximum static pressure in a specific circuit limited by a relief valve at a flow no greater than 10% of the rated circuit flow

**3.17****hydraulic limit**

condition when the tool forces are limited by maximum relief circuit pressure

**3.18****tipping limit**

condition when the tool forces are limited by the onset of tipping of the machine

**3.19****slipping limit**

condition when the tool forces are limited by the machine slipping on the test surface

## 4 Measurement methods

### 4.1 Test site and general

The test site shall consist of a level, hard surface, with anchor points and space for using the measuring devices specified in 4.2.1 to 4.2.3. For measurements made below the ground plane, a space below that plane is required for acceptance of the machine tool and the measurement devices, the anchorage and any auxiliary equipment.

All measurements shall be accurate to within  $\pm 2\%$  or shall accord with an International Standard relative to test equipment accuracy.

In the preferred method, the force to be measured is applied directly to the force measuring device (4.2.1). If the force is applied via a pulley, its friction should be taken into account. The wire rope (4.2.4) should be as short as possible to minimize the affect on accuracy.

### 4.2 Test apparatus

**4.2.1 Force measuring device**, of accuracy according to ISO 9248.

**4.2.2 Hydraulic oil pressure measuring device**, of accuracy according to ISO 9248.

**4.2.3 Instrument(s) for measuring linear dimensions**, of accuracy according to ISO 9248.

**4.2.4 Wire ropes and shackles, pulley, safety chains and adjustable supporting frames.**

### 4.3 Preparation for testing


The machine shall be equipped according to ISO 6016.

The machine shall be fitted with the bucket, grab or clamshell and appropriate counterweights, and shall have the tyre pressure, and tyre ballast or track tension as specified by the manufacturer.


The hoe, shovel, grab or clamshell equipment for each test shall be as specified by the manufacturer.

Prior to testing, the engine and hydraulic system shall attain the normal operating temperature. The working circuit hydraulic pressure and maximum relief circuit hydraulic pressure shall then be checked for compliance with the manufacturer's ratings using the measuring device specified in 4.2.2.

The machine shall be positioned on the test site. The bucket or attachment shall be connected to a force measuring device (4.2.1), as shown in Figures 1, 2, 3, and 4.



a) Hydraulic excavator fitted with hoe




b) Hydraulic excavator fitted with shovel


**Key**

- F* tool force
- 1 arm cylinder
- 2 force measuring device (load cell)
- 3 arm pivot

**Figure 1 — Typical arrangements for measuring maximum arm cylinder tool force (see 4.8.2)**



a) Hydraulic excavator fitted with hoe




b) Hydraulic excavator fitted with shovel

**Key**

- $F$  tool force
- 1 bucket cylinder
- 2 bucket pivot
- 3 force measuring device (load cell)


**Figure 2 — Typical arrangements for measuring maximum bucket cylinder tool force (see 4.8.3)**



**Key**

- F* tool force
- 1 force measuring device (load cell)

**Figure 3 — Hydraulic excavator fitted with telescoping boom — Typical arrangement for measuring maximum crowd tool force (see 4.8.4)**



**Key**

- 1 force measuring device (load cell)

**Figure 4 — Grab or clamshell attachment — Typical test arrangement for measuring grab/clamshell closing force (see 4.8.5)**

#### **4.4 Requirement during testing**

The tests shall be conducted with the machine running in accordance with the manufacturer's operating instructions and observing all safety rules.

Tie-down and blocking devices (4.2.4) shall be applied to the machine to limit slippage and tipping. Safety chains shall be loose so that the machine can attain the tipping condition and yet be prevented from overturning.

Components may be mounted on a test bed simulating a complete machine.

The required cylinder(s) shall be operated independently and the force at the bucket lip or attachment recorded with the engine running at the manufacturer's rated speed.

A series of preliminary tests shall be conducted with the equipment boom arm and bucket at different angles in relation to each other (i.e. by varying the cylinder stroke), in order to obtain the optimum position giving the maximum force. The position (angle) of the boom, arm and bucket at the optimum position shall be recorded.

#### **4.5 Limit conditions**

The limit condition for each test shall be noted.

If the hydraulic limit condition is reached, the report should note the system or circuit in which the maximum relief circuit hydraulic pressure was exceeded.

If the tipping limit condition is reached, the tool force shall be measured after the onset of tipping.

If the slipping limit condition is reached, the machine shall be anchored and the reported results should indicate that the maximum tool force was obtained by anchoring the machine.

#### **4.6 Pivot positions**

When alternative pivot positions for the boom, arm, attachment and cylinders and/or a telescopically adjustable boom are available, the relative pin positions of boom, arm and bucket fixing and/or the telescopic boom position as tested shall be recorded.

#### **4.7 Outriggers**

For machines fitted with outriggers, the tests shall be conducted with the outriggers raised or lowered as specified by the manufacturer.

#### **4.8 Measurement procedure**

##### **4.8.1 General**

Each test shall be conducted three times, and the maximum tool force for each test shall be noted; the arithmetic mean of these three values shall be recorded in the test results.

The tool forces shall be measured in accordance with the specified requirements.

For buckets with a curved or pointed cutting edge, the tool forces shall be measured at the centre of the bucket width.

The direction of the tool forces to be measured shall be tangential to the arc described by the bucket lip.

For each machine equipped with hoe, shovel, or telescoping boom equipment, bucket and arm tool forces are required to properly determine the tool forces. For each machine equipped with either grab or clamshell equipment, only the grab/clamshell closing force is required for proper determination.

Where both arm and bucket cylinder tool forces are required, both shall be either actual tool forces or both shall be rated tool forces.

The actual tool force is determined from measurements and considers variables such as the weight of the arm, bucket, clamshell, links, pins, cylinders and attaching hardware, as well as friction.

## **4.8.2 Arm cylinder tool force**

### **4.8.2.1 Hoe equipment**

Measure this tool force tangential to the arc described by the bucket lip about the arm pivot. Position the load cell (4.2.1) such that it is placed in tension, as shown in [Figure 1 a\)](#).

For the maximum tool force, the working circuit hydraulic pressure shall be at maximum and the bucket positioned for maximum bucket cylinder tool force so as to produce the maximum rotating moment about the arm pivot.

### **4.8.2.2 Shovel equipment**

Measure this tool force tangential to the arc described by the bucket lip about the arm pivot. Position the load measurement device such that it is placed in tension as shown in [Figure 1 b\)](#).

The bucket lip shall move away from the base machine. See [Figure 1 b\)](#).

Position the bucket for maximum bucket cylinder tool force so as to have a minimum distance between the bucket lip and the arm pivot.

No part of the bucket shall be outside of the arc described by the bucket lip about the arm pivot.

For the maximum tool force, the working circuit hydraulic pressure shall be at maximum and the bucket positioned for maximum bucket cylinder tool force so as to produce the maximum rotating moment about the arm pivot.

## **4.8.3 Bucket cylinder tool force**

### **4.8.3.1 Hoe and telescoping boom equipment**

Measure this tool force tangential to the arc described by the bucket lip about the bucket pivot. Position the load measurement device such that it is placed in tension as shown in [Figure 2 a\)](#) or [Figure 3](#), as applicable.

Position the bucket for maximum bucket cylinder tool force. No part of the bucket shall be outside the arc described by the bucket lip about the arm pivot.

For the maximum bucket cylinder tool force, the working circuit hydraulic pressure shall be at maximum and the bucket positioned so as to produce the maximum rotating moment about the bucket pivot.

Adjustable and telescoping boom equipment shall be in the minimum extension position, unless otherwise noted. If the arm can be articulated horizontally, it shall be in the straight position.

### **4.8.3.2 Shovel equipment**

Measure this tool force tangential to the arc described by the bucket lip about the bucket pivot. Position the load measurement device such that it is placed in tension as shown in [Figure 2 b\)](#).

For the maximum bucket cylinder tool force, the working circuit hydraulic pressure shall be at maximum and the bucket positioned so as to produce the maximum curling moment about the bucket pivot.

#### 4.8.4 Crowd tool force

The crowd tool force shall be measured parallel to the line of action of the retracting boom. The load measurement device shall be positioned such that it is placed in tension.

The bucket lip shall move toward the base machine.

The bucket shall be positioned so that the line of action of the crowd force is parallel to the line of action of the telescoping boom.

For the maximum crowd tool force, the working circuit hydraulic pressure shall be at maximum. See [Figure 3](#).

#### 4.8.5 Grab/clamshell closing force

A force measuring device ([4.2.1](#)) shall be placed between the cutting edges or teeth tips of the grab or clamshell, which shall be in the position of maximum closing force, applied by the hydraulic closing cylinders or other means.

The distance between the cutting edges shall be recorded, see [Figure 4](#). In order to minimize measurement errors, the force measuring device ([4.2.1](#)) should be as small as possible in order to approach measuring the load tangential to the cutting edges or teeth lips.

The maximum grab or clamshell closing force is obtained when the working circuit hydraulic pressure is at a maximum and the clamshell or grab is positioned for maximum closing moment.

The direction of the closing forces to be determined shall be tangential to the arc described by the clamshell grab cutting edges or teeth lips.

### 4.9 Test report

The following information shall be reported.

a) **Machine:**

- 1) type;  
model;
- 3) manufacturer;
- 4) operating mass of machine as tested, in kilograms;
- 5) working circuit hydraulic pressure or maximum relief circuit hydraulic pressure settings, in kilopascals.

b) **Type of undercarriage** (i.e. crawler or wheeled machine, in accordance with ISO 6746-1):

- 1) Crawler machine
  - i) type of track shoe;
  - ii) maximum width (over tracks),  $W1$ , in metres;
  - iii) track gauge,  $W2$ , in metres;
  - iv) track shoe width,  $W4$ , in metres;

- v) crawler base (distance between vertical centrelines of front and rear idlers or sprockets),  $L2$ , in metres.

Wheeled machine

- i) tread,  $W3$ , in metres (specifying front and rear if different);
- ii) wheel-base,  $L3$ , in metres;
- iii) tyre size(s);
- iv) tyre pressure, in kilopascals;
- v) ballast (if specified), in kilograms.

c) **Equipment fitted** (in accordance with ISO 7135):

- 1) boom length (at available pin or telescoped positions), in metres;  
arm length (at available pin or telescoped positions), in metres;
- 3) bucket type, rated volume (in accordance with ISO 7451 or ISO 7546) and operating mass, in kilograms;
- 4) attachments (specify) and operating mass, in kilograms;
- 5) counterweights, in kilograms;
- 6) outriggers — width between pad centres, outriggers extended,  $W6$ , in metres.

The tool forces shall be recorded in accordance with [Table 1](#). Under “limit condition”, the manufacturer shall indicate if blocking, tie-downs, safety chains or other devices were necessary to limit movement of the machine during the test.

**Table 1 — Test results — Maximum (actual) tool and closing forces**

Maximum tool force	Pin position and arm length m	Force $F$	Limit condition
		N	
Hoe	Arm cylinder tool force		
	Bucket cylinder tool force		
Shovel	Arm cylinder tool force		
	Bucket cylinder tool force		
Maximum grab/clamshell closing force	Distance between teeth/ cutting edges		

## 5 Calculation methods

### 5.1 General

The tool forces and grab/clamshell closing forces shall be calculated excluding the weight of all components and the effect of friction.

## 5.2 Rated tool forces and closing force

### 5.2.1 Arm cylinder tool force

Calculate the tangential arm cylinder tool force as being the force generated by the arm cylinder and tangent to the arc of radius  $A$  as shown in [Figure 5 a\)](#) for hoe equipment and b) for shovel equipment.

### 5.2.2 Bucket cylinder tool force


Calculate the bucket cylinder tangential tool force as being the force generated by the bucket cylinder and tangent to the arc of radius  $B$  as shown in [Figure 6 a\)](#), [b\)](#) and [c\)](#) for hoe, shovel and telescoping boom equipment, respectively.

### 5.2.3 Crowd tool force


Calculate the crowd tool force of a telescoping boom as being the force generated by retracting the boom, parallel to its line of action, as shown in [Figure 3](#).

### 5.2.4 Grab/clamshell closing force

Calculate the grab/clamshell closing force as being the force generated by the closing cylinder or other means, tangent to the arc of radius  $C$ , as shown in [Figure 7](#).



a) Hoe attachment




**b) Shovel attachment**


**Key**

- A* arm force radius
- F* tool force
- 1 arm pivot


**Figure 5 — Calculated arm cylinder tool force (see 5.2.1)**



**a) Hoe attachment**



b) Shovel attachment




c) Telescoping boom attachment

**Key**

- B* bucket force radius
- F* tool force
- 1 bucket pivot

**Figure 6 — Calculated bucket cylinder tool force (see 5.2.2)**

**Key**

- $C$  grab/clamshell force radius  
 $F$  closing force

**Figure 7 — Grab/clamshell attachment — Calculation of grab/clamshell closing force (see 5.2.4)**

## 6 Verification of rated tool and closing forces

Rated tool and closing forces based on calculations may be published, but these shall have been correlated (verified) by actual measurement.

For verification purposes, the rated tool force shall be no more than 95 % of the actual tool force measured. If the tool force has been calculated, then the manufacturer shall state this.

The manufacturer shall specify the arm or boom position used when a published tool force value has been obtained using a multi-position boom and/or arm.

The specified guide linkage and bucket linkage shall be used for the published values of tool forces for machines fitted with hoe or shovel equipment.

**Standards Australia**

Standards Australia develops Australian Standards® and other documents of public benefit and national interest. These Standards are developed through an open process of consultation and consensus, in which all interested parties are invited to participate. Through a Memorandum of Understanding with the Commonwealth Government, Standards Australia is recognized as Australia's peak non-government national standards body.

For further information visit [www.standards.org.au](http://www.standards.org.au)

**Australian Standards®**

Committees of experts from industry, governments, consumers and other relevant sectors prepare Australian Standards. The requirements or recommendations contained in published Standards are a consensus of the views of representative interests and also take account of comments received from other sources. They reflect the latest scientific and industry experience. Australian Standards are kept under continuous review after publication and are updated regularly to take account of changing technology.

**International Involvement**

Standards Australia is responsible for ensuring the Australian viewpoint is considered in the formulation of International Standards and that the latest international experience is incorporated in national Standards. This role is vital in assisting local industry to compete in international markets. Standards Australia represents Australia at both the International Organization for Standardization (ISO) and the International Electrotechnical Commission (IEC).



GPO Box 476 Sydney NSW 2001  
Phone (02) 9237 6000  
[mail@standards.org.au](mailto:mail@standards.org.au)  
[www.standards.org.au](http://www.standards.org.au)