

AS ISO 7546:2021
ISO 7546:1983



STANDARDS
Australia



Earth-moving machinery — Loader and front loading excavator buckets — Volumetric ratings



AS ISO 7546:2021

This Australian Standard ® was prepared by ME-063, Earthmoving Equipment. It was approved on behalf of the Council of Standards Australia on 24 March 2021.

This Standard was published on 9 April 2021.

The following are represented on Committee ME-063:

- Australian Industry Group
- Better Regulation Division – SafeWork NSW
- Construction and Mining Equipment Industry Group
- Department of Natural Resources, Mines and Energy, Qld
- Department of Regional NSW
- Engineers Australia
- Institute of Instrumentation, Control & Automation Australia
- Minerals Council of Australia
- Mining Electrical and Mining Mechanical Engineering Society
- University of Queensland

This Standard was issued in draft form for comment as DR AS ISO 7546:2020.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76113 279 7

Earth-moving machinery — Loader and front loading excavator buckets — Volumetric ratings

First published as AS ISO 7546:2021.

COPYRIGHT

© ISO 2021 — All rights reserved
© Standards Australia Limited 2021

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968(Cth).

Preface

This Standard was prepared by the Standards Australia Committee ME-063, Earthmoving Equipment.

The objective of this document is to specify a method for approximating the volume of typical materials contained in the bucket of front end loaders and excavators with front loading buckets. The volume ratings are based on the inside dimensions of the bucket and representative volumes on top of the bucket.

The method employs the technique of dividing the complex shape of the material in the bucket into simple geometric forms to allow volume calculations of different bucket configurations.

The rating method is intended to provide a consistent means of comparing bucket capacities. It is not intended to define actual capacities that might be observed in any specific application.

This document is identical with, and has been reproduced from, ISO 7546:1983, *Earth-moving machinery — Loader and front loading excavator buckets — Volumetric ratings*.

As this document has been reproduced from an International Standard, the following applies:

- (a) In the source text “this International Standard” should read “this document”.
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

Contents

Preface	ii
Foreword	iv
1 Scope and field of application	1
2 References	1
3 Restrictions and limitations	1
4 Definitions and symbols	2
4.1 bucket component.....	2
5 Volumetric ratings	3
5.1 Basic bucket.....	3
5.2 Extended straight cutting edge.....	3
5.3 Extended back sheet.....	4
5.4 Irregular cutting edge.....	5
5.5 Extended cutting edge and extended back sheet.....	6
6 Expression of volumetric ratings	7

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been authorized has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 7546 was developed by Technical Committee ISO/TC 127, *Earth moving machinery*, and was circulated to the member bodies in December 1981.

It has been approved by the member bodies of the following countries:

Australia	France	Spain
Austria	Germany, F.R.	Sweden
Belgium	Italy	United Kingdom
Brazil	Mexico	USA
Bulgaria	Poland	USSR
Czechoslovakia	Romania	
Egypt, Arab Rep. of	South Africa, Rep. of	

The member body of the following country expressed disapproval of the document on technical grounds:

Japan

Australian Standard[®]

Earth-moving machinery — Loader and front loading excavator buckets — Volumetric ratings

1 Scope and field of application

1.1 This International Standard specifies a procedure for approximating the volume of typical materials contained in the bucket of front end loaders and excavators with front loading bucket. The volume ratings are based on the inside dimensions of the bucket and representative volumes on top of the bucket.

1.2 The method employs the technique of dividing the complex shape of the material in the bucket into simple geometric forms to allow volume calculations of different bucket configurations.

1.3 The rating method is intended to provide a consistent means of comparing bucket capacities. It is not intended to define actual capacities that might be observed in any specific application.

2 References

ISO 7131, *Earth-moving machinery — Loaders — Terminology*.¹⁾

ISO 7135, *Earth-moving machinery — Excavators — Terminology*.¹⁾




Figure 1 — Bucket

3 Restrictions and limitations

3.1 The effect on volumes of local discontinuities such as bucket teeth, tooth adapters, and gussets shall be ignored.

3.2 Grated or slotted back sheets attached to the bucket to protect the machine or operator from material that might spill over the back of the bucket shall not be included in the capacity calculations.

¹⁾ At present at the Stage of draft.

Solid extended back sheets providing the same function may be included in the capacity calculations only if they are an integral part of the bucket.

3.3 Only buckets with an X/Y ratio greater than 12 shall be considered by the rating method(s). (See [figure 2](#).)




Figure 2 — X and Y dimensions for irregular side sheet

4 Definitions and symbols

4.1 bucket component

See [figure 1](#) and ISO 7131 and 7135.

4.2

strike plane

Horizontal plane across the width of the bucket from the cutting edge to the back sheet. (See [clause 5](#) for different bucket shapes.)

4.3

struck volume

V_S

Volume which lies beneath the strike plane.

4.4

top volume

V_T

Volume of material, a 2:1 slope, which lies on top of the strike plane.

4.5

rated bucket volume

V_R

Rated bucket capacity.

This capacity is calculated by adding the struck and top volumes : $V_R = V_S + V_T$.


5 Volumetric ratings

5.1 Basic bucket

The back sheet does not extend beyond a transverse line connecting the rear corners of the side sheets and the cutting edge does not extend beyond a transverse line connecting the front corners of the side sheets.

5.1.1 The strike plane passes through a line along the top of the back sheet at the rear and a line along the top of the cutting edge at the front as shown in [figure 3](#).

5.1.2 The volumetric capacity is calculated as shown in [figure 3](#).



Struck volume : $V_S = AW$

A is the interior cross section area

W is the interior width of the bucket

Top volume : $V_T = \frac{d^2W}{8} - \frac{d^3}{24}$

d is at transverse middle of bucket

The rated capacity is expressed as follows : $V_R = V_S + V_T$


Figure 3 — Basic bucket

5.2 Extended straight cutting edge

The cutting edge is straight in the transverse direction and extends beyond a transverse line connecting the front corners of the side sheets and the back sheet does not extend beyond a transverse line connecting the rear corners of the side sheets.

5.2.1 The strike plane passes through a line along the cutting edge at the front and a line along the top of the back sheet at the rear as shown in [figure 4](#).

5.2.2 The volumetric capacity is calculated as shown in [figure 4](#).



Struck volume : $V_S = AW - \frac{2f^2d}{3}$

Top volume : $V_T = \frac{d^2W}{8} - \frac{d^2}{6}(f + c)$

The rated capacity is expressed as follows : $V_R = V_S + V_T$


Figure 4 — Extended straight cutting edge

5.3 Extended back sheet

The back sheet extends beyond a transverse line connecting the rear corners of the side sheets and the cutting edge does not extend beyond the transverse line connecting the front corners of the side sheets.

5.3.1 The strike plane passes through the line along the top of the extended back sheet at the rear and a line along the cutting edge at the front as shown in [figure 5](#).

5.3.2 The volumetric capacity is calculated as shown in figure 5.



$$\text{Struck volume : } V_S = AW - \frac{2e^2d}{3}$$

$$\text{Top volume : } V_T = \frac{d^2W}{8} - \frac{d^2}{6}(e + c)$$

The rated capacity is expressed as follows : $V_R = V_S + V_T$


Figure 5 — Extended back sheet

5.4 Irregular cutting edge

The cutting edge extends beyond a transverse line connecting the front corners of the side sheets and is not straight in the transverse direction. The back sheet does not extend beyond the transverse line connecting the rear corners of the side sheets.

5.4.1 The strike plane passes through an imaginary transverse line at one third the distance of the protruding cutting edge at the front and a line along the top of the back sheet at the rear as shown in figure 6.

5.4.2 The volumetric capacity is calculated as shown in figure 6.



Struck volume :
$$V_S = AW - \frac{2f^2d}{3}$$

Top volume :
$$V_T = \frac{d^2W}{8} - \frac{d^2}{6}(f + c)$$

The rated capacity is expressed as follows : $V_R = V_S + V_T$


Figure 6 — Irregular cutting edge

5.5 Extended cutting edge and extended back sheet

The cutting edge (straight or irregular) extends beyond a line joining the front corners of the side sheets and the back sheet extends beyond a line connecting the rear corners of the side sheets.

5.5.1 The strike plane rests on the top edge of the back sheet at the rear and on the top edge of a straight cutting edge or the $h/3$ point (see 5.4.1) of an irregular cutting edge at the front as shown in figure 7.

5.5.2 The volumetric capacity is calculated as shown in figure 7.



$$\text{Struck volume : } V_S = AW - \frac{2(e^2 + ef + f^2)d}{3}$$

$$\text{Top volume : } V_T = \frac{d^2W}{8} - \frac{d^2}{6}(e + f + c)$$

The rated capacity is expressed as follows : $V_R = V_S + V_T$

Figure 7 — Extended cutting edge and extended back sheet

6 Expression of volumetric ratings

6.1 The volumetric rating of a bucket is the summation of the struck volume plus the top volume. It shall be expressed in cubic metres and published as the rated ISO bucket capacity as shown in the table.

6.2 If the determined capacity, as shown in the table, falls below a given rating interval by more than 2 %, the next lower interval shall be the rating.

Table

Range of rated capacity	Increments
Up to and including 0,6	0,02
Over 0,6 up to 1,5	0,05
Over 1,5 up to 2,5	0,1
Over 2,5 up to 5,0	0,2
Over 5,0 up to 10,0	0,5
Over 10,0	1,0

NOTES

Standards Australia

Standards Australia develops Australian Standards® and other documents of public benefit and national interest. These Standards are developed through an open process of consultation and consensus, in which all interested parties are invited to participate. Through a Memorandum of Understanding with the Commonwealth Government, Standards Australia is recognized as Australia's peak non-government national standards body.

For further information visit www.standards.org.au

Australian Standards®

Committees of experts from industry, governments, consumers and other relevant sectors prepare Australian Standards. The requirements or recommendations contained in published Standards are a consensus of the views of representative interests and also take account of comments received from other sources. They reflect the latest scientific and industry experience. Australian Standards are kept under continuous review after publication and are updated regularly to take account of changing technology.

International Involvement

Standards Australia is responsible for ensuring the Australian viewpoint is considered in the formulation of International Standards and that the latest international experience is incorporated in national Standards. This role is vital in assisting local industry to compete in international markets. Standards Australia represents Australia at both the International Organization for Standardization (ISO) and the International Electrotechnical Commission (IEC).



GPO Box 476 Sydney NSW 2001
Phone (02) 9237 6000
mail@standards.org.au
www.standards.org.au