

Australian/New Zealand Standard™

**Electric cables—Reeling and trailing—
For underground coal mining**

AS/NZS 1802:2003

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee EL-003, Electric Wires and Cables. It was approved on behalf of the Council of Standards Australia on 2 September 2003 and on behalf of the Council of Standards New Zealand on 9 September 2003. It was published on 7 November 2003.

The following are represented on Committee EL-003:

Australasian Railway Association
Australian Electrical and Electronic Manufacturers Association
Australian Industry Group
Canterbury Manufacturers Association New Zealand
Department of Defence (Australia)
Department of Mineral Resources N.S.W.
Electrical Contractors Association of New Zealand
Electrical Regulatory Authorities Council
Electricity Supply Association of Australia
Institution of Engineers Australia
Ministry of Economic Development (New Zealand)
National Electrical and Communications Association

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Australia web site at www.standards.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

Alternatively, both organizations publish an annual printed Catalogue with full details of all current Standards. For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia International or Standards New Zealand at the address shown on the back cover.

Australian/New Zealand Standard™

**Electric cables—Reeling and trailing—
For underground coal mining**

Originated in Australia as AS C81—1941.
Originated in New Zealand as NZS/AS 1802:1992.
Previous edition AS/NZS 1802:1995.
Fifth edition 2003.

COPYRIGHT

© Standards Australia/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Jointly published by Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001 and Standards New Zealand, Private Bag 2439, Wellington 6020

ISBN 0 7337 5508 9

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee EL-003, Electric Wires and Cables to supersede AS/NZS 1802:1995 *Electric cables—Reeling and trailing—For underground coal mining purposes*.

The Standard aligns with AS/NZS 2802 *Electric cables—Reeling and trailing—For mining and general use (other than underground coal mining)* for cables that have been developed to meet the special requirements of the Australian surface mining industry.

The objective of this Standard is to specify construction and tests of reeling and trailing cables specifically designed for use in underground coal mines.

Where the method of testing differs from, or has not yet been included in AS/NZS 1660, the test method has been included in Clause 25 and appendices to this Standard.

While the requirements of underground coal mining continue to determine the cables to be incorporated in this Standard, it is recognized that many of these cables will be equally applicable to other installations, e.g. underground metalliferous mines, ship loaders, travelling cranes, reclaimers at loading stations and other materials handling plant. Other requirements may apply in these applications.

Appropriate requirements for new types and sizes will be included in this Standard as the need arises.

This Standard differs from the previous edition in the following significant ways:

- (a) Type 217 and Type 280A cables have been deleted.
- (b) Insulation and sheathing materials have been referenced to AS/NZS 3808.
- (c) The definition of voltage designation has been modified to align with AS/NZS 2802.
- (d) The nominal overall diameters of cables have been deleted from the tables of dimensions. Consequently Appendix D has been deleted.
- (e) The extruded covering on interstitial conductors of Type 240 and Type 260 cables is now termed insulation.

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the appendix to which they apply. A ‘normative’ appendix is an integral part of a Standard, whereas an ‘informative’ appendix is only for information and guidance.

Statements expressed in mandatory terms in notes to tables are deemed to be requirements of this Standard.

CONTENTS

	<i>Page</i>
1 SCOPE	4
2 REFERENCED DOCUMENTS	4
3 DEFINITIONS	5
4 VOLTAGE DESIGNATION.....	7
5 DESIGNATION AND APPLICATION	7
6 MAXIMUM CONDUCTOR TEMPERATURES.....	8
7 POWER, EARTH AND PILOT CONDUCTORS (other than central pilot/control cores and composite earth screens).....	8
8 CENTRAL PILOT/CONTROL CORES (Types 209, 210, 241, 245, 275 and 280B only).....	9
9 CONDUCTOR SCREEN	10
10 INSULATION ON CONDUCTORS (other than earth conductors).....	11
11 TAPE OVER INSULATION OTHER THAN SEMI-CONDUCTIVE TAPE (Types 209, 210, 240 and 260 only).....	11
12 INSULATION SCREEN (non-metallic and composite).....	12
13 IDENTIFICATION OF CORES.....	14
14 CRADLE SEPARATORS.....	16
15 SEMICONDUCTIVE ELASTOMER COVERING FOR INTERSTITIAL EARTH CONDUCTORS (Types 241, 245, 275 and 280B only).....	16
16 LAYING UP OF CORES	17
17 SEMICONDUCTIVE ELASTOMER SCREEN FOR CORE ASSEMBLY (Types 241, 245, 275 and 280B only).....	17
18 REINFORCEMENT FOR CORE ASSEMBLY (Types 241, 245, 275 and 280B only).....	17
19 INNER SHEATH (Type 260 only).....	18
20 PLIABLE ARMOUR (Type 260 only).....	18
21 OUTER SHEATH (all cables).....	18
22 OPTIONAL OUTER SHEATH REINFORCEMENT (Types 209, 240 and 260 only)	19
23 CONSTRUCTION AND DIMENSIONS (all cables).....	19
24 JOINTS IN COMPLETED CABLE LENGTHS.....	20
25 TESTS.....	20
26 MARKING (all cables)	26
27 FIGURES OF CONSTRUCTION AND TABLES OF DIMENSIONS	27
 APPENDICES	
A PURCHASING GUIDELINES.....	43
B DETERMINATION OF SHEATH THICKNESS AND PLIABLE ARMOUR STRAND SIZE USING FICTITIOUS CALCULATION METHOD	44
C MEASUREMENT OF VOLUME RESISTIVITY	46

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Australian/New Zealand Standard**Electric cables—Reeling and trailing—For underground coal mining****1 SCOPE**

This Standard specifies elastomer-insulated, elastomer-sheathed reeling and trailing electric cables for use in underground coal mines. An essential feature of this Standard is the requirement that cables used for alternating current supply be electrically symmetrical.

This Standard is intended to apply only to cables of the types provided for in the tables of construction and dimensions.

This Standard also provides the basis of requirements for other sizes of cable not specified in this Standard.

NOTE: Purchasing guidelines are provided in Appendix A.

2 REFERENCED DOCUMENTS

The following documents are referred to in this Standard:

AS

1931 High voltage test techniques (all parts)

AS/NZS

1125 Conductors in insulated electric cables and flexible cords

1660 Test methods for electric cables, cords and conductors

1660.1 Method 1: Conductors and metallic components

1660.2.1 Method 2.1: Insulation, extruded semi-conductive screens and non-metallic sheaths—Methods for general application

1660.2.2 Method 2.2: Insulation, extruded semi-conductive screens and non-metallic sheaths—Methods specific to elastomeric, XLPE and XLPVC materials

1660.2.5 Method 2.5: Insulation, extruded semi-conductive screens and non-metallic sheaths—Methods specific to cables above 1 kV

1660.3 Method 3: Electrical tests

1660.5.6 Method 5.6: Fire tests—Test for combustion propagation

2802 Electric cables—Reeling and trailing—For mining and general use (other than underground coal mining)

3808 Insulating and sheathing materials for electric cables

3863 Galvanized mild steel wire for armouring cables

5000 Electric cables—Polymeric insulated

5000.1 Part 1: For working voltages up to and including 0.6/1 kV

ISO

1139 Textiles—Designation of yarns

3 DEFINITIONS

For the purpose of this Standard, the definitions given in the referenced Standards and those below apply.

3.1 Approximate value

A value which is neither guaranteed nor checked.

3.2 Bunch

A number of wires all of which are twisted together in the same direction and with the same length of lay throughout.

3.3 Composite screen

A screen comprising stranded or bunched copper wires applied in one direction and interwoven in the opposite direction with polyethylene terephthalate yarn, or its equivalent.

3.4 Conductor covering

Elastomeric semiconductive material extruded over the earth conductors.

3.5 Conductor screen

A layer of non-metallic semiconductive material applied directly over the conductor.

3.6 Cradle separator

A shaped section of elastomeric material, designed to support the core assembly, fill the centre interstice and provide a specified separation between individual power cores.

3.7 Direction of lay

The slope direction of the conductor wire, bunch, core, screen or armour strands when the stranded conductor or cable is held vertically. It is right-hand when the slope is in the direction of the central part of the letter Z, and left-hand when the slope is in the direction of the central part of the letter S.

3.8 Earth conductor

A conductor laid up in the cable for the purpose of providing earth continuity.

3.9 Fictitious diameter

Diameter calculated according to a formula based only on cross-sectional area of conductor, number of cores and specified component dimensions and which ignores conductor make-up and the possibility of components having dimensions other than as specified.

The fictitious value is only used to determine the mechanical protective coverings of the cable, i.e. inner and outer sheath and pliable armour strand size.

3.10 Insulation screen

A screen applied directly over insulation as follows:

- (a) A non-metallic semiconductive material.
- (b) A combination of (a) and composite screen.

3.11 Length of lay

The axial length of one complete turn of the helix formed by a cable component, e.g.—

- (a) a bunch of a multiple stranded conductor;
- (b) a core of a laid-up core assembly; or
- (c) the strands of pliable armour in a cable.

3.12 Maximum conductor temperature

The permitted maximum temperature at the surface of the conductor.

3.13 Multiple-stranded conductor

A group of bunches or strands laid up helically and symmetrically such that within any one layer the length of lay of bunches or strands is uniform.

3.14 Pilot/control core

An insulated conductor for use in conjunction with a protection or other control system.

3.15 Pitch circle diameter

The diameter of a circle which passes through the midpoints of like cable components, e.g.—

- (a) a given layer of bunches or strands in a multiple stranded conductor, or the laid-up cores of a multicore circular cable; or
- (b) the composite screen of a core or strands of pliable armour in a circular cable.

3.16 Power core

A power conductor with insulation of the appropriate voltage grade including, where applicable, semiconductive and composite screens.

3.17 Reeling and trailing cable

A cable having flexible conductors, insulation incorporating conductor and insulation screens where appropriate, filling, reinforcement where appropriate, one or more protective coverings, and being specially designed to provide a flexible electrical connection between portable or mobile equipment and a point of supply.

3.18 Routine tests

Tests made by the manufacturer on all completed cable to demonstrate the integrity of the cable.

3.19 Sample tests

Tests made by the manufacturer on samples of completed cables or components taken from completed cables, at a specified frequency, so as to verify that the finished product meets the design specification.

3.20 Strand

An assembly of wires laid up helically in one or more layers.

3.21 Type tests

Tests required to be made before supplying on a general commercial basis a type of cable covered by this Standard, to demonstrate performance characteristics to satisfy the intended application. These tests are such that after they have been made, they need not be repeated unless changes are made in the cable materials or design which might change the performance characteristics.

4 VOLTAGE DESIGNATION

Due to common usage in the mining industry, cables in this Standard have voltages designated using 'phase voltage'/'phase voltage'. However, although the cables specified for use with a.c. in this Standard are suitable in non-effectively earthed systems they are not intended for continuous operation with one phase earthed.

The voltage designation takes into consideration the fact that the system voltage may vary up to 9.1 percent from the designated voltage.

5 DESIGNATION AND APPLICATION

Cables are designated by means of a type number. The type number incorporates reference to the voltage, e.g. Type 209.3 identifies Type 209 rated at 3.3/3.3 kV.

Types of cables and their applications are listed in Table 1.

NOTE: For the cables specified in this Standard for use in underground coal mines, the first digit of the type number is 2. For those specified in AS/NZS 2802, for use in other than underground mining, the first digit of the type number is 4. These initial numerals have been chosen so that, for cables of like construction (e.g. as in the case of Types 209 and 409), the possibility of mistaken identity is reduced even after the cable has been worn or damaged.

TABLE 1
TYPES OF CABLES

1	2	3	4
Type no.	Description and typical intended application	Voltage designation kV	Details of construction and dimensions
209	Cables for general use (excluding shuttle cars): Composite screened three-core cable with central pilot core	1.1/1.1 to 11/11	Figure 3 and Table 9
240	Composite screened three-core cable with interstitial pilot cores	1.1/1.1 to 11/11	Figure 5 and Table 11
241	Semiconductive screened three-core cable with interstitial earth conductors and a central pilot core	1.1/1.1 to 11/11	Figure 6 and Table 12
245	Semiconductive screened three-core cable with interstitial earth conductors and three central pilot/control cores	1.1/1.1 to 3.3/3.3	Figure 7 and Table 13
260	Composite screened pliable armoured three-core cable with interstitial pilot cores	1.1/1.1 to 11/11	Figure 8 and Table 14
280B	Cables for general use (including shuttle cars): Semiconductive screened three-core cables with interstitial earth conductors and a central pilot core	1.1/1.1	Figure 10 and Table 16
210	Cable for hand-held boring machines: Composite screened three-core cable with central pilot core	1.1/1.1	Figure 4 and Table 10
275	Cables for shuttle cars: Semiconductive screened three-core cable with interstitial earth conductors and a central pilot core	1.1/1.1	Figure 9 and Table 15

6 MAXIMUM CONDUCTOR TEMPERATURES

The maximum conductor temperature of cables is specified in Table 2.

The emergency operation temperature (indicated in Column 2 of Table 2) is applicable for an average, over several years, of not more than one period per year. No period shall exceed 36 h and there shall not be more than three periods in any 12 consecutive months. The service life of cables may be reduced if flexed or reeled during emergency operation.

TABLE 2
MAXIMUM CONDUCTOR TEMPERATURE

1	2	3
Normal operation	Emergency operation	Short-circuit operation (5 s maximum duration)
°C	°C	°C
90	130	250*

* Account should be taken of the possibility that tinning could melt at 250°C.

NOTE: With respect to the hazard of hot surface ignition of coal dust maximum surface temperature of the cable must not exceed 150°C under any circumstances.

7 POWER, EARTH AND PILOT CONDUCTORS (other than central pilot/control cores and composite earth screens)

7.1 General

Power, earth and pilot conductors shall consist of tinned annealed copper wires complying with the appropriate requirements of AS/NZS 1125, except that the wires taken from the completed cable need not comply with the continuity test for tin plating specified in AS/NZS 1660.1. Conductor sizes from 1.5 mm² up to and including 4 mm² shall be Class 5 flexible conductors and conductor sizes greater than 4 mm² and up to 400 mm² shall be multiple-stranded circular flexible conductors (rope lay).

Tables 11 to 16 specify the standard interstitial conductors appropriate for a given cable. The conductors may consist of a larger number of smaller diameter wires provided that the individual wires are not less than 0.19 mm or 50 percent of the specified diameter rounded to one decimal place for a given conductor size, whichever is the greater, and provided that the conductor is of at least equal cross-sectional area to the standard conductor.

7.2 Joints

Joints shall comply with the appropriate requirements of AS/NZS 1125.

7.3 Direction of lay

The direction of lay of wires and of bunches or strands shall be such as to minimize cable distortion in service.

7.4 Length of lay of bunches for interstitial conductors (Types 240, 241, 245, 260, 275 and 280B only)

The bunches (as distinct from wires in the bunches) forming interstitial conductors shall be laid up with a length of lay not exceeding nine times the pitch circle diameter of the interstitial conductor bunches.

7.5 Resistance of earth and interstitial pilot conductors

These shall be as follows:

- (a) Types 241 and 245

Except where a specific resistance value applies, as specified below, the electrical d.c. resistance of the three interstitial conductors combined, when expressed as a ratio to the maximum permissible resistance of one associated power conductor (see AS/NZS 1125), shall not exceed the following values:

- (i) For all cables rated at 3.3/3.3 kV and above, and for cables rated at 1.1/1.1 kV with power conductors up to and including 70 mm² nominal cross-sectional area, the ratio 2.0.
- (ii) For cables rated at 1.1/1.1 kV with power conductors larger than 70 mm² nominal cross-sectional area, the ratio or value 3.0 or 0.547 Ω/km, whichever is the lesser.

(b) Types 240 and 260

Except where a specific resistance value applies, as is specified below, the electrical d.c. resistance of the three interstitial pilot conductors combined, when expressed as a ratio to the maximum permissible resistance of one associated power conductor (see AS/NZS 1125), shall not exceed the following values:

- (i) For cables with power conductors up to and including 70 mm² nominal cross-sectional area, the ratio 2.0.
- (ii) For cables with power conductors larger than 70 mm² nominal cross-sectional area, the ratio or value 3.0 or 0.547 Ω/km, whichever is the lesser.

(c) Types 275 and 280B

Except where a specific resistance value applies, as is specified below, the electrical d.c. resistance of the three interstitial earth conductors combined, when expressed as a ratio to the maximum permissible resistance of one associated power conductor (see AS/NZS 1125), shall not exceed the following values:

- (i) For cables with power conductors up to and including 50 mm² nominal cross-sectional area, the ratio 1.333.
- (ii) For cables with power conductors of 70 mm² nominal cross-sectional area, the ratio 2.0.
- (iii) For cables with power conductors larger than 70 mm² nominal cross-sectional area, the ratio or value 3.0 or 0.547 Ω/km, whichever is the lesser.

8 CENTRAL PILOT/CONTROL CORES (Types 209, 210, 241, 245, 275 and 280B only)

8.1 Conductor material and resistance

Central pilot or control conductors shall comply with Clause 7.1. The conductor resistance shall not exceed the following values:

- (a) For cables, other than Type 245, having power conductors of nominal cross-sectional area up to and including 35 mm² 5.5 Ω/100 m length of cable.

- (b) For cables having power conductors of nominal cross-sectional area above 35 mm² and all Type 245 cables 3 Ω/100 m length of cable.

8.2 Extensibility of pilot conductor

Central pilot conductors (Types 209, 210, 241, 275 and 280B only) shall meet the requirements of Test 5 in Table 7.

8.3 Central pilot/control cores (Type 245)

Central pilot/control cores shall be laid up with a right-hand direction of lay. The length of lay, expressed as a multiple of the pitch circle diameter of the core assembly, shall not exceed 13 times.

8.4 Joints in central pilot/control conductor

Individual wires may be joined in accordance with AS/NZS 1125.

8.5 Material and thickness of insulation

Central pilot/control conductors shall have an insulation of R-EP-90 complying with Clause 10. The thickness of insulation shall be not less than 0.50 mm at any point.

8.6 Location

The pilot/control cores shall be located in the centre of the cradle separator.

9 CONDUCTOR SCREEN

9.1 General

All cables having a voltage rating of 3.3/3.3 kV and above shall have a semiconductive screen applied directly over each power conductor. The screen shall be applied by taping or extrusion, or both.

9.2 Material

Any extruded semiconductive screen shall be made of cross-linked polymeric material.

Any taped screen shall be made of textile-reinforced semiconductive tape.

In both cases the material shall be compatible with and have a temperature rating not less than that of the insulation.

9.3 Application

9.3.1 *Extruded screen*

The extruded material shall bond to the insulation material so that it is not possible to separate the two materials without damage to their interface.

9.3.2 *Taped screen*

One or more tapes shall be applied free of creases. Where one tape is used, this shall be applied with an overlap of 50 percent of the tape width.

9.3.3 *Combined taped and extruded screen*

The tape shall be applied directly on the conductor, followed by the extruded screen.

The extruded screen need not be bonded to the taped screen.

9.4 Removal from conductor

The conductor screen shall not migrate into or adhere to the conductor.

9.5 Thickness

9.5.1 *Extruded screen or combined taped and extruded screen*

The screen thickness, determined by the method specified for measurement of insulation thickness in AS/NZS 1660.2.1, shall be not less than 0.30 mm at any point of the extruded or combined taped and extruded screen.

9.5.2 *Taped screen*

The minimum thickness of the tape for a taped screen when not in combination with the extruded screen shall be 0.1 mm.

9.6 Tests

The tests shall be performed as set down in Table 7.

10 INSULATION ON CONDUCTORS (other than earth conductors)

10.1 Material

The insulation shall be R-EP-90 in accordance with AS/NZS 3808.

10.2 Application

The insulation shall be applied by the extrusion process.

The application shall be as follows:

- (a) For all pilots and for 1.1/1.1 kV designated cables

The insulation shall fit closely on, but not adhere to, the conductor.

At the discretion of the manufacturer, a separator tape may be applied immediately over the power and pilot conductor. Any separator tape shall be coloured or opaque if it does not adhere to the insulation.

- (b) For power cores designated 3.3/3.3 kV and above

The insulation shall be bonded to the extruded conductor screen if applied, and does not need to be bonded to the taped screen.

10.3 Thickness

The thickness of insulation on conductors other than central pilot/control conductors, determined by the method specified in AS/NZS 1660.2.1 and Clause 25.2, shall be not less than the thickness specified (t_i) in Tables 9 to 16, as appropriate.

The minimum thickness of insulation at any point shall not fall below the specified thickness by more than 10 percent of the specified thickness plus 0.10 mm, i.e.

$$\text{minimum thickness} = (0.9t_i - 0.10 \text{ mm})$$

NOTE: See Clause 8.5 for requirements for insulation on central pilot/control conductors.

10.4 Tests

All tests shall be performed as set down in Table 7.

11 TAPE OVER INSULATION OTHER THAN SEMI-CONDUCTIVE TAPE (Types 209, 210, 240 and 260 only)

11.1 Material

The tape shall comprise a textile fabric approximately 0.1 mm thick.

11.2 Application

The tape shall be applied with an overlap of not less than 10 percent of the tape width or 2 mm, whichever is the greater.

For Types 209.1, 210.1, 240.1 and 260.1, a tape shall be applied directly over the insulation of each power core.

For Types 240 and 260 (all voltage ratings), a tape shall be applied over the insulation of all interstitial cores.

The tape shall be removable without damage to the insulation.

12 INSULATION SCREEN (non-metallic and composite)

12.1 General

The insulation screen on power cores shall comprise the following:

- (a) Types 209, 240 and 260 rated 3.3/3.3 kV and above
semiconductive elastomer (see Clause 12.2) or textile reinforced semiconductive tape (see Clause 12.3), or a combination of the two followed by a composite screen.
- (b) Types 241 and 245
semiconductive elastomer only.
- (c) Type 280B
textile reinforced semiconductive tape only.

12.2 Semiconductive elastomer screen

12.2.1 Material

The material shall comprise a layer of cross-linked semiconductive elastomer which shall be compatible with the insulation. It shall comply with the requirements of Table 7.

12.2.2 Application

The semiconductive elastomer shall be applied directly over the insulation of each power core.

It shall be capable of being removed by hand without damage to the insulation and shall not exceed the maximum stripping force specified in Clause 12.2.4.

12.2.3 Thickness of semiconductive screen

The average thickness of the screen, determined by the method specified for measurement of insulation thickness in AS/NZS 1660.2.1, shall be not less than 0.8 mm.

The thickness at any point shall be not less than 80 percent or more than 150 percent of the specified thickness.

12.2.4 Requirements for stripping of screen

The semiconductive screen shall be capable of being hand-stripped in accordance with the requirements of Table 7.

12.2.5 Tests

Tests on a semiconductive screen shall be made as set down in Table 7.

12.3 Textile reinforced semiconductive tape screen (Types 209, 240 and 260 only)

12.3.1 General

As an alternative to the elastomeric screen, a textile reinforced semiconductive tape screen may be applied over the insulation of the power cores of 3.3/3.3 kV rated cables and above.

12.3.2 *Material*

The semiconductive tape shall comprise a textile fabric, coated with a semiconductive elastomer and having a continuous print on one side identifying it as being semiconductive. It shall be compatible with the insulation of the power cores.

The volume resistivity of the tape shall comply with the requirements of Table 7.

When not in combination with a semiconductive elastomer screen, the average thickness of the tape shall be not less than 0.2 mm. When in combination with a semiconductive elastomer screen, the combined average thickness shall be not less than 0.6 mm.

12.3.3 *Application*

The semiconductive tape shall be applied immediately over the insulation with an overlap of not less than 10 percent of tape width or 2 mm, whichever is the greater.

It shall be capable of being removed by hand without damage to the insulation.

Where tape is applied in combination with a semiconductive elastomer screen, the tape shall be outermost, with the printed side of the tape facing outwards.

12.4 **Textile reinforced semiconductive tape screen (Type 280B only)**

12.4.1 *Material*

The semiconductive tape shall comprise a textile fabric, coated with a semiconductive elastomer. It shall be compatible with the insulation of the power cores.

The volume resistivity shall comply with the requirements of Table 7.

The thickness of the tape shall be not less than 0.1 mm.

12.4.2 *Application*

Two layers of the semiconductive tape shall be helically applied immediately over the insulation.

They shall be capable of being removed by hand without damage to the insulation.

12.5 **Composite screen (Types 209, 210, 240 and 260 only)**

12.5.1 *Construction*

Composite screens shall consist of copper strands interwoven with polyethylene terephthalate yarn or equivalent.

The copper strands shall be applied with a right-hand direction of lay and shall be interwoven in the left-hand direction with the yarn, thus forming a braid. Each of the textile fibrous members shall be not less than R60 tex (see ISO 1139).

Each strand shall consist of seven tinned annealed copper wires, each having a nominal diameter within the limits of 0.25 and 0.50 mm, inclusive. The recommended strand size for each cable is shown in Tables 9, 10, 11 or 14, as appropriate.

NOTE: A suitable semiconductive tape may be applied over the composite screen.

12.5.2 *Joints*

There shall be no joints in the complete braid. Where renewal of spindles is necessary, the ends of the individual copper strands of a spindle shall be butt-jointed with silver solder.

Such butt-jointed screen strands shall be free from sharp edges, solder lumps or similar imperfections.

The breaking strength of a butt-soldered joint shall be not less than 80 percent of a strand not containing a joint.

There shall be not more than one spindle renewal in any 1 m length of core.

12.5.3 Length of lay

The length of lay, expressed as a multiple of the pitch circle diameter of the screen, shall not exceed 4.5 times.

12.5.4 Coverage

The coverage by the copper shall be not less than 80 percent when derived from the following equation:

$$\text{Percentage covering} = \frac{W}{m} \times 100 \quad \dots 12.5(1)$$

where

W = number of strands \times diameter of single strand, in millimetres

$$m = \frac{L\pi d}{\sqrt{[(\pi d)^2 + L^2]}}$$

L = axial length or pitch of one complete turn of a screen strand, in millimetres

d = pitch diameter of screen strands, in millimetres, taken as the nominal diameter under the composite screen plus the diameter of one strand together with an allowance for increased thickness due to opposite weave yarn.

12.5.5 Resistance

Except where a specific resistance value applies as is specified below, the electrical d.c. resistance of the three screens combined, when expressed as a ratio to the maximum permissible resistance of one associated power conductor (see AS/NZS 1125), shall not exceed the following values:

- (a) For Type 210, the ratio..... 1.0.
- (b) For cables rated at 3.3/3.3 kV and above and for cables rated at 1.1/1.1 kV with power conductors up to and including 70 mm² nominal cross-sectional area, the ratio 2.0.
- (c) For cables rated at 1.1/1.1 kV with power conductors larger than 70 mm² nominal cross-sectional area, the ratio or value..... 3.0 or 0.547 Ω /km whichever is the lesser.

13 IDENTIFICATION OF CORES

13.1 General

Insulated conductors shall be distinctly and durably identified in accordance with Clauses 13.2 and 13.3.

13.2 Identification method

The identification method used shall be as indicated in Tables 3 and 4. The letters in Table 3 indicate the following methods:

- (a) Colour-coded insulation.
- (b) Colour-coded or continuously numbered proofed tape over the insulation.
- (c) Colour-coded or continuously numbered semiconductive tape over the insulation.
- (d) Colour-coded yarn in composite screen.
- (e) Types 241 and 245 only. Colour-coded or numbered semiconductive elastomer insulation screen, identifiable at intervals not greater than 300 mm.

TABLE 3
CORE IDENTIFICATION METHOD

1	2	3	4	5
Type No.	Voltage designation, kV			
	≤1.1/1.1		≥3.3/3.3	
	Power cores	Pilot cores	Power cores	Pilot cores
209	(a), (b) or (d)	(a)	(a), (c) or (d)	(a)
210	(a), (b) or (d)	(a)	not applicable	not applicable
240	(a), (b) or (d)	(a) and (b)*	(a), (c) or (d)	(a) and (b)*
241 and 245	(a) or (e)	(a)	(a) or (e)	(a)
260	(a), (b) or (d)	(a) and (b)*	(a), (c) or (d)	(a) and (b)*
275	(a)	(a)	not applicable	not applicable
280B	(a)	(a)	not applicable	not applicable

* Grey or white tape may be used.

13.3 Identification and rotational sequence

13.3.1 Identification by colours

Where identification is achieved by the use of colours, the colours and rotational sequence shall be in accordance with Table 4. Where colouring of power cores is not practicable, see Clause 13.3.2.

13.3.2 Identification by numbers

Where identification of power cores is achieved by numbering, the core colours shall be replaced by numbers, in the sequence specified in Clause 13.3.1, as follows:

- (a) No. 1 shall take the place of the red core.
- (b) No. 2 shall take the place of the white core.
- (c) No. 3 shall take the place of the blue core.

The printed power cores shall be identifiable at intervals of not greater than 300 mm.

TABLE 4
COLOURS AND ROTATIONAL SEQUENCE

Type No.	Rotational sequence of core colours
209*	red, white, blue
210*	red, white, blue
240	red, grey, white, grey, blue, grey
241*	red, black [‡] , white, black [‡] , blue, black [‡]
245 [†]	red, black [‡] , white, black [‡] , blue, black [‡]
260	red, grey, white, grey, blue, grey
275*	red, black [‡] , white, black [‡] , blue, black [‡]
280B*	red, black [‡] , white, black [‡] , blue, black [‡]

* The central pilot conductor insulation in all cases is coloured grey.

† The central pilot/control conductor insulations are coloured grey and numbered 1, 2 and 3.

‡ As the semiconductive covered earth conductors (Types 241, 245, 275 and 280B) are covered with semiconductive elastomer which is inherently black, it is not possible to assign the normal (green/yellow) earth colour identification to these conductors.

14 CRADLE SEPARATORS

14.1 Material

The material shall be of semiconductive elastomer (PCP, CSP or CPE) which shall be compatible with the insulation and comply with Tables 6 and 7.

14.2 Freedom to move and provision for cradle separator fingers

The cradle separators shall be such that the cores are free to move when the cable is flexed. Each finger of the cradle separator shall extend beyond a straight line joining the axis of power cores either side of the finger. The thickness of each finger shall be not less than 2.5 mm except for Type 245, where it shall be not less than is specified in Table 13.

15 SEMICONDUCTIVE ELASTOMER COVERING FOR INTERSTITIAL EARTH CONDUCTORS (Types 241, 245, 275 and 280B only)

15.1 Material

The material shall be of semiconductive elastomer (PCP, CSP or CPE) which shall be compatible with the insulation and comply with Tables 6 and 7.

15.2 Application

The semiconductive covering shall fit closely on, but not adhere to, the conductor.

15.3 Thickness

The average thickness of covering determined by the method specified for measurement of insulation thickness in AS/NZS 1660.2.1, shall be not less than the thickness specified (t_c) in Tables 12, 13, 15 and 16, as appropriate.

The minimum thickness at any point shall not fall below the specified thickness by more than 20 percent at the specified thickness plus 0.10 mm, i.e.

$$\text{minimum thickness} = (0.8t_c - 0.10 \text{ mm})$$

16 LAYING UP OF CORES

The cores of all cables shall be laid up with a right-hand direction of lay.

The length of lay, expressed as a multiple of the pitch circle diameter of the power core assembly, shall not exceed the following limits:

- (a) For Type 210 cable 9 times.
- (b) For cables up to and including 3.3/3.3 kV with power conductors up to and including 70 mm², other than (a) above..... 13 times.
- (c) For cables with power conductors larger than 70 mm² and all cables rated above 3.3/3.3 kV..... 16 times.

17 SEMICONDUCTIVE ELASTOMER SCREEN FOR CORE ASSEMBLY (Types 241, 245, 275 and 280B only)

17.1 Material

The material shall be of semiconductive elastomer (PCP, CSP or CPE) which shall be compatible with the insulation and comply with Tables 6 and 7.

17.2 Application

The semiconductive elastomer screen shall be applied over, but not adhere to, the laid-up core assembly so as to fill the remaining outer interstices and make continuous electrical contact with the exposed surface of the cores and the semiconductive covered earth conductors.

17.3 Thickness

The minimum thickness at any point of the screen, determined by the method specified in AS/NZS 1660.2.1 for the measurement of thickness of non-metallic sheath and the supplementary requirements specified in Clause 25.2, shall be not less than 0.3 mm.

The maximum thickness at any point shall not exceed the values given in Table 5.

TABLE 5
MAXIMUM THICKNESS OF SEMICONDUCTIVE SCREEN
FOR CORE ASSEMBLY
(Types 241, 245, 275 and 280B only)

Sheath thickness	Maximum thickness of elastomeric screen for core assembly
mm	mm
≤5.0	1.0
>5.0 ≤7.0	1.5
>7.0 ≤9.0	2.0
>9.0	3.0

NOTE: When establishing or measuring sheath thickness, the semiconductive elastomer screen is taken as part of the outer sheath (see Tables 12, 13, 15 and 16).

18 REINFORCEMENT FOR CORE ASSEMBLY (Types 241, 245, 275 and 280B only)

These types shall have a reinforcement binder comprising an open-weave polyamide monofilament tape or polyethylene terephthalate tape, applied over the semiconductive elastomer screened core assembly.

Alternatively, the reinforcement may comprise polyethylene terephthalate yarn (or equivalent), open-weave braid, or open-whipping in two contra-directional layers.

19 INNER SHEATH (Type 260 only)

19.1 Material

For Type 260, the sheath beneath the armour shall be GP-85-PCP, GP-90-CSP or GP-90-CPE in accordance with AS/NZS 3808.

NOTE: Where the zinc surface of the armour has become corroded, an adverse effect may occur on the ageing characteristics of CSP sheaths.

19.2 Application

The sheath shall fit closely over, but not adhere to, the laid-up core assembly and shall fill the outer interstices between the cores.

19.3 Thickness

The average thickness of inner sheath determined by the method specified in AS/NZS 1660.2.1 and Clause 25.2, shall be not less than the thickness (t_s) specified in Table 14. The minimum thickness at any point shall not fall below the specified thickness by more than 10 percent of the specified thickness plus 0.3 mm, i.e.

$$\text{minimum thickness} = (0.9t_s - 0.30 \text{ mm})$$

See Appendix B for basis on which sheath thickness is determined.

19.4 Tests

All tests shall be made as set down in Table 7.

20 PLIABLE ARMOUR (Type 260 only)

20.1 Material

The armour shall comprise galvanized low carbon (mild) steel strands. Each strand shall consist of seven wires of appropriate diameter, as specified in Table 14. The wires shall comply with the requirements of AS/NZS 3863.

20.2 Application

The requisite number of strands shall be applied helically over the inner sheath to provide close cover, with a length of lay of not less than 4.5 times nor more than 6 times the pitch circle diameter of the armour.

The direction of lay of the armour strands shall be opposite to that of the laid-up cores, i.e. left hand.

See Appendix B for the basis on which armour size is determined.

21 OUTER SHEATH (all cables)

21.1 Material

The outer sheath of all types of cable shall be HD-85-PCP, HD-90-CSP or HD-90-CPE in accordance with AS/NZS 3808.

21.2 Colour

The recommended colour for the outer sheath is black.

21.3 Application

The outer sheath of all cables shall be applied as follows:

- (a) Types 209, 210, 240 and 260

The sheath shall fit closely over, but not adhere to, the core assembly or, in the case of Type 260, the armour.

Where the sheath is applied directly over the laid-up core assembly, it shall fill the outer interstices between the cores.

Where the sheath is applied in two layers (e.g. where a sheath reinforcement is provided), the layers shall make an effective bond.

(b) Types 241, 245, 275 and 280B

The sheath shall be applied over the reinforcement (see Clause 18) and make an effective bond to the underlying semiconductive elastomer screen layer (see Clause 17).

The surface of the sheath of Types 275 and 280B cables shall be free from curing-tape indentations.

21.4 Thickness

The average thickness of outer sheath determined by the method specified in AS/NZS 1660.2.1 and Clause 25.2, shall be not less than the thickness (t_s) specified in Tables 9 to 16 inclusive, as appropriate. The minimum thickness at any point shall not fall below the specified thickness by more than 10 percent of the specified thickness plus 0.3 mm, i.e.

$$\text{minimum thickness} = (0.9t_s - 0.30 \text{ mm})$$

NOTES:

- 1 The sheath thickness need not be measured at the point of external identification marking.
- 2 Any open-weave reinforcement is taken to be part of the sheath.
- 3 See Appendix B for basis on which sheath thickness is determined.

21.5 Tests

All tests shall be made as set down in Table 7.

22 OPTIONAL OUTER SHEATH REINFORCEMENT (Types 209, 240 and 260 only)

22.1 Material

The use of reinforcement is optional. Where used (see Appendix A), the outer sheath shall be reinforced with three-ply R110 tex (see ISO 1139) polyethylene terephthalate yarn or open-weave polyamide monofilament or polyethylene terephthalate tape, or equivalent.

22.2 Application

Any yarn reinforcing shall be applied in the form of an open-weave braid, or open-whipping in two contra-directional layers, with a lay ratio of 1 to 4 times the pitch circle diameter.

22.3 Location of reinforcement

The reinforcement shall be located so that the thickness of the sheath over the reinforcement constitutes not less than 50 percent nor more than 80 percent of the total reinforced sheath thickness.

23 CONSTRUCTION AND DIMENSIONS (all cables)

The construction and dimensions of all cables shall be as specified in Figures 3 to 10 and Tables 9 to 16, as appropriate.

TABLE 6
TESTS AND CRITERIA FOR SEMICONDUCTIVE ELASTOMER
CRADLE SEPARATORS, COVERING ON EARTH CONDUCTORS
AND SCREEN FOR CORE ASSEMBLY

1	2	3	4
Test*	Pass criteria	Category of test	Reference for test method
A Mechanical tests without ageing on conditioned specimens:		Type	AS/NZS 1660.2.1
1 Tensile strength, minimum (MPa)	8.5		
2 Elongation at rupture, minimum (%)	200		
B Hot set test:		Sample	AS/NZS 1660.2.2
Duration—15 min			
Temperature—200 ±3 °C			
Load—200 kPa			
1 Elongation under load, maximum (%)	175		
2 Residual elongation after cooling, maximum (%)	20		
C Mechanical test after ageing in an oven:		Type	AS/NZS 1660.2.2
Duration—240 h			
Temperature—120 ±3°C			
1 Tensile strength, actual minimum (MPa)	6.2		
2 Elongation at rupture, actual minimum (%)	50		
D Electrical tests:			
Volume resistivity, at 23 ±3°C (Ω.m)	1.0 max.	Type	Appendix C

* Due to difficulty of sample preparation, tests may be made on pressed sheets.

24 JOINTS IN COMPLETED CABLE LENGTHS

Except where specifically agreed between the purchaser and manufacturer, there shall be no joints permitted in a completed cable other than those specified in Clause 7.2 and 8.4.

25 TESTS

25.1 Testing—General requirements

Cable shall comply with Table 7.

Type testing of a cable of designated type, voltage rating and conductor size shall qualify all cables of the same type and voltage rating with conductor sizes larger than the tested cable and shall also qualify such cable in lower voltage ratings for the range of conductor sizes.

NOTE: Refer to Appendix A(k) for cables with smaller conductor sizes.

TABLE 7
TESTS—PASS CRITERIA, CATEGORY AND REFERENCE

1	2	3	4	5
Test No.	Test	Pass criteria	Category of test	Reference for test method
1	All appropriate tests with exception of resistance on conductors taken from the completed cable	As specified in AS/NZS 1125 for the appropriate conductor and Clause 7 herein		
2	Conductor examination and measurement of resistance including that of any composite screens	The conductor form, material and resistance shall comply with the appropriate requirements in AS/NZS 1125 (see Note 1) and Clauses 7, 8 and 12	Routine	AS/NZS 1660.1
3	All appropriate tests on insulation taken from the completed cable	As specified in AS/NZS 3808		
4	All appropriate tests on inner and outer sheath taken from the completed cable	As specified in AS/NZS 3808 for the relevant sheath designation		
5	Extensibility test on central pilot core (Types 209, 210, 241, 275 and 280B cable only)	A sample of pilot core taken from the completed cable shall be capable of withstanding an elongation of not less than 15% without any conductive components fracturing	Type	AS/NZS 1125 (method as for elongation test)
6	Tests on textile reinforced semiconductive conductor screen taken from the completed cable or laboratory prepared samples: (a) Measurement of volume resistivity (b) Measurement of thickness (where not in combination with semiconductive elastomer screen)	500 Ω .m max. at 23 \pm 3°C As specified in Clause 9.5.2	Type Sample	AS/NZS 1660.3 —
7	Tests on elastomeric semiconductive conductor screen taken from the completed cable or laboratory prepared samples: (a) Measurement of volume resistivity (b) Elongation at rupture after ageing: Duration—168 h Temperature—100 \pm 3°C minimum (%) (c) Measurement of thickness	200 Ω .m max. at 23 \pm 3°C 100 As specified in Clause 9.5	Type Type Sample	AS/NZS 1660.3 AS/NZS 1660.2.2 (Method as for insulation) AS/NZS 1660.2.1
8	Measurement of thickness of insulation or covering taken from the completed cable	Compliance with Clauses 10.3 and 15.3	Sample	AS/NZS 1660.2.1 and Clause 25.2

(continued)

TABLE 7 (continued)

1	2	3	4	5
Test No.	Test	Pass criteria	Category of test	Reference for test method
9	Tests on elastomeric semiconductive insulation screen:			
	(a) Measurement of volume resistivity	200 Ω .m max. at 23 \pm 3°C	Type	AS/NZS 1660.3
	(b) Elongation at rupture after ageing: Duration—168 h Temperature—100 \pm 3°C minimum (%)	100	Type	AS/NZS 1660.2.2 (method as for insulation)
	(c) Strippability for hand-strippable elastomeric screen	The strip shall be capable of being peeled from the insulation without tearing in two and without leaving semiconductive material which cannot be readily removed.	Sample	AS/NZS 1660.2.5
	(d) Adhesion test for hand strippable elastomeric screen NOTE: Pre-treatment by heating may be required to strip material from insulation	The force to remove shall be not more than 125 N	Sample	AS/NZS 1660.2.5
	(e) Measurement of thickness	Compliance with Clause 12.2.3	Sample	AS/NZS 1660.2.1 and Clause 25.2
10	Tests on textile reinforced semiconductive insulation screen (Types 209, 240 and 260 cable only):			
	(a) Measurement of volume resistivity	500 Ω .m max. at 23 \pm 3°C	Type	AS/NZS 1660.3
	(b) Measurement of thickness	Compliance with Clause 12.3.2	Sample	—
11	Measurement of thickness of inner sheath	Compliance with Clause 19.3	Sample	AS/NZS 1660.2.1 and Clause 25.2
12	Measurement of armour dimensions	Compliance with Clause 20.1	Sample	AS/NZS 1660.1
13	Test for armour wires	Compliance with AS/NZS 3863	Type	AS/NZS 3863
14	Measurement of thickness of outer sheath	Compliance with Clause 21.4	Sample	AS/NZS 1660.2.1 and Clause 25.2
15	Needle penetration test:	Compliance with Clause 25.4		
	(a) Complete cable (Types 241, 245, 275 and 280B only)		Routine	Clause 25.4
	(b) Cradle separator (Types 209, 210, 240 and 260 only)		Sample	Clause 25.4

(continued)

TABLE 7 (continued)

1	2	3	4	5
Test No.	Test	Pass criteria	Category of test	Reference for test method
16	Combustion propagation test (a) Complete cable (see Notes 2 and 3) (b) Cradle separator or semiconductive covered earth conductor (Types 241, 245, 275 and 280B only) (c) Tests (a) and (b) above	The sample shall be self-extinguishing within 30 s of removal of the flame. After all burning has ceased, the surface of the sample shall be wiped clean and the charred or affected portion shall not extend to within 50 mm of the lower edge of the clamp fitted at the top. The sample shall be self-extinguishing within 60 s of removal of the flame and the total length of cable component burnt or charred shall not exceed 250 mm During the tests, no falling particle shall ignite the tissue paper underlay	Type	AS/NZS 1660.5.6
17	High voltage a.c. test for 5 min	No breakdown	Routine	Clause 25.3

NOTES:

- To correct the resistance for the short pitch of lay specified for Type 210 cables, the maximum resistance specified in AS/NZS 1125 shall be multiplied by a factor 1.02.
- Application to assessment of fire hazard* The test provides direct data on the likelihood of a single electric cable igniting and transmitting fire when exposed to a specified external ignition source. Fire, however, is a complex phenomenon and fire associated with a cable run is a function of the characteristics of the cable insulation material, the method of installation, and the environment in which it is used. Consequently, no single test can give a full assessment of the fire hazard under all conditions of fire that may apply. There must be a constant awareness of these interrelated factors and the effects of important variables in using this test to assess the fire hazard in any particular situation, e.g. with coiled cables, special installation precautions may have to be taken as it cannot be assumed that a bunch of cables (e.g. when coiled) will behave in the same way as a single cable.
- Reporting of results* When reporting the results, the following cautionary note shall be added:
Individual items of the test report should not be quoted in isolation as proof of product acceptability nor applied to directly assess performance under conditions other than as envisaged by the reference specification, e.g. individual fire tests to prove an overall acceptable fire hazard level.

25.2 Thickness of insulation, covering and sheath

The thickness of core insulation, covering, semiconductive elastomer core screens (if any) and inner sheath (if any) and outer sheath shall be determined by the method detailed in AS/NZS 1660.2.1.

To determine the average thickness of each such component, a representative specimen of cable shall have all conductors, composite screens (if any) and armour (if any) removed. The specimen shall be cut into a number of sections of equal size. The number of sections shall be not less than three. The exact number shall, however, be sufficient to provide a total of 18 measurements of all thicknesses on each component, such measurements being made at approximately equiangular displacements corresponding to the geometric minimum of the component. Examples of the places of measurement are shown in Figure 1.




FIGURE 1 EXAMPLES OF PLACES OF MEASUREMENT

Any semiconductive elastomer screen other than insulation screen (see Clause 17), reinforcement for core assembly (see Clause 18) or outer sheath reinforcement (see Clause 22) shall be considered to be part of the sheath. The average of all the 18 measurements for each component shall then be calculated and be taken as the 'thickness' of the component for the purposes of this Standard. The smallest value of the 18 measurements taken for each component shall be taken as the 'minimum thickness at any point' of the component for the purpose of this Standard.

25.3 High voltage a.c. test for 5 min on power cores and pilot conductors

The cable shall be subjected to the following voltage test. The voltage shall be applied between the phase conductor and the core earth screens or earth conductors, and between pilot/control conductors and core earth screens or earth conductors. The composite screens or earth conductors and any armour shall be earthed.

The test shall be at ambient temperature, with an alternating voltage having a frequency in the range 40 Hz to 62 Hz. Its waveform shall approximate to a sine curve and have both half cycles reasonably alike (see AS 1931). The value of the applied voltage shall be as specified in Table 8. The voltage shall be increased gradually and maintained at the full value for 5 min.

TABLE 8
HIGH VOLTAGE a.c. TEST VOLTAGES

1	2
Cable component or designation	Test voltage kV r.m.s.
(a) Cable component Pilot conductors including central pilot/control conductors (regardless of cable designation)	1
(b) Cable voltage designation, kV	
1.1/1.1	4.2
3.3/3.3	12
6.6/6.6	22
11/11	30

NOTE: The test voltages specified do not apply to cables terminated or fitted with plugs.

25.4 Needle penetration test

25.4.1 General

The purpose of this test is to ensure that the conductance of the semiconductive elastomer components and construction meet the requirements of this Standard.

This test does not apply to any semiconductive conductor screens, nor to the semiconductive insulation screens of Types 209, 240 and 260 cables.

25.4.2 Test voltage and circuit

For the tests specified in Clauses 25.4.3 and 25.4.4, the test voltage shall be 315 ± 5 V r.m.s. at 40 Hz to 62 Hz, in series with a resistance of $424 \pm 5 \Omega$ connected in the circuit.

25.4.3 Requirements for Types 209, 210, 240 and 260 cables

For this test, the length of test specimen is unimportant and can be as short as practicable.

The semiconductive cradle separator shall be removed from the cable and prepared for test as follows:

- (a) Types 209 and 210
remove the central pilot core and replace it with a tight-fitting copper rod.
- (b) Types 240 and 260
insert a bare copper spike, having a diameter of at least 1.2 mm, axially along the geometric centre of the cradle separator.

Approximately 60 s before application of the test voltage, a 1.2 mm diameter bare steel needle shall be pushed through the cradle separator. The needle shall be positioned approximately midway between the bare copper conductor, rod or spike (as appropriate) and the edge of the cradle as shown in Figure 2.

The test voltage shall be applied between the copper conductor, rod or spike and the bare steel needle. The current which flows after application of the test voltage shall be measured and shall reach an instantaneous value of at least 500 mA within 10 ms of being switched on.

If the time taken to reach the prescribed current flow exceeds 10 ms, two further tests may be made on portions of the cradle separator, taken 150 and 300 mm respectively from the

place of original measurement. If each of these additional tests produces a current flow of 500 mA within 10 ms, the cable shall be deemed to have passed this test.

NOTE: Consideration is being given to revising the needle test to relate more closely to protection requirements.




FIGURE 2 POSITION OF TEST NEEDLE

25.4.4 Requirements for Types 241, 245, 275 and 280B cable

The test voltage shall be applied between a power conductor and an adjacent earth conductor on a suitable sample length of complete cable.

A fault shall be created by means of a 1.2 mm diameter bare steel needle pushed perpendicularly through the outer sheath of the cable, the semiconductive elastomeric screen and into the power conductor. The conductivity of the semiconductive core/cradle separator/core assembly screen combination shall be such that the current which flows shall reach an instantaneous value of at least 500 mA within a time interval of 10 ms from the instant the needle makes contact with the power conductor.

Alternatively, the needle may be inserted approximately 60 s before the test voltage is applied, in which case the time interval and current flow are determined from the instant the voltage is switched on.

If the time to reach the prescribed current flow exceeds 10 ms on any one core, two further tests shall be performed on each of the remaining two power cores. If each of these additional tests produces a current flow of 500 mA minimum within 10 ms, the cable shall be deemed to have passed this test.

26 MARKING (all cables)

26.1 Internal

All cables shall be durably and legibly marked with the manufacturer’s name or registered trademark, numbers to indicate the year of manufacture, and voltage designation (see Clause 4). The marking shall consist of printing on one or more cores or of printing on a non-hygroscopic tape and shall appear throughout the entire length of the cable at length intervals of not more than the following:

- (a) For cables incorporating power conductors of 16 mm² nominal cross-sectional area or larger 1 m.
- (b) For cables incorporating power conductors less than 16 mm² nominal cross-sectional area.....300 mm.

26.2 External

Cables shall be durably and legibly marked on the external sheath by pressed lettering or other durable means and numbers at length intervals not greater than 10 m. The letters and

numbers shall have a nominal height of 6 mm and, where pressed lettering is used, with a depth not less than 0.4 mm or more than 0.8 mm. The following information shall be marked:

- (a) A registered name or registered mark which enables the manufacturer or supplier to be identified.
- (b) Designation of insulation and sheath.
- (c) The type number of the cable and, except for Types 210, 275 and 280B, the voltage designation, e.g. Type 209.11 (see Tables 9 to 16 inclusive).
- (d) Year of manufacture.
- (e) Cross-sectional area of main conductor.

26.3 Marking of cable drums

Every drum of cable shall be durably and legibly marked with the following information:

- (a) A registered name or registered mark which enables the manufacturer or supplier to be identified.
- (b) Drum reference number.
- (c) Order number.
- (d) Cable type number and voltage rating.
- (e) Length of cable, in metres.
- (f) Gross mass of cable including drum, in kilograms.
- (g) Size of main conductors, in square millimetres.
- (h) Specified maximum resistance of pilot/control conductor, where appropriate, in ohms per hundred metres.
- (i) Designation of insulation and sheath.


NOTE: Manufacturers making a statement of compliance with this Australian/New Zealand Standard on a product, packaging, or promotional material related to that product are advised to ensure that such compliance is capable of being verified.

27 FIGURES OF CONSTRUCTION AND TABLES OF DIMENSIONS

Figures 3 to 10 and Tables 9 to 16 give the construction and dimensions, respectively, of the following types of cable:

Type	Figure	Table
209	3	9
210	4	10
240	5	11
241	6	12
245	7	13
260	8	14
275	9	15
280B	10	16

TYPE 209 SECTIONAL DIAGRAM




Construction (from the centre outward)	Clause reference for requirements
Semiconductive elastomer cradle separator containing a central pilot core	8 and 14
Three power cores of equal cross-sectional area, each comprising— a conductor	7
a conductor screen for cable 3.3/3.3 kV and above insulation	9 10
a tape and composite screen for 1.1/1.1 kV cable, or insulation screen (semiconductive and composite) for cables 3.3/3.3 kV and above	11 and 12 12
The three power cores laid up around the cradle separator	16
Outer sheath of heavy duty elastomer that also fills the outer interstices of the laid-up core assembly	21
Optional sheath reinforcement (within sheath)	22

FIGURE 3 CONSTRUCTION OF TYPE 209—COMPOSITE SCREENED CABLE FOR GENERAL USE (EXCLUDING SHUTTLE CARS)

TABLE 9
DIMENSIONS OF TYPE 209—COMPOSITE SCREENED CABLE FOR
GENERAL USE (EXCLUDING SHUTTLE CARS)

1	2	3	4	5	6
Type	Voltage designation kV	Power conductor			Sheath thickness (t_s) mm
		Nominal cross-sectional area mm ²	Insulation thickness (t_i) mm	Composite screen strand size No./mm	
209.1	1.1/1.1	6	1.5	7/0.25	3.8
		10	1.5	7/0.25	3.8
		16	1.6	7/0.25	4.0
		25	1.6	7/0.25	4.3
		35	1.6	7/0.25	4.6
		50	1.7	7/0.25	5.0
		70	1.8	7/0.25	5.4
		95	2.0	7/0.25	6.0
		120	2.1	7/0.25	6.4
		150	2.3	7/0.25	6.9
		185	2.5	7/0.30	7.4
		240	2.8	7/0.30	8.2
209.3	3.3/3.3	16	3.0	7/0.25	5.3
		25	3.0	7/0.25	5.6
		35	3.0	7/0.25	5.9
		50	3.0	7/0.25	6.3
		70	3.0	7/0.25	6.6
		95	3.0	7/0.25	7.1
		120	3.0	7/0.30	7.4
		150	3.0	7/0.30	7.8
		185	3.0	7/0.40	8.2
		240	3.0	7/0.40	8.8
209.6	6.6/6.6	16	5.0	7/0.25	6.4
		25	5.0	7/0.25	6.7
		35	5.0	7/0.25	7.0
		50	5.0	7/0.25	7.3
		70	5.0	7/0.25	7.7
		95	5.0	7/0.30	8.1
		120	5.0	7/0.30	8.5
		150	5.0	7/0.40	8.9
		185	5.0	7/0.40	9.3
		240	5.0	7/0.40	9.9
209.11	11/11	25	7.6	7/0.25	8.1
		35	7.6	7/0.30	8.4
		50	7.6	7/0.30	8.7
		70	7.6	7/0.30	9.1
		95	7.6	7/0.40	9.6
		120	7.6	7/0.40	9.9
		150	7.6	7/0.40	10.3
		185	7.6	7/0.40	10.7
240	7.6	7/0.50	11.3		

TYPE 210 SECTIONAL DIAGRAM



Construction (from the centre outward)	Clause reference for requirements
Semiconductive elastomer cradle separator containing a central pilot core	8 and 14
Three power cores of equal cross-sectional area, each comprising— a conductor insulation a tape and composite screen	7 10 11 and 12
The three power cores laid up around the cradle separator	16
Outer sheath of heavy duty elastomer that also fills the outer interstices of the laid-up core assembly	21


FIGURE 4 CONSTRUCTION OF TYPE 210—COMPOSITE SCREENED CABLE FOR HAND-HELD BORING MACHINES
Voltage designation: 1.1/1.1 kV (see Note)

NOTE: Certain regulatory authorities limit the use of this cable to 250/250 V.

TABLE 10
DIMENSIONS OF TYPE 210

Power conductor			Sheath thickness (t_s) mm
Nominal cross-sectional area mm ²	Insulation thickness (t_i) mm	Composite screen strand size No./mm	
1.5	1.4	7/0.25	3.0
2.5	1.5	7/0.25	3.0

TYPE 240 SECTIONAL DIAGRAM




Construction (from the centre outward)	Clause reference for requirements
Semiconductive elastomer cradle separator	14
Three power cores of equal cross-sectional area, each comprising— a conductor a conductor screen for cable 3.3/3.3 kV and above insulation a tape and composite screen for 1.1/1.1 kV cable, or insulation screen (semiconductive and composite) for cables 3.3/3.3 kV and above	7 9 10 11 and 12 12
The three power cores laid up around the cradle separator	16
Three elastomer insulated and taped pilot conductors disposed one into each other of the outer interstices of the laid-up power core assembly	7, 10 and 11
Outer sheath of heavy duty elastomer that also fills the outer interstices of the laid-up core assembly	21
Optional sheath reinforcement (within sheath)	22

FIGURE 5 CONSTRUCTION OF TYPE 240—COMPOSITE SCREENED CABLE FOR GENERAL USE (EXCLUDING SHUTTLE CARS)

TABLE 11
DIMENSIONS OF TYPE 240—COMPOSITE SCREENED CABLE
FOR GENERAL USE (EXCLUDING SHUTTLE CARS)

1	2	3	4	5	6	7	8
Type	Voltage designation kV	Power conductor			Pilot conductor		Sheath thickness (t_s) mm
		Nominal cross-sectional area mm ²	Insulation thickness (t_i) mm	Composite screen strand size No./mm	Minimum number and nominal diameter of wires No./mm	Insulation thickness (t_i) mm	
240.1	1.1/1.1	6	1.5	7/0.25	15/0.30	1.0	3.8
		10	1.5	7/0.25	24/0.30	1.0	3.8
		16	1.6	7/0.25	39/0.30	1.0	4.0
		25	1.6	7/0.25	63/0.30	1.2	4.3
		35	1.6	7/0.25	87/0.30	1.2	4.6
		50	1.7	7/0.25	114/0.30		5.0
		70	1.8	7/0.25	36/0.67	1.2	5.4
		95	2.0	7/0.25	36/0.67	1.2	6.0
		120	2.1	7/0.25	39/0.67	1.4	6.4
		150	2.3	7/0.25	48/0.67	1.4	6.9
		180	2.5	7/0.30	63/0.67	1.4	7.4
		240	2.8	7/0.30	77/0.67	1.6	8.2
		300	3.0	7/0.40	98/0.67	1.6	8.8
240.3	3.3/3.3	16	3.0	7/0.25	39/0.30	1.4	5.3
		25	3.0	7/0.25	63/0.30	1.4	5.6
		35	3.0	7/0.25	87/0.30	1.4	5.9
		50	3.0	7/0.25	114/0.30	1.4	6.3
		70	3.0	7/0.25	36/0.67	1.4	6.6
		95	3.0	7/0.25	36/0.67	1.4	7.1
		120	3.0	7/0.30	39/0.67	1.6	7.4
		150	3.0	7/0.30	48/0.67	1.6	7.8
		185	3.0	7/0.40	63/0.67	1.8	8.2
		240	3.0	7/0.40	77/0.67	1.8	8.8
300	3.0	7/0.50	98/0.67	1.8	9.4		
240.6	6.6/6.6	16	5.0	7/0.25	39/0.30	1.4	6.4
		25	5.0	7/0.25	63/0.30	1.4	6.7
		35	5.0	7/0.25	87/0.30	1.6	7.0
		50	5.0	7/0.25	114/0.30	1.6	7.3
		70	5.0	7/0.25	36/0.67	1.6	7.7
		95	5.0	7/0.30	36/0.67	1.6	8.1
		120	5.0	7/0.30	39/0.67	1.8	8.5
		150	5.0	7/0.40	48/0.67	1.8	8.9
		185	5.0	7/0.40	63/0.67	1.8	9.3
		240	5.0	7/0.40	77/0.67	1.8	9.9
300	5.0	7/0.50	98/0.67	1.8	10.4		
240.11	11/11	25	7.6	7/0.25	63/0.30	2.0	8.1
		35	7.6	7/0.30	87/0.30	2.0	8.4
		50	7.6	7/0.30	114/0.30	2.0	8.7
		70	7.6	7/0.30	36/0.67	2.0	9.1
		95	7.6	7/0.40	36/0.67	2.0	9.6
		120	7.6	7/0.40	39/0.67	2.2	9.9
		150	7.6	7/0.40	48/0.67	2.2	10.3
		185	7.6	7/0.40	63/0.67	2.2	10.7
240	7.6	7/0.50	77/0.67	2.2	11.3		

TYPE 241 SECTIONAL DIAGRAM




Construction (from the centre outward)	Clause reference for requirements
Semiconductive elastomer cradle separator containing a central pilot core	8 and 14
Three power cores of equal cross-sectional area, each comprising—	
a conductor	7
a conductor screen for cable 3.3/3.3 kV and above	9
insulation	10
a semiconductive elastomer insulation screen	12
The three power cores laid up around the cradle separator	16
Three semiconductive elastomer covered earth conductors disposed one into each of the outer interstices of the laid-up power core assembly	7 and 15
Semiconductive elastomer filling and screen for laid-up core assembly	17
Reinforcement for core assembly	18
Outer sheath of heavy duty elastomer	21

FIGURE 6 CONSTRUCTION OF TYPE 241—SEMICONDUCTIVE SCREENED CABLE FOR GENERAL USE (EXCLUDING SHUTTLE CARS)

TABLE 12
DIMENSIONS OF TYPE 241—SEMICONDUCTIVE SCREENED CABLE
FOR GENERAL USE (EXCLUDING SHUTTLE CARS)

1	2	3	4	5	6	7
Type	Voltage designation kV	Power conductor		Earth conductor		Sheath thickness including the semi-conductive screen over core assembly (t_s) mm
		Nominal cross-sectional area mm ²	Insulation thickness (t_i) mm	Minimum number and nominal diameter of wires No./mm	Semi-conductive covering thickness (t_c) mm	
241.1	1.1/1.1	6	1.5	15/0.30	1.0	3.8
		10	1.5	24/0.30	1.0	3.8
		16	1.6	39/0.30	1.0	3.9
		25	1.6	63/0.30	1.0	4.2
		35	1.6	87/0.30	1.0	4.4
		50	1.7	114/0.30	1.0	4.9
		70	1.8	36/0.67	1.0	5.3
		95	2.0	36/0.67	1.0	5.8
		120	2.1	39/0.67	1.2	6.3
		150	2.3	48/0.67	1.2	6.7
		185	2.5	63/0.67	1.4	7.3
		240	2.8	77/0.67	1.4	8.0
		300	3.0	98/0.67	1.4	8.7
241.3	3.3/3.3	16	3.0	39/0.30	1.0	5.0
		25	3.0	63/0.30	1.0	5.3
		35	3.0	87/0.30	1.0	5.6
		50	3.0	114/0.30	1.2	6.0
		70	3.0	36/0.67	1.2	6.4
		95	3.0	45/0.67	1.2	6.8
		120	3.0	57/0.67	1.2	7.2
		150	3.0	77/0.67	1.2	7.6
		185	3.0	91/0.67	1.4	8.0
		240	3.0	112/0.67	1.4	8.6
241.6	6.6/6.6	16	5.0	39/0.30	1.4	6.1
		25	5.0	63/0.30	1.4	6.4
		35	5.0	87/0.30	1.4	6.7
		50	5.0	114/0.30	1.4	7.1
		70	5.0	36/0.67	1.4	7.4
		95	5.0	45/0.67	1.4	7.9
		120	5.0	57/0.67	1.4	8.3
		150	5.0	77/0.67	1.4	8.6
		185	5.0	91/0.67	1.4	9.0
		240	5.0	112/0.67	1.4	9.6
241.11	11/11	25	7.6	63/0.30	1.8	7.8
		35	7.6	87/0.30	1.8	8.1
		50	7.6	114/0.30	1.8	8.5
		70	7.6	36/0.67	1.8	8.9
		95	7.6	45/0.67	1.8	9.3
		120	7.6	57/0.67	1.8	9.7
		150	7.6	77/0.67	1.8	10.0
		185	7.6	91/0.67	1.8	10.4
240	7.6	112/0.67	1.8	11.0		

TYPE 245 SECTIONAL DIAGRAM



Construction (from the centre outward)	Clause reference for requirements
Semiconductive elastomer cradle separator containing three pilot/control cores	8 and 14
Three power cores of equal cross-sectional area, each comprising— a conductor a conductor screen for cable 3.3/3.3 kV cable only insulation a semiconductive elastomer insulation screen	7 9 10 12
The three power cores laid up around the cradle separator	16
Three semiconductive elastomer covered earth conductors disposed one into each of the outer interstices of the laid-up power core assembly	7 and 15
Semiconductive elastomer filling and screen for laid-up core assembly	17
Reinforcement for core assembly	18
Outer sheath of heavy duty elastomer	21


FIGURE 7 CONSTRUCTION OF TYPE 245—SEMICONDUCTIVE SCREENED CABLE FOR GENERAL USE (EXCLUDING SHUTTLE CARS)

TABLE 13
DIMENSIONS OF TYPE 245—SEMICONDUCTIVE SCREENED CABLE FOR GENERAL USE (EXCLUDING SHUTTLE CARS)

1	2	3		4		5		6		7	8
		Power conductor		Earth conductor		Semiconductive covering thickness (t_c)		Semiconductive cradle finger thickness (t_f)			
Type	Voltage designation kV	Nominal cross-sectional area mm ²	Insulation thickness (t_i) mm	Minimum number and nominal diameter of wires No./mm	Semiconductive covering thickness (t_c) mm	Semiconductive cradle finger thickness (t_f) mm	Sheath thickness including the semi-conductive screen over core assembly (t_s) mm				
245.1	1.1/1.1kV	16	2.0	39/0.30	1.8*	6.2	4.1				
		25	1.6	63/0.30	1.8*	5.8	4.2				
		35	1.6	87/0.30	1.4*	5.6	4.4				
		50	1.7	114/0.30	1.0	5.4	4.8				
		70	1.8	36/0.67	1.0	5.1	5.1				
		95	2.0	36/0.67	1.0	4.8	5.6				
		120	2.1	36/0.67	1.2	4.7	6.0				
		150	2.3	48/0.67	1.2	4.2	6.3				
		185	2.5	63/0.67	1.4	4.0	6.8				
		245.3	3.3/3.3kV	25	3.0	63/0.30	1.5*	5.4	5.2		
				35	3.0	87/0.30	1.0	5.2	5.4		
				50	3.0	114/0.30	1.0	5.0	5.7		
				70	3.0	36/0.67	1.2	4.7	6.0		
				95	3.0	45/0.67	1.2	4.4	6.4		
				120	3.0	57/0.67	1.2	4.3	6.7		
		150	3.0	77/0.67	1.2	3.9	7.0				
		185	3.0	91/0.67	1.4	3.8	7.4				

* Thickness of covering over earth built up to ensure cradle fingers meet the requirements of Clause 14.2.

TYPE 260 SECTIONAL DIAGRAM



Construction (from the centre outward)	Clause reference for requirements
Semiconductive elastomer cradle separator	14
Three power cores of equal cross-sectional area, each comprising—	
a conductor	7
a conductor screen for cable 3.3/3.3 kV and above	9
insulation	10
a tape and composite screen for 1.1/1.1 kV cable or	11 and 12
insulation screen (semiconductive and composite) for cables 3.3/3.3 kV and above	12
The three power cores laid up around the cradle separator	16
Three elastomer insulated and taped pilot conductors disposed one into each of the outer interstices of the laid-up power core assembly	7, 10 and 11
Inner sheath of heavy duty elastomer that also fills the outer interstices of the laid-up core assembly	19
Pliable armour	19
Outer sheath of heavy duty elastomer	21
Optional sheath reinforcement (within outer sheath)	22

FIGURE 8 CONSTRUCTION OF TYPE 260—COMPOSITE SCREENED AND PLIABLE ARMoured CABLE FOR GENERAL USE (EXCLUDING SHUTTLE CARS)

TABLE 14
DIMENSIONS OF TYPE 260—COMPOSITE SCREENED AND PLIABLE ARMoured CABLE FOR GENERAL USE (EXCLUDING SHUTTLE CARS)


1	2	3	4	5	6	7	8		9	10	
							Sheath thickness (t_s)				
Type	Voltage designation kV	Power conductor			Pilot conductor		Insulation thickness (t_i)		Sheath thickness (t_s)		Pliable armour, number, and nominal diameter of wires No./mm
		Nominal cross-sectional area mm ²	Insulation thickness (t_s) mm	Composite screen strand size No./mm	Minimum number and nominal diameter of wires No./mm	Insulation thickness (t_i) mm	inner mm	outer mm			
260.1	1.1/1.1	6	1.5	7/0.25	15/0.30	1.0	2.0	3.8	7/0.45		
		10	1.5	7/0.25	24/0.30	1.0	2.0	3.8	7/0.45		
		16	1.6	7/0.25	39/0.30	1.0	2.5	4.0	7/0.71		
		25	1.6	7/0.25	63/0.30	1.2	2.5	4.3	7/0.71		
		35	1.6	7/0.25	87/0.30	1.2	2.5	4.6	7/0.71		
		50	1.7	7/0.25	114/0.30	1.2	2.5	5.0	7/0.71		
		70	1.8	7/0.25	36/0.67	1.2	2.5	5.4	7/0.71		
		95	2.0	7/0.25	36/0.67	1.2	3.5	6.0	7/0.90		
		120	2.1	7/0.25	39/0.67	1.4	3.5	6.4	7/0.90		
		150	2.3	7/0.25	48/0.67	1.4	3.5	6.9	7/0.90		
260.3	3.3/3.3	16	3.0	7/0.25	39/0.30	1.4	2.5	5.3	7/0.71		
		25	3.0	7/0.25	63/0.30	1.4	2.5	5.6	7/0.71		
		35	3.0	7/0.25	87/0.30	1.4	3.5	5.9	7/0.90		
		50	3.0	7/0.25	114/0.30	1.4	3.5	6.3	7/0.90		
		70	3.0	7/0.25	36/0.67	1.4	3.5	6.6	7/0.90		
		95	3.0	7/0.25	36/0.67	1.4	3.5	7.1	7/0.90		
		120	3.0	7/0.30	39/0.67	1.6	3.5	7.4	7/0.90		
		150	3.0	7/0.30	48/0.67	1.6	4.5	7.8	7/1.25		
		185	3.0	7/0.40	63/0.67	1.8	4.5	8.2	7/1.25		
		240	3.0	7/0.40	77/0.67	1.8	4.5	8.8	7/1.25		
300	3.0	7/0.50	98/0.67	1.8	4.5	9.4	7/1.25				

(continued)

TABLE 14 (continued)

1	2	3	4	5	6	7	8		10		
							9				
Type	Voltage designation kV	Power conductor			Pilot conductor		Sheath thickness (t_s)		Pliable armour, number, and nominal diameter of wires No./mm		
		Nominal cross-sectional area mm ²	Insulation thickness (t_s) mm	Composite screen strand size No./mm	Minimum number and nominal diameter of wires No./mm	Insulation thickness (t_i) mm	inner mm	outer mm			
260.6	6.6/6.6	16	5.0	7/0.25	39/0.30	1.4	3.5	6.4	7/0.90		
		25	5.0	7/0.25	63/0.30	1.4	3.5	6.7	7/0.90		
		35	5.0	7/0.25	87/0.30	1.6	3.5	7.0	7/0.90		
		50	5.0	7/0.25	114/0.30	1.6	3.5	7.3	7/0.90		
		70	5.0	7/0.25	36/0.67	1.6	4.5	7.7	7/1.25		
		95	5.0	7/0.30	36/0.67	1.6	4.5	8.1	7/1.25		
		120	5.0	7/0.30	39/0.67	1.8	4.5	8.5	7/1.25		
		150	5.0	7/0.40	48/0.67	1.8	4.5	8.9	7/1.25		
		185	5.0	7/0.40	63/0.67	1.8	4.5	9.3	7/1.25		
		240	5.0	7/0.40	77/0.67	1.8	4.5	9.9	7/1.25		
		300	5.0	7/0.50	98/0.67	1.8	4.5	10.4	7/1.25		
		260.11	11/11	25	7.6	7/0.25	63/0.30	2.0	4.5	8.1	7/1.25
				35	7.6	7/0.30	87/0.30	2.0	4.5	8.4	7/1.25
				50	7.6	7/0.30	114/0.30	2.0	4.5	8.7	7/1.25
				70	7.6	7/0.30	36/0.67	2.0	4.5	9.1	7/1.25
95	7.6			7/0.40	36/0.67	2.0	4.5	9.6	7/1.25		
120	7.6			7/0.40	39/0.67	2.2	4.5	9.9	7/1.25		
		150	7.6	7/0.40	48/0.67	2.2	4.5	10.3	7/1.25		
		185	7.6	7/0.40	63/0.67	2.2	4.5	10.7	7/1.25		
		240	7.6	7/0.50	77/0.67	2.2	4.5	11.3	7/1.25		

TYPE 275 SECTIONAL DIAGRAM



Construction (from the centre outward)	Clause reference for requirements
Semiconductive elastomer separator containing a central pilot core	8 and 14
Three power cores of equal cross-sectional area, each comprising— a conductor insulation	7 10
The three power cores laid up around the cradle separator	16
Three semiconductive elastomer covered earth conductors disposed one into each of the outer interstice of the laid-up power core assembly	7 and 15
Semiconductive elastomer filling and screen for laid-up core assembly	17
Reinforcement for core assembly	18
Outer sheath of heavy duty elastomer	21


FIGURE 9 CONSTRUCTION OF TYPE 275—CIRCULAR a.c. SHUTTLE CAR CABLE
Voltage designation: 1.1/1.1 kV

TABLE 15

DIMENSIONS OF TYPE 275—CIRCULAR a.c. SHUTTLE CAR CABLE
Voltage designation: 1.1/1.1 kV

Power conductor		Earth conductor		Sheath thickness including the semiconductive screen over core assembly (t _s)
Nominal area	Insulation thickness (t _i)	Minimum number and nominal diameter of wires	Semi-conductive covering thickness (t _c)	
mm ²	mm	No./mm	mm	mm
16	1.6	57/0.30	1.0	3.8
25	1.6	54/0.40	1.0	4.0
35	1.6	75/0.40	1.0	4.3
50	1.7	99/0.40	1.0	4.7

TYPE 280B SECTIONAL DIAGRAM



Construction (from the centre outward)	Clause reference for requirements
Semiconductive elastomer cradle separator containing a central pilot core	8 and 14
Three power cores of equal cross-sectional area, each comprising— a conductor	7
insulation	10
textile reinforced semiconductive tape insulation screen	12
The three power cores laid up around the cradle separator	16
Three semiconductive elastomer covered earth conductors disposed one into each of the outer interstice of the laid-up power core assembly	7 and 15
Semiconductive elastomer filling and screen for laid-up core assembly	17
Reinforcement for core assembly	18
Outer sheath of heavy duty elastomer	21

FIGURE 10 CONSTRUCTION OF TYPE 280B—SEMICONDUCTIVE SCREENED CABLE FOR GENERAL USE (INCLUDING SHUTTLE CARS)
Voltage designation: 1.1/1.1 kV

TABLE 16
DIMENSIONS OF TYPE 280B—SEMICONDUCTIVE SCREENED
CABLE FOR GENERAL USE (INCLUDING SHUTTLE CARS)
Voltage designation: 1.1/1.1 kV

1	2	3	4	5
Power conductor		Earth conductor		Sheath thickness including the semiconductive screen over core assembly (t_s) mm
Nominal cross- sectional area mm ²	Insulation thickness (t_i) mm	Minimum number and nominal diameter of wires No./mm	Semi-conductive covering thickness (t_c) mm	
6	1.5	24/0.30	1.0	
10	1.5	36/0.30	1.0	3.8
16	1.6	57/0.30	1.0	3.8
25	1.6	54/0.40	1.0	4.1
35	1.6	75/0.40	1.0	4.4
50	1.7	99/0.40	1.0	4.8
70	1.8	36/0.67	1.0	5.2
95	2.0	36/0.67	1.0	5.8
120	2.1	39/0.67	1.2	6.2
150	2.3	51/0.67	1.2	6.7
185	2.5	63/0.67	1.4	7.2
240	2.8	77/0.67	1.4	8.0
300	3.0	98/0.67	1.4	8.6

APPENDIX A
PURCHASING GUIDELINES
(Informative)

A1 GENERAL

Australian/New Zealand Standards are intended to include the technical requirements for relevant products, but do not purport to comprise all the necessary provisions of a contract. This Appendix contains advice and recommendations on the information to be supplied by the purchaser at the time of enquiry or order.

A2 INFORMATION TO BE SUPPLIED BY THE PURCHASER

The purchaser should supply the following information at the time of enquiry and order.

- (a) The number of this Australian/New Zealand Standard, i.e. AS/NZS 1802.
- (b) The type of cable required and its intended use in relation to the nature of the mine, e.g. Type 209 for continuous miner, Type 275 for underground coal mine shuttle car.
- (c) The voltage designation of the cable (see Clause 4 and Table 1).
- (d) The nominal cross-sectional area.
- (e) The required maximum operating temperature of the cable due to ambient temperature and heating effect of current. If this is not known, the manufacturer should be informed of the maximum continuous current rating to be assigned to the cable and the maximum ambient temperature in which the cable will be used.
- (f) The type of outer sheath, e.g. PCP, CSP or CPE (see Clause 21.1).
- (g) Whether for Types 209, 240 and 260, reinforcement is required in the outer sheath (see Clause 22) and, if so, what type.
- (h) Whether for 3.3/3.3 kV and higher rated Types 209, 240 and 260, textile-reinforced semiconductive tape or semiconductive elastomer conductor and insulation screens are required.
- (i) For cables incorporating a central pilot conductor, the maximum required resistance per unit length of the conductor if the value specified in Clause 8 is too great for the particular end use of the cable.
- (j) What sample tests, if any, are required (see Clause 3.19 and Table 7).
- (k) Whether type tests are accepted for a cable of the same designated class, type and voltage as a cable which has been type tested, but which has a smaller conductor size than the cable which was previously type tested (refer Clause 25.1).
- (l) The total length and packing lengths required.
- (m) The mass of the cable, if required.
- (n) Nominal overall diameter of cable and tolerances.

APPENDIX B

DETERMINATION OF SHEATH THICKNESS AND PLIABLE ARMOUR
STRAND SIZE USING FICTITIOUS CALCULATION METHOD

(Normative)

B1 GENERAL

The basic concept of fictitious calculation of sheath thickness is given in AS/NZS 5000.1. However, because of the specialized nature of the cables specified in this Standard, a somewhat different method is used for this Standard and this is given below.

B2 METHOD**B2.1 Outer sheath**

The sheath thickness (t_s) specified in Tables 9 to 16 inclusive is calculated as follows:

B2.1.1 *For other than Type 210 up to and including 4 mm² conductor:*

$$t_s = 0.125D_f + 1.3 \text{ mm}$$

The calculated value (t_s) is then rounded off to one decimal place and is subject to a minimum value of 3.8 mm.

For Type 245 cables

$$\text{Thickness of sheath; } t_s = 0.115D_f + 1.3 \text{ mm}$$

D_f is the fictitious diameter over the laid-up core assembly and is calculated by the following equations:

(a) Types 209, 240 and 260, rated 1.1/1.1 kV only:

$$D_f = 1.16 (d_L + 2t_i + 3.5) + (d_L + 2t_i + 1.0)$$

(b) Types 209, 240 and 260, rated 3.3/3.3 kV and higher:

$$D_f = 1.16 (d_L + 2t_i + 5.5) + (d_L + 2t_i + 3.0)$$

(c) Type 241 (rated 1.1/1.1 kV only) and 280A:

$$D_f = 1.16 (d_L + 2t_i + 2.9) + (d_L + 2t_i + 0.4)$$

(d) Type 241, rated 3.3/3.3 kV and higher:

$$D_f = 1.16 (d_L + 2t_i + 4.5) + (d_L + 2t_i + 2.0)$$

(e) Type 275:

$$D_f = 1.16 (d_L + 2t_i + 2.5) + (d_L + 2t_i)$$

(f) Type 280B:

$$D_f = 1.16 (d_L + 2t_i + 2.7) + (d_L + 2t_i + 0.2)$$

(g) For Type 245 (rated at 1.1/1.1 kV):

$$D_f = 1.16 (d_L + 2t_i + 0.4 + t_f) + (d_L + 2t_i + 0.4)$$

(h) For Type 245 (rated at 3.3/3.3 kV):

$$D_f = 1.16 (d_L + 2t_i + 2.0 + t_f) + (d_L + 2t_i + 2.0)$$

where

d_L = the fictitious conductor diameter, in millimetres (see AS/NZS 5000.1)

t_f = the finger thickness in Table 13.

t_i = the thickness of power conductor insulation, in millimetres, specified in Tables 9 to 16.

NOTE: In (a), (b), (c), (d), (f), (g) and (h), above the constants 1.0, 3.0, 0.4, 2.0, 0.2, 0.4 and 2.0 constitute the fictitious dimensional allowance due to composite screen, conductor/insulation and composite screen, insulation screen, conductor and insulation screens and taped insulation screen respectively, and the constants 3.5, 5.5, 2.9, 4.5 and 2.7 constitute the sum of 2.5 mm (for the cradle finger thickness) plus the appropriate fictitious screen dimension described above. In (e), the constant 2.5 is the cradle finger thickness, in millimetres.

B2.1.2 For type 210 up to and including 4 mm² conductor:

The sheath thickness is 3.0 mm.

B2.2 Inner sheath and armour (Type 260 only)

The inner sheath thickness and the pliable armour strand size specified in Table 14 is determined from Table B1.

TABLE B1

THICKNESS OF INNER SHEATH AND SIZE OF PLIABLE ARMOUR STRAND

Calculated fictitious diameter (D_f) over the laid-up core assembly mm	Inner sheath thickness mm	Pliable armour strand size No./mm
≤20	2.0	7/0.45
>20 ≤35	2.5	7/0.71
>35 ≤50	3.5	7/0.90
>50	4.5	7/1.25

APPENDIX C
MEASUREMENT OF VOLUME RESISTIVITY
(Normative)

C1 SCOPE

This Appendix describes the method of measurement of volume resistivity of semiconductive elastomeric cradle separators, covering on earth conductors and semiconductive elastomeric screen for core assembly, using laboratory prepared samples.

C2 PROCEDURE

The procedure shall be as follows:

- (a) Press-cure a sheet (of uniform thickness) of the semiconductive material to achieve a degree of cross-linking not less than that which is achieved in a completed cable.
- (b) Prepare samples by cutting from the sheet narrow strips of uniform width and approximately 200 mm long.
- (c) To one face of the sample apply four silver-painted electrodes of width not less than 5 mm, as follows:
 - (i) Two potential electrodes not less than 50 mm apart.
 - (ii) One current electrode at least 25 mm beyond each potential electrode.

NOTE: Where a high degree of accuracy is not required, these tests may be carried out with only two electrodes, spaced at least 50 mm apart, for each test.

- (d) The measurement is carried out at a temperature of $23 \pm 3^\circ\text{C}$ using a.c. or d.c. voltage. The power of the test circuit shall not exceed 100 mW.

C3 CALCULATION

Volume resistivity shall be calculated as follows:

$$\rho = \frac{Rwt}{1000L}$$

where

- ρ = volume resistivity, in ohm metres
 R = measured resistance, ohms
 w = width of sample, in millimetres
 t = thickness of sample, in millimetres
 L = distance between potential electrodes, in millimetres.

NOTES

NOTES

Standards Australia

Standards Australia is an independent company, limited by guarantee, which prepares and publishes most of the voluntary technical and commercial standards used in Australia. These standards are developed through an open process of consultation and consensus, in which all interested parties are invited to participate. Through a Memorandum of Understanding with the Commonwealth government, Standards Australia is recognized as Australia's peak national standards body.

Standards New Zealand

The first national Standards organization was created in New Zealand in 1932. The Standards Council of New Zealand is the national authority responsible for the production of Standards. Standards New Zealand is the trading arm of the Standards Council established under the Standards Act 1988.

Australian/New Zealand Standards

Under an Active Co-operation Agreement between Standards Australia and Standards New Zealand, Australian/New Zealand Standards are prepared by committees of experts from industry, governments, consumers and other sectors. The requirements or recommendations contained in published Standards are a consensus of the views of representative interests and also take account of comments received from other sources. They reflect the latest scientific and industry experience. Australian/New Zealand Standards are kept under continuous review after publication and are updated regularly to take account of changing technology.

International Involvement

Standards Australia and Standards New Zealand are responsible for ensuring that the Australian and New Zealand viewpoints are considered in the formulation of international Standards and that the latest international experience is incorporated in national and Joint Standards. This role is vital in assisting local industry to compete in international markets. Both organizations are the national members of ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission).

Visit our Web sites

www.standards.com.au

www.standards.co.nz

This page has been left intentionally blank.