

Australian/New Zealand Standard™

**Reconstituted wood-based panels—
Specifications**

Part 3: Decorative overlaid wood panels



AS/NZS 1859.3:2017

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee TM-011, Engineered Timber Products. It was approved on behalf of the Council of Standards Australia on 29 August 2017 and by the New Zealand Standards Approval Board on 6 September 2017.
This Standard was published on 27 October 2017.

The following are represented on Committee TM-011:

Australian Building Codes Board
Australian Forest Products Association
Australian Timber Importers Federation
Australian Wood Panels Association
Building Research Association of New Zealand
Engineered Wood Products Association of Australasia
Forest and Wood Products Australia
Furntech-AFRDI
Glued Laminated Timber Association of Australia
Master Builders Australia
New Zealand Plywood Manufacturers Association
New Zealand Timber Industry Federation
Timber Design Society
University of Melbourne
Wood Processors and Manufacturers Association of New Zealand

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.saiglobal.com or Standards New Zealand web site at www.standards.govt.nz and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of Standards Australia or the New Zealand Standards Executive at the address shown on the back cover.

This Standard was issued in draft form for comment as DR AS/NZS 1859.3:2016.

Reconstituted wood-based panels— Specifications

Part 3: Decorative overlaid wood panels

COPYRIGHT

© The Crown in right of New Zealand, administered by the New Zealand Standards Executive

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, PO Box 1473, Wellington 6140.

ISBN 978 1 76035 934 8

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee TM-011, Engineered Timber Products, to supersede AS/NZS 1859.3:2005.

The objective of this Standard is to provide performance requirements and specifications for the manufacture and application of decorative overlaid wood panels. This Standard includes four types of decorative overlay applied to wood panel substrate.

This Standard is Part 3 of the AS/NZS 1859 series, dealing with reconstituted wood-based panel products, as follows:

- AS/NZS
- 1859 Reconstituted wood-based panels—Specifications
- 1859.1 Part 1: Particleboard
- 1859.2 Part 2: Dry process fibreboard
- 1859.3 Part 3: Decorative overlaid wood panels (this Standard)
- 1859.4 Part 4: Wet process fibreboard

The term ‘informative’ has been used in this Standard to define the application of the appendix to which it applies. An ‘informative’ appendix is only for information and guidance.

CONTENTS

| | <i>Page</i> |
|--|-------------|
| SECTION 1 SCOPE AND GENERAL | |
| 1.1 SCOPE..... | 4 |
| 1.2 APPLICATION | 4 |
| 1.3 REFERENCED DOCUMENTS..... | 4 |
| 1.4 DEFINITIONS..... | 5 |
| 1.5 CLASSIFICATION | 5 |
| SECTION 2 GENERAL REQUIREMENTS | |
| 2.1 DIMENSIONAL TOLERANCES..... | 6 |
| 2.2 APPEARANCE | 6 |
| 2.3 SUBSTRATE | 7 |
| 2.4 MARKING | 7 |
| SECTION 3 LOW PRESSURE MELAMINE | |
| 3.1 SCOPE OF SECTION | 8 |
| 3.2 RESISTANCE TO SURFACE ABRASION..... | 8 |
| 3.3 POROSITY..... | 8 |
| 3.4 STEAM RESISTANCE | 8 |
| 3.5 CRACKING RESISTANCE..... | 8 |
| 3.6 STAIN RESISTANCE..... | 8 |
| 3.7 SUPPLEMENTARY TESTS | 9 |
| SECTION 4 PVC FILM | |
| 4.1 SCOPE OF SECTION | 10 |
| 4.2 GLUE SPREAD..... | 10 |
| 4.3 BOND STRENGTH..... | 10 |
| 4.4 HEAT RESISTANCE..... | 10 |
| 4.5 MOISTURE RESISTANCE | 10 |
| 4.6 BOND DURABILITY | 10 |
| SECTION 5 PAPER FOILS | |
| 5.1 SCOPE OF SECTION | 11 |
| 5.2 GLUE SPREAD..... | 11 |
| 5.3 HEAT RESISTANCE..... | 11 |
| 5.4 MOISTURE RESISTANCE | 11 |
| 5.5 CROSSCUT..... | 11 |
| SECTION 6 WOOD VENEERS | |
| 6.1 GENERAL REQUIREMENTS..... | 12 |
| 6.2 GLUE SPREAD..... | 13 |
| 6.3 VENEER BOND STRENGTH | 13 |
| 6.4 VENEER BOND DURABILITY..... | 13 |
| APPENDICES | |
| A PURCHASING GUIDELINES..... | 15 |
| B STORAGE AND HANDLING OF DECORATIVE OVERLAID WOOD PANELS..... | 16 |
| C SELECTION AND APPLICATION OF SCREW FASTENERS..... | 18 |

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Australian/New Zealand Standard
Reconstituted wood-based panels—Specifications

Part 3: Decorative overlaid wood panels

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard specifies requirements for decorative overlaid wood panels. It includes four types of decorative overlay applied to wood panel substrate.

NOTES:

- 1 Appendix A lists information that should be supplied by the purchaser at the time of inquiry or order.
- 2 Appendix B describes recommended practices for the storage and handling of decorative overlaid wood panel.
- 3 Appendix C describes recommended practices for selection and application of screw fasteners.

1.2 APPLICATION

Decorative overlaid wood panels shall comply with Section 2 and the following sections, as applicable to type:

- (a) Direct-surfaced with thermosetting resins (termed low pressure melamine) Section 3.
- (b) PVC film Section 4.
- (c) Paper foils Section 5.
- (d) Wood veneers Section 6.

NOTE: This Standard is one of the series relating to particleboard and wet and dry process fibreboard. Decorative finishes may also apply to plywood (decorative wood veneers in particular) but this application is not covered by this Standard.

1.3 REFERENCED DOCUMENTS

The following documents are referred to in this Standard:

| | |
|--------|--|
| AS/NZS | |
| 1859 | Reconstituted wood-based panels—Specifications |
| 1859.1 | Part 1: Particleboard |
| 1859.2 | Part 2: Dry process fibreboard |
| 1859.4 | Part 4: Wet process fibreboard |
| 2924 | High pressure decorative laminates—Sheets made from thermosetting resins |
| 2924.1 | Part 1: Classification and specifications |
| 4266 | Reconstituted wood-based panels—Methods of testing |
| 4266.1 | Part 1: Base panels |
| 4266.2 | Part 2: Decorative overlaid panels |

1.4 DEFINITIONS

For the purpose of this Standard, the definitions below apply.

1.4.1 Layon

Sheet of material to be applied as an overlay.

1.4.2 Overtrim margin

The difference between the nominal dimensions of the sheet of particleboard or MDF and the actual dimensions.

1.4.3 Substrate

Base panel onto which lay-ons are applied.

1.5 CLASSIFICATION

Decorative overlaid wood panels shall be classified as follows:

- (a) *Low pressure melamine (LPM)* Manufactured by directly applying partially uncured amyloplast resin impregnated papers to one or both faces of wood panel substrates and achieving bonding and curing in the same process using heat and pressure but without the use of an adhesive.
- (b) *PVC film* Manufactured by roll laminating PVC film to one or both faces of wood panel substrates using an adhesive to bond the PVC film to the substrate.
- (c) *Paper foils* Manufactured by laminating paper foils to one or both faces of wood panel substrates using an adhesive to bond the foil to the substrate.
- (d) *Wood veneer* Manufactured by gluing wood veneers to both faces of wood panel substrates, using a suitable adhesive to match the performance of the substrate as specified in Section 6.

SECTION 2 GENERAL REQUIREMENTS

2.1 DIMENSIONAL TOLERANCES

When determined in accordance with AS/NZS 4266.1, the actual dimensions of substrate panels shall comply with the requirements of AS/NZS 1859, Parts 1, 2 and 4, as applicable.

NOTES:

- 1 Flatness requirements are only applicable to decorative overlaid panels at time of delivery from manufacturer. Numerous factors, including changes in temperature and relative humidity in storage and fabrication areas at building sites, may cause boards and panels to bow or twist irreversibly.
- 2 Care should be taken in specifying unbalanced overlaid panels, that is, panels laminated on one side only, or with significantly different overlays on each side. Supply of panels laminated on one side with PVC film, paper foils, or melamine should be agreed between buyer and supplier.

2.2 APPEARANCE

2.2.1 Defects

When inspected according to AS/NZS 4266.2, the surface layer of panels shall appear to be continuous. The following defects are permitted:

- (a) *Spots, dirt and similar surface defects* The admissible size of such defects is based on a maximum area equivalent to 1.0 mm²/m² of panel and is proportional to the panel size under inspection. The total admissible area of contamination may be concentrated in one spot or dispersed over an unlimited area of smaller defects provided Item (c) below is complied with.
- (b) *Fibres, hairs, scratches* The admissible area of defects is based on a maximum contaminated length equivalent to 10 mm²/m² of panel and is proportional to the panel size under inspection. The total admissible area of contamination may be concentrated in one spot or dispersed over an unlimited area of smaller defects provided Item (c) below is complied with.
- (c) *Combination of surface defects* When defect types described in Items (a) and (b) above occur in the same panel, then the maximum level for each of the two types of defect shall not exceed half of the level prescribed in Items (a) and (b) above.

NOTE: These permitted surface defects are consistent with requirements for high pressure decorative laminate according to AS/NZS 2924.1.

2.2.2 Faults

Faults not permitted include faults showing through from the substrate to the surface and air bubbles, blisters, craters or faults in the decorative layer.

2.2.3 Imperfections

Imperfections and sawing defects are permitted within the overtrim margin.

2.2.4 Colour, pattern and surface finish

If colour, pattern and surface finish are assessed against other standards or customer colour samples, assessment shall be made under the same conditions specified in Clause 2.2.1.

2.3 SUBSTRATE

All substrates used to manufacture decorative overlaid wood panels should comply with the requirements in AS/NZS 1859.1, AS/NZS 1859.2 and AS/NZS 1859.4, as applicable.

Alternatively, validation of properties for decorative overlaid products shall be tested in their final shape and form.

2.4 MARKING

Decorative overlaid wood panels shall be marked according to classification in accordance with Clause 1.5, or the appropriate product name that would indicate the overlay classification.

Packs or individual panels of decorative overlaid wood panels shall have the following information legibly attached at least once:

- (a) The manufacturer's name or registered mark.
- (b) Reference to this Standard, i.e. AS/NZS 1859.3.
- (c) Classification of overlay and type of substrate (i.e. MDF or particleboard) or brand name that would indicate the overlay classification and substrate type.
- (d) Classification of substrate, that is, the word 'Standard (STD)', or the letters 'MR', as appropriate to the product.
- (e) Identification of the face side on each sheet, where applicable.

NOTE: If relevant, the country of manufacture should be included in the marking label.

SECTION 3 LOW PRESSURE MELAMINE

3.1 SCOPE OF SECTION

This Section specifies limits of physical and mechanical properties of low pressure melamine (LPM) overlaid wood panels. Table 3.1 sets out the requirements covered by this Section.

3.2 RESISTANCE TO SURFACE ABRASION

When determined in accordance with AS/NZS 4266.2, the mean surface wear for solid colours shall be not less than 300 revolutions and, for printed patterns, not less than 40 revolutions.

3.3 POROSITY

When determined in accordance with AS/NZS 4266.2, the mean porosity rating shall be not greater than three.

3.4 STEAM RESISTANCE

When determined in accordance with AS/NZS 4266.2, the mean steam resistance rating shall be not greater than three.

3.5 CRACKING RESISTANCE

When determined in accordance with AS/NZS 4266.2, there shall be no visible cracks or micro cracks.

3.6 STAIN RESISTANCE

When determined in accordance with AS/NZS 4266.2, the stain resistance rating shall be not worse than two for any reagent.

TABLE 3.1
PROPERTY REQUIREMENTS FOR LOW PRESSURE
MELAMINE OVERLAID WOOD PANELS

| Property | Parameter examined | Test method AS/NZS 4266.2 | Units | Requirements |
|--------------------------------|---------------------|---------------------------|-------------|----------------------------|
| Appearance | Appearance | Section 2 | — | See Clause 2.2 |
| Resistance to surface abrasion | Abrasion resistance | Section 3 | Revolutions | Solid colour: ≥300 |
| | | | | Printed patterns: ≥40 |
| Porosity | Appearance | Section 5 | Rating | ≤3 |
| Steam resistance | Appearance | Section 6 | Rating | ≤3 |
| Cracking resistance | Appearance | Section 7 | — | No visible or micro cracks |
| Stain resistance | Appearance | Section 8 | Rating | ≤2 |

3.7 SUPPLEMENTARY TESTS

For certain applications, additional product testing may be required. If cure testing is requested, it shall be determined using one of the test methods listed in Table 3.2.

TABLE 3.2
PROPERTY REQUIREMENTS FOR CURE TESTING
OVERLAID WOOD PANELS

| Property | Parameter examined | Test method AS/NZS 4266.2 | Units | Requirements |
|---------------------|--------------------|------------------------------|--------|---|
| Resin cure Method 1 | Appearance | Section 4 | Rating | 2 to 4 |
| Resin cure Method 2 | Scratching | Section 4 | Load | Gloss finish ≥2 N Smooth finish ≥2 N Textured finish ≥4 N |

Accessed by ORION on 20 NOV 2017 (Document ownership not guaranteed when printed)

SECTION 4 PVC FILM

4.1 SCOPE OF SECTION

This Section specifies limits of physical and mechanical properties of PVC film overlaid wood panels. Table 4.1 sets out the requirements covered by this Section.

4.2 GLUE SPREAD

Glue spread shall be continuous over the whole surface.

4.3 BOND STRENGTH

When determined in accordance with AS/NZS 4266.2, the mean peel force shall be not less than 25 N.

4.4 HEAT RESISTANCE

When determined in accordance with AS/NZS 4266.2, the mean shrinkage shall be not greater than 0.5 mm.

4.5 MOISTURE RESISTANCE

When determined in accordance with AS/NZS 4266.2, there shall be no visible reduction in water volume.

4.6 BOND DURABILITY

When determined in accordance with AS/NZS 4266.2, bond durability is considered satisfactory if, on visual examination, there is no separation of the vinyl from the substrate.

TABLE 4.1
PROPERTY REQUIREMENTS FOR PVC FILM
OVERLAID WOOD PANELS

| Property | Parameter examined | Test method AS/NZS 4266.2 | Units | Requirements |
|---------------------|--------------------|---------------------------|-------|--------------|
| Bond strength | Peel force | Section 9 | N | ≥25 |
| Heat resistance | Shrinkage | Section 10 | mm | ≤0.5 |
| Moisture resistance | Water volume | Section 11 | — | No reduction |
| Bond durability | Visual | Section 14 | — | Pass |

S E C T I O N 5 P A P E R F O I L S

5.1 SCOPE OF SECTION

This Section specifies limits of physical and mechanical properties of paper foil overlaid wood panels. Table 5.1 sets out the requirements covered by this Section.

5.2 GLUE SPREAD

Glue spread shall be continuous over the whole surface.

5.3 HEAT RESISTANCE

When determined in accordance with AS/NZS 4266.2, the mean shrinkage shall be not greater than 0.5 mm.

5.4 MOISTURE RESISTANCE

When determined in accordance with AS/NZS 4266.2, there shall be no visible reduction in water volume.

5.5 CROSSCUT

When tested in accordance with AS/NZS 4266.2, the percentage of pieces having paper foils removed shall be not greater than 10.

TABLE 5.1
PROPERTY REQUIREMENTS FOR PAPER FOIL
OVERLAID WOOD PANELS

| Property | Parameter examined | Test method AS/NZS 4266.2 | Units | Requirements |
|---------------------|---------------------|------------------------------|------------|--------------|
| Heat resistance | Shrinkage | Section 10 | mm | ≤0.5 |
| Moisture resistance | Water volume | Section 11 | — | No reduction |
| Crosscut | Paper foils removed | Section 12 | Percentage | ≤10 |

S E C T I O N 6 W O O D V E N E E R S

6.1 GENERAL REQUIREMENTS

6.1.1 Veneer

The veneer shall comply with the following requirements (see Clause 6.1.3):

- (a) Each piece of veneer leaf shall be of sound timber, smoothly and tightly cut to a uniform thickness. Veneer thickness shall be 0.5 mm to 0.7 mm or as agreed between purchaser and supplier.

NOTE: Eucalyptus species often have gum veins and pin holes as an acceptable feature.

- (b) Veneer leaf moisture content shall be in the range of 6% to 12% prior to making up into lay-on and also prior to pressing onto the substrate.
- (c) Veneer leaf shall be cut such that the long edges or edges parallel to the grain are parallel and clean cut. Leaf shall be edge butt joined by suitable means to form a lay-on of the required grain pattern and dimensions.

NOTE: A veneer lay-on is made up of a number of pieces of veneer leaf, suitably matched for figure and colour according to purchaser requirements.

6.1.2 Panel forms

Veneer panels may be manufactured in various forms based on veneer grades and end use requirements, as specified in Table 6.1.

TABLE 6.1
WOOD VENEER PANEL FORMS

| Ordering code | Face veneer | Backing veneer |
|---------------|-------------|---|
| G1S/DGB | Face grade | Backing grade of same species but lower grade |
| G2S | Face grade | Face grade both sides of panel |
| BAMO | Face grade | Backing grade at manufacturer’s option |
| G1S | Face grade | Grade and species nominated by the customer |

LEGEND:
G1S/DGB = Good 1 side/Down grade back
G2S = Good 2 sides
BAMO = Backs at manufacturer’s option

6.1.3 Face grade veneers

In addition to the requirements in Clause 6.1.1, face grade veneers shall exclude the following:

- (a) Open joints.
- (b) Overlapping joints.
- (c) Splits.
- (d) Non-natural discolouration.
- (e) Any other faults detrimental to the finish and appearance of the surface.

NOTE: Natural cracks and holes are permitted in some exotic veneers and burls. These may require attention during finishing.

6.1.4 Backing grade veneers

Backing grade veneers may be of lower quality than face grade veneers. The following imperfections are permitted:

- (a) Minor open joints, overlaps, knots, knotholes, splits and mismatching.
- (b) Mild discolouration.
- (c) Natural blemishes such as gum veins and knots.
- (d) Other minor faults that do not impair the integrity of the veneer.

NOTE: Patching of open defects with a suitable filler of matching colour can be arranged subject to agreement between supplier and purchaser.

6.1.5 Adhesive

Adhesive used to bond the veneer to the substrate shall comply with the requirements of AS/NZS 4266.2 and with the bond durability requirements according to the substrate specified.

6.1.6 Construction

Veneered panels shall be constructed as follows:

- (a) Veneered panels shall be balanced, that is, generally the same species and thickness of veneer shall be applied to both sides.

There may be occasions where purchasers' requirements call for differing species on the face and back. These cases shall be subject to consultation and agreement between purchaser and supplier.

- (b) The grain of the veneer shall be generally parallel to the long edges of the panel. There will be exceptions to this according to purchasers' requirements, e.g. diagonal and cross grain panels. In these cases, grain direction should be the same on both sides where possible.

6.1.7 Finish

Where trimmed, edges shall be clean cut and square to the surface. Sanded finish shall be equivalent to 150 grit or higher.

NOTE: Unsanded and untrimmed veneer panels may be supplied subject to agreement between the purchaser and supplier.

6.2 GLUE SPREAD

Glue spread shall be continuous over the whole surface.

6.3 VENEER BOND STRENGTH

When determined in accordance with AS/NZS 4266.2, Veneer bond strength shall be considered satisfactory provided that—

- (a) failure occurs in the veneer; or
- (b) failure load exceeds requirements of Table 6.2.

6.4 VENEER BOND DURABILITY

When determined in accordance with AS/NZS 4266.2, Veneer bond durability is considered satisfactory if, on visual examination, there is no separation of the veneer from the substrate (see Table 6.2).

TABLE 6.2
PROPERTY REQUIREMENTS FOR WOOD VENEER PANELS

| Property | Parameter examined | Test method AS/NZS 4266.2 | Units | Requirements |
|------------------------|-------------------------|------------------------------|-------|------------------|
| Veneer bond strength | Visual and failure load | Section 13 | — | Pass and 0.6 MPa |
| Veneer bond durability | Visual | Section 14 | — | No separation |

APPENDIX A

PURCHASING GUIDELINES

(Informative)

A1 GENERAL

Australian/New Zealand Standards are intended to include the technical provisions necessary for the supply of products referred to in the particular Standard, but do not purport to comprise all the necessary provisions of a contract. This Appendix contains advice and recommendations on the information to be supplied by the purchaser at the time of inquiry or order.

Its aims are to avoid misunderstanding, and to result in the purchaser receiving satisfactory products and service.

NOTE: Where particular applications require improved tolerance values to those specified in Clause 2.1, then in such cases the specifier or purchaser should advise the supplier of these requirements and negotiate appropriate arrangements.

A2 INFORMATION TO BE SUPPLIED BY THE PURCHASER

The following particulars should be supplied in the sequence given below:

- (a) The substrate required (refer to AS/NZS 1859.1, AS/NZS 1859.2 and AS/NZS 1859.4, as applicable).
- (b) The type of decorative overlay required:
 - (i) LPM (see Section 3).
 - (ii) PVC film (see Section 4).
 - (iii) Paper foils (see Section 5).
 - (iv) Wood veneers (see Section 6).
- (c) Treatment required for the substrate, or performance of treated product (refer to AS/NZS 1859.1, AS/NZS 1859.2 and AS/NZS 1859.4, as applicable).
- (d) The following dimensions of the sheet, in millimetres:
 - (i) Thickness; and for flooring, the centre-to-centre spacing of supporting joists.
 - (ii) Length.
 - (iii) Width.
 - (iv) For cut-to-size sheets, thickness and dimension details.
- (e) Other special tolerances, if required.
- (f) The number of sheets in each size.
- (g) The place and time of delivery.
- (h) Packing requirements, e.g. pack mass limits (for unloading purposes).

Additional information may be required when ordering wood veneer overlaid products:

- (A) Name of veneer species.
- (B) Type of cut, e.g. crown cut, quarter cut, rotary cut.
- (C) Matching type, e.g. book match, slip match, random match.

APPENDIX B

STORAGE AND HANDLING OF DECORATIVE OVERLAID WOOD PANELS

(Informative)

B1 INTRODUCTION


Decorative overlaid wood panels require care in storage and handling. This Appendix makes recommendations on the storage and maintenance of panel material.

B2 RECOMMENDATIONS FOR STORAGE AND HANDLING


The following recommendations should be applied to maintain decorative overlaid wood panels in good order and condition:

- (a) The storage area should be protected from sun, rain and wind to minimize rapid changes in temperature and humidity. Open-sided sheds should not be regarded as dry stores.
- (b) All packs should be evenly supported at each end and at intervals of not more than 600 mm. Where packs are multiple stacked, all supports should be vertically aligned [see Figures B1(a) and B1(b)].
- (c) Should it be necessary to store in the open, decorative overlaid wood panels should be covered with a waterproof sheet, supported on battens laid on top of the pack allowing air to circulate around and over the pack. The cover sheet should protect both sides and ends to floor level and be tied to prevent lifting [see Figure B1(c)].
- (d) The stack should be kept dry and clear of the ground, and be placed so that it will not be exposed to mechanical damage.
- (e) Where packs are supported on bearers manufactured from decorative overlaid wood panels, care should be taken to ensure that surface water does not make contact with the bearers. Added care may be taken by supporting each bearer on natural timber packing (or other impervious material). The minimum thickness of packing should be 38.0 mm.
- (f) To avoid staining and fading, the sheets should not be exposed to the weather while awaiting installation.
- (g) The surface should be kept free of contaminants, e.g. dust, oil, and adhesives that will affect the overlaying of veneer, plastic laminate and other surface finishes.
- (h) Sheets should be installed in accordance with the manufacturer's instructions.
- (i) Small quantities of formaldehyde may be emitted from decorative overlaid wood panel sheets. Under normal conditions, atmospheric concentrations of formaldehyde will be well below recommended safe levels. If large quantities of decorative overlaid wood panels are stored together there may be a risk of formaldehyde build-up. Provision for ventilation in storage areas should prevent formaldehyde build-up.


Material safety data sheets, available from decorative overlaid wood panel manufacturers, should be consulted for further information.



(a) Incorrect storage method



(b) Correct storage method



(c) Temporary cover (tarpaulin)

FIGURE B1 RECOMMENDED STORAGE AND HANDLING OF DECORATIVE OVERLAID WOOD PANELS

APPENDIX C

SELECTION AND APPLICATION OF SCREW FASTENERS

(Informative)

C1 INTRODUCTION

Because of the homogeneous nature of decorative overlaid wood panel, the selection of screw fasteners requires care as to type and application. This Appendix makes recommendations for the selection and use of screws in decorative overlaid wood panels. To reduce the possibility of staining and discolouration of veneer surfaces, fasteners should be corrosion resistant including high quality galvanizing, stainless steel or aluminium.

C2 TAPERED WOOD SCREWS

Traditional tapered wood screws are not recommended for use in decorative overlaid wood panels (see Figure C1). Taper and partial threading decreases the holding power of this fastener, especially when it is used on, or near to, edges, which may result in splitting and delamination between the surfaces.




FIGURE C1 FASTENER TYPES USED IN WOOD PRODUCTS

C3 RECOMMENDED FASTENERS

The correct choice of fastener is most important for optimum screw holding power. Screws with parallel shank (core) and thread are superior and more desirable than tapered fasteners (see Figure C1).

NOTE: Screws with high overall thread diameter to core diameter have increased holding power over lesser diameter threads.

C4 FIXING METHOD

The technique of fixing screws into decorative overlaid wood panels is of importance, as an inferior technique may render the fittings (i.e. hinges, catches and other attachments) unserviceable.

When fitting items to decorative overlaid wood panels, consideration should be given to the following:

- (a) *Screw driving* Fasteners should be screwed down firmly without over-tightening.
NOTE: Over-tightening crushes the decorative overlaid wood panel’s structure and reduces screw-holding power.
- (b) *Pilot holes* For parallel-threaded fasteners, pilot holes are recommended, and should be drilled out to approximately 80% of the core diameter and a minimum of 2.0 mm beyond the screw penetration depth, board thickness permitting (see Figure C2).
- (c) *Fastener clearance* When attaching wood or other fixing to decorative overlaid wood panels, the screw fixing point clearance should be sufficient to prevent binding of the screw threads on the sides of the attachment. Figure C2 illustrates pilot hole depth and screw head clearance for thin and thick attachments.
- (d) *Fastener heads* The two basic types of fastener heads used to fix items to decorative overlaid wood panels are slotted head and recessed head (see Figure C1). Recessed head fasteners are preferred to slotted head fasteners when positive driving action and resistance to slip are required.




FIGURE C2 ATTACHMENT FIXING METHODS

NOTES

Standards Australia

Standards Australia is an independent company, limited by guarantee, which prepares and publishes most of the voluntary technical and commercial standards used in Australia. These standards are developed through an open process of consultation and consensus, in which all interested parties are invited to participate. Through a Memorandum of Understanding with the Commonwealth government, Standards Australia is recognized as Australia's peak national standards body.

Standards New Zealand

The first national Standards organization was created in New Zealand in 1932. The New Zealand Standards Executive is established under the Standards and Accreditation Act 2015 and is the national body responsible for the production of Standards.

Australian/New Zealand Standards

Under a Memorandum of Understanding between Standards Australia and Standards New Zealand, Australian/New Zealand Standards are prepared by committees of experts from industry, governments, consumers and other sectors. The requirements or recommendations contained in published Standards are a consensus of the views of representative interests and also take account of comments received from other sources. They reflect the latest scientific and industry experience. Australian/New Zealand Standards are kept under continuous review after publication and are updated regularly to take account of changing technology.

International Involvement

Standards Australia and Standards New Zealand are responsible for ensuring that the Australian and New Zealand viewpoints are considered in the formulation of international Standards and that the latest international experience is incorporated in national and Joint Standards. This role is vital in assisting local industry to compete in international markets. Both organizations are the national members of ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission).

Visit our web sites

www.standards.org.au

www.standards.govt.nz



GPO Box 476 Sydney NSW 2001
Phone (02) 9237 6000
Email mail@standards.org.au
Internet www.standards.org.au
SAI Global Customer Service
Phone 13 12 42
Email sales@saiglobal.com



PO Box 1473 Wellington 6011
Freephone 0800 782 632
Phone (04) 498 5990
Email enquiries@standards.govt.nz
Website www.standards.govt.nz

ISBN 978 1 76035 934 8

Printed in Australia

This page has been left intentionally blank.