

ASME B18.16.4-2008

Serrated Hex Flange Locknuts 90,000 psi (Inch Series)

AN AMERICAN NATIONAL STANDARD



The American Society of
Mechanical Engineers



Date of Issuance: October 7, 2008

This Standard will be revised when the Society approves the issuance of a new edition. There will be no addenda issued to this edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this document. Periodically, certain actions of the ASME B18 Committee may be published as Cases. Cases and interpretations are published on the ASME Web site under the Committee Pages at <http://cstools.asme.org> as they are issued.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Three Park Avenue, New York, NY 10016-5990

Copyright © 2008 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	iv
Committee Roster	v
Correspondence With the B18 Committee	vi
1 Scope	1
2 Comparison to ISO Standards.....	1
3 Terminology	1
4 Reference Standards	1
5 Dimensions	1
6 Serrations	1
7 Tops of Nuts	1
8 True Position of Hexagon to Tapped Hole	1
9 Countersink.....	1
10 Threads	3
11 Material and Hardness	3
12 Mechanical Requirements.....	3
13 Finish	4
14 Grade and Identification Marking	4
15 Inspection and Quality Assurance	4
16 Designation.....	4
17 Options	4
18 Workmanship	4
Tables	
1 Regular Serrated Flange Locknuts	2
2 Large Serrated Flange Locknuts	3
3 Proof Load and Torque Values	4

ASME B18.16.4-2008

Serrated Hex Flange Locknuts 90,000 psi (Inch Series)

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**



FOREWORD

This 2008 edition was approved by the American National Standards Institute on August 25, 2008, and designated as ASME B18.16.4-2008.

ASME B18 COMMITTEE

Standardization of Bolts, Nuts, Rivets, Screws, Washers, and Similar Fasteners

(The following is the roster of the Committee at the time of approval of this Standard.)

STANDARDS COMMITTEE OFFICERS

D. A. Clever, *Chair*
R. D. Strong, *Vice Chair*
R. L. Crane, *Secretary*

STANDARDS COMMITTEE PERSONNEL

V. Cartina , Continental-Aero	J. F. Koehl , <i>Contributing Member</i> , Spirol International Corp.
D. A. Clever , Deere & Co.	W. H. Kopke , ITW Shakeproof Assembly Components
A. P. Cockman , Ford Motor Co.	J. G. Langenstein , <i>Honorary Member</i> , Consultant
B. D. Burnside , <i>Alternate</i> , Ford Motor Co.	W. J. Lutkus , Heli-Coil Emhart
R. L. Crane , The American Society of Mechanical Engineers	D. A. McCrindle , Canadian Fasteners Institute
A. C. DiCola , Wrought Washer Co.	M. D. Prasad , <i>Contributing Member</i> , General Motors Corp.
B. A. Dusina , Federal Screw Works	S. Savoji , ITW Medalist
J. S. Foote , <i>Contributing Member</i> , Trade Association Management, Inc.	W. R. Schevey , <i>Contributing Member</i> , BGM Fastener Co., Inc.
D. S. George , ND Industries	W. R. Stevens , Ramco
J. Greenslade , Industrial Fasteners Institute	R. D. Strong , General Motors Corp.
J. J. Grey , <i>Contributing Member</i> , Fastener Consulting Services, Inc.	S. W. Vass , Consultant
B. Hasiuk , <i>Contributing Member</i> , Defense Supply Center Philadelphia	C. B. Wackrow , <i>Contributing Member</i> , MNP Corp.
A. Herskovitz , Consultant	W. K. Wilcox , Consultant
J. Jennings , <i>Contributing Member</i> , Naval Surface Warfare Center	C. B. Williamson , Fastenal Co.
	C. J. Wilson , Consultant
	R. B. Wright , <i>Contributing Member</i> , Wright Tool Co.
	J. G. Zeratsky , National Rivet and Manufacturing Co.

SUBCOMMITTEE 16 — LOCKNUTS

W. R. Stevens , <i>Chair</i> , Ramco	J. Jennings , Naval Surface Warfare Center
V. Cartina , <i>Vice Chair</i> , Continental-Aero	J. F. McCarrick , Defense Supply Center Philadelphia
A. P. Cockman , Ford Motor Co.	W. L. Sakowski , Account Managers LLC
B. A. Dusina , Federal Screw Works	D. F. Sharp , GMS Structural Engineers
M. A. Elmi , Caterpillar, Inc.	D. J. Soscia , Electric Boat Corp.
D. S. George , ND Industries	R. D. Strong , General Motors Corp.
J. Greenslade , Industrial Fasteners Institute	W. K. Wilcox , Consultant
J. J. Grey , Fastener Consulting Services, Inc.	C. B. Williamson , Fastenal Co.
	C. J. Wilson , Consultant

CORRESPONDENCE WITH THE B18 COMMITTEE

General. ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions, and attending Committee meetings. Correspondence should be addressed to:

Secretary, B18 Standards Committee
The American Society of Mechanical Engineers
Three Park Avenue
New York, NY 10016-5990

Proposing Revisions. Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

Proposing a Case. Cases may be issued for the purpose of providing alternative rules when justified, to permit early implementation of an approved revision when the need is urgent, or to provide rules not covered by existing provisions. Cases are effective immediately upon ASME approval and shall be posted on the ASME Committee Web page.

Requests for Cases shall provide a Statement of Need and Background Information. The request should identify the standard, the paragraph, figure or table number(s), and be written as a Question and Reply in the same format as existing Cases. Requests for Cases should also indicate the applicable edition(s) of the standard to which the proposed Case applies.

Interpretations. Upon request, the B18 Standards Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the B18 Standards Committee.

The request for an interpretation should be clear and unambiguous. It is further recommended that the inquirer submit his/her request in the following format:

Subject: Cite the applicable paragraph number(s) and the topic of the inquiry.
Edition: Cite the applicable edition of the Standard for which the interpretation is being requested.
Question: Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. The inquirer may also include any plans or drawings, which are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in this format may be rewritten in the appropriate format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not "approve," "certify," "rate," or "endorse" any item, construction, proprietary device, or activity.

Attending Committee Meetings. The B18 Standards Committee regularly holds meetings, which are open to the public. Persons wishing to attend any meeting should contact the Secretary of the B18 Standards Committee.

SERRATED HEX FLANGE LOCKNUTS 90,000 psi (INCH SERIES)

1 SCOPE

This Standard covers the general, dimensional, and mechanical performance requirements for low strength carbon steel, case hardened, regular and large serrated flange locknuts (inch series), recognized as American National Standard.

2 COMPARISON TO ISO STANDARDS

There is no inch series ISO standard for these products at this time.

3 TERMINOLOGY

For definitions of terms relating to fasteners or component features used in this Standard, refer to ASME B18.12.

4 REFERENCE STANDARDS

The following is a list of publications referenced in this Standard.

- ASME B1.1, Unified Inch Screw Threads
 ASME B1.3, Screw and Thread Gaging Systems for Dimensional Acceptability — Inch and Metric Screw Threads (UN, UNR, UNJ, M, and MJ)
 ASME B18.12, Glossary of Terms for Mechanical Fasteners
 ASME B18.18.2M, Inspection and Quality Assurance for High-Volume Machine Assembly Fasteners
 ASME Y14.5M, Dimensioning and Tolerancing
 Publisher: The American Society Of Mechanical Engineers (ASME), Three Park Avenue, New York, NY 10016-5990; Order Department: 22 Law Drive, P.O. Box 2300, Fairfield, NJ 07007-2300
- ASTM F 606, Test Methods for Determining the Mechanical Properties of Externally and Internally Threaded Fasteners, Washers, Direct Tension Indicators, and Rivets
 ASTM F 812, Specification for Surface Discontinuities of Nuts, Inch Series
 ASTM F 1941, Electrodeposited Coatings on Threaded Fasteners [Unified Inch Screw Threads (UN/UNR)]
 ASTM F 2282, Standard Specification for Quality Assurance Requirements for Carbon and Alloy Steel Wire, Rods, and Bars for Mechanical Fasteners

ASTM F 2328, Standard Test Method for Determining Decarburization and Carburization in Hardened and Tempered Threaded Steel Bolts, Screws, and Studs
 Publisher: ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959

5 DIMENSIONS

(a) Unless otherwise specified, all dimensions in this Standard shall be as specified in Tables 1 and 2, and sections 6 through 9. All dimensions in this Standard are in inches and apply before plating or coating is specified. When a plating or coating is specified, the finished product dimensions shall be agreed upon between the supplier and purchaser.

(b) Symbols specifying geometric characteristics are in accordance with ASME Y14.5M.

6 SERRATIONS

The configuration of the serrations shall be at the discretion of the manufacturer, provided the performance requirements as specified in para. 12.2 are met.

7 TOPS OF NUTS

Tops of nuts shall be flat and chamfered. The length of chamfer at hex corners shall be from 5% to 15% of the basic thread size. The surface may be slightly convex or rounded.


8 TRUE POSITION OF HEXAGON TO TAPPED HOLE

At maximum material condition (MMC), the axis of the hexagon shall be located at true position with respect to the axis of the thread pitch diameter within a tolerance zone having a diameter equivalent to 4% of the maximum width across flats.

9 COUNTERSINK


Tapped hole shall be countersunk on the bearing face and may be countersunk on the top. The maximum countersink diameter shall be the thread basic (nominal) major diameter plus 0.030 in. for $\frac{3}{8}$ in. nominal size nuts and smaller, and 1.08 times the basic major diameter for

Table 1 Regular Serrated Flange Locknuts



Nominal Size or Basic Major Diameter of Thread	Width Across Flats, <i>F</i>		Width Across Corners, <i>G</i>		Flange Diameter, <i>B</i>		Nut Thickness, <i>H</i>		Minimum Hex Height, <i>J</i>	Minimum Flange Thickness, <i>K</i>	Maximum Perpendicularity of Bearing Surface	
	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.				
No. 6	0.1380	0.312	0.302	0.361	0.342	0.422	0.408	0.171	0.156	0.10	0.02	0.014
8	0.1640	0.344	0.334	0.397	0.381	0.469	0.452	0.203	0.187	0.13	0.02	0.016
10	0.1900	0.375	0.365	0.433	0.416	0.500	0.480	0.219	0.203	0.13	0.03	0.017
12	0.2160	0.438	0.428	0.505	0.488	0.594	0.574	0.236	0.222	0.14	0.04	0.020
1/4	0.2500	0.438	0.428	0.505	0.488	0.594	0.574	0.236	0.222	0.14	0.04	0.020
5/16	0.3125	0.500	0.489	0.577	0.557	0.680	0.660	0.283	0.268	0.17	0.04	0.023
3/8	0.3750	0.562	0.551	0.650	0.628	0.750	0.728	0.347	0.330	0.23	0.04	0.025
7/16	0.4375	0.688	0.675	0.794	0.768	0.937	0.910	0.395	0.375	0.26	0.04	0.032
1/2	0.5000	0.750	0.736	0.866	0.840	1.031	1.000	0.458	0.437	0.31	0.05	0.035
9/16	0.5625	0.875	0.861	1.010	0.982	1.188	1.155	0.506	0.483	0.35	0.05	0.040
5/8	0.6250	0.938	0.922	1.083	1.051	1.281	1.248	0.569	0.545	0.40	0.05	0.044
3/4	0.7500	1.125	1.088	1.299	1.240	1.500	1.460	0.675	0.627	0.46	0.06	0.051

GENERAL NOTE: Dimensions are in inches.

Table 2 Large Serrated Flange Locknuts

Nominal Size or Basic Major Diameter of Thread	Width Across Flats, <i>F</i>		Width Across Corners, <i>G</i>		Flange Diameter, <i>B</i>		Nut Thickness, <i>H</i>		Minimum Hex Height, <i>J</i>	Minimum Flange Thickness, <i>K</i>	Maximum Perpendicularity of Bearing Surface	
	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.				
1/4	0.2500	0.438	0.428	0.505	0.488	0.728	0.700	0.312	0.281	0.15	0.04	0.024
5/16	0.3125	0.500	0.489	0.577	0.557	0.820	0.790	0.375	0.343	0.20	0.04	0.028
3/8	0.3750	0.562	0.551	0.650	0.628	0.915	0.885	0.406	0.390	0.24	0.04	0.031
7/16	0.4375	0.688	0.675	0.794	0.768	1.131	1.100	0.468	0.437	0.26	0.04	0.038
1/2	0.5000	0.750	0.736	0.866	0.840	1.205	1.175	0.515	0.485	0.29	0.06	0.041
9/16	0.5825	0.875	0.861	1.010	0.982	1.300	1.260	0.578	0.546	0.37	0.06	0.044
5/8	0.6250	0.938	0.922	1.083	1.051	1.360	1.280	0.640	0.600	0.42	0.06	0.045

GENERAL NOTE: All dimensions are in inches.

nuts larger than 3/8 in. No part of the threaded portion shall project beyond the bearing surface.

10 THREADS

Threads shall be Unified coarse or fine thread series (UNC or UNF series) Class 2B, in accordance with ASME B1.1.

Inspection shall be based on System 21 of ASME B1.3.

11 MATERIAL AND HARDNESS

Unless otherwise specified, nuts shall be manufactured from carbon steel in accordance with ASTM F 2282. The nuts shall have a case hardness of HR 15N 78-90 on the surface of the nut in accordance with ASTM F 2328. For referee purposes, case hardness shall be measured in the serrations.

12 MECHANICAL REQUIREMENTS

12.1 Proof Load Test

Nuts shall meet the proof load test using the values in Table 3. The proof load test procedure from ASTM F 606 shall be followed.

12.2 Break Loose Torque Test

Nuts shall have a break loose torque value equal to or greater than 100% of the seating torque value. The seating torque value shall be $\pm 10\%$ of the values listed in Table 3.

(a) *Procedure.* Place a test bolt through a cold-rolled steel strip and spacers as required. Assemble a test nut so that at least three thread pitches of the bolt extend beyond the top of the nut. While preventing the steel strip from rotating, apply the torque value listed in Table 3. Record the seating torque values, break the nut loose from its seated position, and record the highest

Table 3 Proof Load and Torque Values

Nut Size and Threads per inch	Proof Load, lb	Seating Torque	Nut Size and Threads per inch	Proof Load, lb	Seating Torque
6-32	820	50 in.-lb	6-40	900	55 in.-lb
8-32	1,250	60 in.-lb	8-36	1,350	65 in.-lb
10-24	1,650	70 in.-lb	10-32	1,800	75 in.-lb
12-24	2,200	90 in.-lb	12-28	2,300	95 in.-lb
1/4-20	2,900	9 ft.-lb	1/4-28	3,300	10 ft.-lb
5/16-18	4,700	14 ft.-lb	5/16-24	5,200	15 ft.-lb
3/8-16	7,000	27 ft.-lb	3/8-24	7,900	29 ft.-lb
7/16-14	9,550	40 ft.-lb	7/16-20	10,700	43 ft.-lb
1/2-13	12,800	62 ft.-lb	1/2-20	14,400	68 ft.-lb
9/16-12	16,400	82 ft.-lb	9/16-18	18,300	90 ft.-lb
5/8-11	20,300	125 ft.-lb	5/8-18	22,900	140 ft.-lb
3/4-10	30,000	240 ft.-lb	3/4-16	33,600	269 ft.-lb

GENERAL NOTE: Proof load values are based on 90,000 psi.

torque value. That value is the "break loose torque." A different unused test bolt, test nut, and hole in the test strip must be used for every test. The test bolt shall be prevented from turning during testing. Additional lubricant shall not be added.

(b) *Test Bolt.* The test bolt shall be plain finished with threads conforming to Class 2A tolerances as specified in ASME B1.1. The bolt shall have an ultimate tensile strength not less than the specified proof load of the nut to be tested. Bolt length shall be such that a minimum length equivalent to six thread pitches as measured from the end of the bolt will protrude through the nut when the nut is seated.

(c) *Test Strip.* The steel strip must be a minimum of 0.060 in. thick, having a hardness between HRB 60 and HRB 90. The strip must have holes for placing the bolt through that are 0.010 in. to 0.025 in. over the bolt's nominal thread diameter.

(d) *Torque Measuring Device.* Test results may be measured by an analog or digital device that is capable of indicating and holding a peak torque value. The analog or electronic measuring system shall have a certified accuracy of $\pm 2\%$ or less.

13 FINISH

Unless otherwise specified, nuts shall be furnished with an electrodeposited zinc-plated finish in accordance with ASTM F 1941, Fe/Zn 3A.

14 GRADE AND IDENTIFICATION MARKING

Unless otherwise specified by the purchaser, these nuts shall have no grade marking requirements. Nuts

1/4 in. and above in diameter shall be marked with the source identification marking.

15 INSPECTION AND QUALITY ASSURANCE

Unless otherwise specified by the purchaser, inspection of serrated flange locknuts shall be in accordance with ASME B18.18.2M.

16 DESIGNATION

Serrated hex flange locknuts shall be designated by the following data, preferably in the sequence as follows:

(a) product name and designation of standard (ASME B18.16.4)

(b) nominal diameter and thread pitch

(c) steel property class or material identification, and protective coating, if required.

EXAMPLE: Regular serrated flange locknut, ASME B18.16.4, 1/2-13, zinc plated per ASTM F 1941 Fe/Zn 3A.

17 OPTIONS

Options, where specified, shall be at the discretion of the manufacturer, unless otherwise agreed between manufacturer and purchaser.

18 WORKMANSHIP

Nuts shall be free of surface irregularities that might affect their serviceability, such as burrs, seams, laps, loose scale, and other irregularities. While control of surface discontinuities is important for the application intended, ASTM F 812 shall be specified by the purchaser.

B18 AMERICAN NATIONAL STANDARDS FOR BOLTS, NUTS, RIVETS, SCREWS, WASHERS, AND SIMILAR FASTENERS

Small Solid Rivets	B18.1.1-1972 (R2001)
Large Rivets	B18.1.2-1972 (R2001)
Metric Small Solid Rivets	B18.1.3M-1983 (R2001)
Square and Hex Bolts and Screws (Inch Series)	B18.2.1-1996
Square and Hex Nuts (Inch Series)	B18.2.2-1987 (R1999)
Metric Hex Cap Screws	B18.2.3.1M-1999
Metric Formed Hex Screws	B18.2.3.2M-2005
Metric Heavy Hex Screws	B18.2.3.3M-1979 (R2001)
Metric Hex Flange Screws	B18.2.3.4M-2001
Metric Hex Bolts	B18.2.3.5M-1979 (R2001)
Metric Heavy Hex Bolts	B18.2.3.6M-1979 (R2001)
Metric Heavy Hex Structural Bolts	B18.2.3.7M-1979 (R2001)
Metric Hex Lag Screws	B18.2.3.8M-1981 (R1999)
Metric Heavy Hex Flange Screws	B18.2.3.9M-2001
Square Head Bolts (Metric Series)	B18.2.3.10M-1996 (R2003)
Metric Hex Nuts, Style 1	B18.2.4.1M-2002
Metric Hex Nuts, Style 2	B18.2.4.2M-2005
Metric Slotted Hex Nuts	B18.2.4.3M-1979 (R2001)
Metric Hex Flange Nuts	B18.2.4.4M-1982 (R1999)
Metric Hex Jam Nuts	B18.2.4.5M-1979 (R2003)
Metric Heavy Hex Nuts	B18.2.4.6M-1979 (R2003)
Fasteners for Use in Structural Applications	B18.2.6-2006
Metric 12-Spline Flange Screws	B18.2.7.1M-2002
Clearance Holes for Bolt, Screws, and Studs	B18.2.8-1999
Socket Cap, Shoulder, and Set Screws, Hex and Spline Keys (Inch Series)	B18.3-2003
Socket Head Cap Screws (Metric Series)	B18.3.1M-1986 (R2002)
Metric Series Hexagon Keys and Bits	B18.3.2M-1979 (R2003)
Hexagon Socket Head Shoulder Screws (Metric Series)	B18.3.3M-1986 (R2002)
Hexagon Socket Button Head Cap Screws (Metric Series)	B18.3.4M-1986 (R2002)
Hexagon Socket Flat Countersunk Head Cap Screws (Metric Series)	B18.3.5M-1986 (R2002)
Metric Series Socket Set Screws	B18.3.6M-1986 (R2002)
Round Head Bolts (Inch Series)	B18.5-1990 (R2003)
Metric Round Head Short Square Neck Bolts	B18.5.2.1M-2006
Metric Round Head Square Neck Bolts	B18.5.2.2M-1982 (R2000)
Round Head Square Neck Bolts With Large Head (Metric Series)	B18.5.2.3M-1990 (R2003)
Wood Screws (Inch Series)	B18.6.1-1981 (R2003)
Slotted Head Cap Screws, Square Head Set Screws, and Slotted Headless Set Screws (Inch Series)	B18.6.2-1998
Machine Screws and Machine Screw Nuts	B18.6.3-2003
Thread Forming and Thread Cutting Tapping Screws and Metallic Drive Screws (Inch Series)	B18.6.4-1998
Metric Thread-Forming and Thread-Cutting Tapping Screws	B18.6.5M-2000
Metric Machine Screws	B18.6.7M-1999
General Purpose Semi-Tubular Rivets, Full Tubular Rivets, Split Rivets and Rivet Caps	B18.7-2007
Metric General Purpose Semi-Tubular Rivets	B18.7.1M-2007
Clevis Pins and Cotter Pins (Inch Series)	B18.8.1-1994 (R2000)
Taper Pins, Dowel Pins, Straight Pins, Grooved Pins, and Spring Pins (Inch Series)	B18.8.2-2000
Spring Pins: Coiled Type, Spring Pins: Slotted, Machine Dowel Pins: Hardened Ground, and Grooved Pins (Metric Series)	B18.8.100M-2000
Cotter Pins, Headless Clevis Pins, and Headed Clevis Pins (Metric Series)	B18.8.200M-2000
Plow Bolts	B18.9-2007
Track Bolts and Nuts	B18.10-1982 (R2000)
Miniature Screws	B18.11-1961 (R2000)
Glossary of Terms for Mechanical Fasteners	B18.12-2001
Screw and Washer Assemblies — Sems (Inch Series)	B18.13-1996 (R2003)
Screw and Washer Assemblies: Sems (Metric Series)	B18.13.1M-1998 (R2003)
Forged Eyebolts	B18.15-1985 (R2003)
Metric Lifting Eyes	B18.15M-1998 (R2004)

ASME B18.16.4-2008

Prevailing-Torque Type Steel Metric Hex Nuts and Hex Flange Nuts B18.16M-2004
 Serrated Hex Flange Locknuts 90,000 psi (Inch Series) B18.16.4-2008
 Inspection and Quality Assurance for General Purpose Fasteners B18.18.1-2006
 Inspection and Quality Assurance for High-Volume Machine Assembly Fasteners B18.18.2M-1987 (R1999)
 Inspection and Quality Assurance for Special Purpose Fasteners B18.18.3M-1987 (R1999)
 Inspection and Quality Assurance for Fasteners for Highly Specialized Engineered Applications B18.18.4M-1987 (R1999)
 Inspection and Quality Assurance Plan Requiring In-Process Inspection and Controls B18.18.5M-1998 (R2003)
 Quality Assurance Plan for Fasteners Produced in a Third Party Accreditation System B18.18.6M-1998 (R2003)
 Quality Assurance Plan for Fasteners Produced in a Customer Approved Control Plan B18.18.7M-1998 (R2003)
 Lock Washers (Inch Series) B18.21.1-1999
 Lock Washers (Metric Series) B18.21.2M-1999
 Metric Plain Washers B18.22M-1981 (R2000)
 Plain Washers B18.22.1-1965 (R2003)
 Part Identifying Number (PIN) Code System for B18 Fastener Products B18.24-2004
 Square and Rectangular Keys and Keyways B18.25.1M-1996 (R2003)
 Woodruff Keys and Keyways B18.25.2M-1996 (R2003)
 Square and Rectangular Keys and Keyways: Width Tolerances and
 Deviations Greater Than Basic Size B18.25.3M-1998 (R2003)
 Tapered and Reduced Cross Section Retaining Rings (Inch Series) B18.27-1998
 Helical Coil Screw Thread Inserts – Free Running and Screw Locking (Inch Series) B18.29.1-1993 (R2002)
 Helical Coil Screw Thread Inserts: Free Running and Screw Locking (Metric Series) B18.29.2M-2005
 Open-End Blind Rivets With Break Mandrels (Metric Series) B18.30.1M-2000
 Metric Continuous and Double-Ended Studs B18.31.1M-2005

The ASME Publications Catalog shows a complete list of all the Standards published by the Society. For a complimentary catalog, or the latest information about our publications, call 1-800-THE-ASME (1-800-843-2763).

ASME Services

ASME is committed to developing and delivering technical information. At ASME's Information Central, we make every effort to answer your questions and expedite your orders. Our representatives are ready to assist you in the following areas:

ASME Press
Codes & Standards
Credit Card Orders
IMEchE Publications
Meetings & Conferences
Member Dues Status

Member Services & Benefits
Other ASME Programs
Payment Inquiries
Professional Development
Short Courses
Publications

Public Information
Self-Study Courses
Shipping Information
Subscriptions/Journals/Magazines
Symposia Volumes
Technical Papers

How can you reach us? It's easier than ever!

There are four options for making inquiries* or placing orders. Simply mail, phone, fax, or E-mail us and an Information Central representative will handle your request.

Mail
ASME
22 Law Drive, Box 2900
Fairfield, New Jersey
07007-2900

Call Toll Free
US & Canada: 800-THE-ASME
(800-843-2763)
Mexico: 95-800-THE-ASME
(95-800-843-2763)
Universal: 973-882-1167

Fax—24 hours
973-882-1717
973-882-5155

E-Mail—24 hours
Infocentral@asme.org

* Information Central staff are not permitted to answer inquiries about the technical content of this code or standard. Information as to whether or not technical inquiries are issued to this code or standard is shown on the copyright page. All technical inquiries must be submitted in writing to the staff secretary. Additional procedures for inquiries may be listed within.

INTENTIONALLY LEFT BLANK

ASME B18.16.4-2008

ISBN-13 : 978-0-7918-3149-6

ISBN-10 : 0-7918-3149-3



9 780791 831496



M19308