

BS ISO 14793:2011



BSI Standards Publication

Road vehicles — Heavy
commercial vehicles and buses
— Lateral transient response
test methods

bsi.

...making excellence a habit.™

National foreword

This British Standard is the UK implementation of ISO 14793:2011. It supersedes BS ISO 14793:2003 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee AUE/15, Safety related to vehicles.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© BSI 2011

ISBN 978 0 580 72782 5

ICS 43.080.01; 43.080.20

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 March 2011.

Amendments issued since publication

Date	Text affected
------	---------------

INTERNATIONAL STANDARD

BS ISO 14793:2011

ISO
14793

Second edition
2011-02-15

Road vehicles — Heavy commercial vehicles and buses — Lateral transient response test methods

Véhicules routiers — Véhicules utilitaires lourds et autobus —
Méthodes d'essai de réponse transitoire latérale



Reference number
ISO 14793:2011(E)

© ISO 2011

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11 Fax + 41 22
749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents	Page
Foreword	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions	1
4 Principle	2
5 Reference system.....	2
6 Variables.....	3
7 Measuring equipment	3
7.1 Description.....	3
7.2 Transducer installation.....	3
7.3 Data processing.....	3
8 Test conditions.....	7
8.1 General	7
8.2 Test track.....	7
8.3 Weather conditions	7
8.4 Test vehicle.....	8
8.5 Warm-up.....	9
8.6 Test speed.....	9
8.7 Lateral acceleration.....	9
8.8 Average longitudinal acceleration.....	10
9 Step input.....	10
9.1 Test procedure.....	10
9.2 Data analysis.....	10
9.3 Data presentation	11
10 Sinusoidal input — One period (see ISO/TR 8725)	12
10.1 Test procedure.....	12
10.2 Data analysis.....	12
10.3 Data presentation	13
11 Random input (see ISO/TR 8726).....	13
11.1 Test procedure.....	13
11.2 Data analysis.....	14
11.3 Data presentation	14
12 Pulse input	15
12.1 Test procedure.....	15
12.2 Data analysis.....	15
12.3 Data presentation	15
13 Continuous sinusoidal input.....	16
13.1 Test procedure.....	16
13.2 Data analysis.....	16
13.3 Data presentation	17
Annex A (normative) Test report — General data	18
Annex B (normative) Test report — Presentation of results.....	24
Bibliography.....	29

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 14793 was prepared by Technical Committee ISO/TC 22, Road vehicles, Subcommittee SC 9, Vehicle dynamics and road-holding ability.

This second edition cancels and replaces the first edition (ISO 14793:2003), which has been technically revised.

Introduction

The main purpose of this International Standard is to provide repeatable and discriminatory test results.

The dynamic behaviour of a road vehicle is a very important aspect of active vehicle safety. Any given vehicle, together with its driver and the prevailing environment, constitutes a closed-loop system that is unique. The task of evaluating the dynamic behaviour is therefore very difficult since the significant interaction of these driver-vehicle-environment elements is each complex in itself. A complete and accurate description of the behaviour of the road vehicle must necessarily involve information obtained from a number of different tests.

Since this test method quantifies only one small part of the complete vehicle handling characteristics, the results of these tests can only be considered significant for a correspondingly small part of the overall dynamic behaviour.

Moreover, insufficient knowledge is available concerning the relationship between overall vehicle dynamic properties and accident avoidance. A substantial amount of work is necessary to acquire sufficient and reliable data on the correlation between accident avoidance and vehicle dynamic properties in general and the results of these tests in particular. Consequently, any application of this test method for regulation purposes will require proven correlation between test results and accident statistics.

Road vehicles — Heavy commercial vehicles and buses — Lateral transient response test methods

1 Scope

This International Standard specifies test methods for determining the transient response behaviour of heavy commercial vehicles, heavy commercial vehicle combinations, buses and articulated buses, as defined in ISO 3833 for trucks and trailers above 3,5 t and buses above 5 t maximum weight, and in UNECE (United Nations Economic Commission for Europe) and EC vehicle classification, categories M3, N2, N3, O3 and O4.

NOTE The open-loop manoeuvres specified in this International Standard are not representative of real driving conditions, but are nevertheless useful for obtaining measures of vehicle transient behaviour — particularly with respect to that which the driver experiences — in response to several specific types of steering input under closely controlled test conditions. For combinations where the response of the last vehicle unit is of importance, see ISO 14791.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1176:1990, Road vehicles — Masses — Vocabulary and codes

ISO 3833:1977, Road vehicles — Types — Terms and definitions

ISO/TR 8725:1988, Road vehicles — Transient open-loop response test method with one period of sinusoidal input

ISO/TR 8726:1988, Road vehicles — Transient open-loop response test method with pseudo-random steering input

ISO 8855:1991, Road vehicles — Vehicle dynamics and road-holding ability — Vocabulary

ECE Regulation No. 30, Uniform provisions concerning the approval of pneumatic tyres for motor vehicles and their trailers

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8855 and the following apply.

3.1

vehicle unit

unit of a vehicle combination which is connected with a yaw-articulation joint

EXAMPLE Tractor, semitrailer, dolly.

NOTE The number of vehicle units is one more than the number of articulation joints.

4 Principle

IMPORTANT — The method of data analysis in the frequency domain is based on the assumption that the vehicle has a linear response. Over the whole range of lateral acceleration this is unlikely to be the case, the standard method of dealing with such a situation being to restrict the range of the input so that linear behaviour can be assumed and, if necessary, to perform more than one test at different ranges of inputs which, together, cover the total range of interest.

The objective of these tests is to determine the transient response of a vehicle. Characteristic values and functions of both linear and nonlinear behaviour are considered necessary for fully characterizing vehicle transient response. Linear characteristic values and functions are determined with tests in the frequency domain and nonlinear characteristic values and functions with tests in the time domain. In the case of vehicle combinations, it is primarily the response of the first vehicle unit that is evaluated.

Important characteristics in the time domain are

- time lags between steering-wheel angle, lateral acceleration and yaw velocity,
- response times of lateral acceleration and yaw velocity (see 9.2.1),
- lateral acceleration gain (lateral acceleration divided by steering-wheel angle),
- yaw velocity gain (yaw velocity divided by steering-wheel angle), and
- overshoot values (see 9.2.3).

Important characteristics in the frequency domain are the transfer functions of

- lateral acceleration related to steering-wheel angle, and
- yaw velocity related to steering-wheel angle,

expressed as gain and phase functions between input and output variables.

There are several test methods for obtaining these characteristics in the time and frequency domains, as follows, the applicability of which depends in part on the size of the test track available.

- a) time domain:
 - 1) step input;
 - 2) sinusoidal input (one period).
- b) frequency domain:
 - 1) random input;
 - 2) pulse input;
 - 3) continuous sinusoidal input.

5 Reference system

The variables of motion used to describe the vehicle behaviour in a test-specific driving situation relate to the intermediate axis system (X, Y, Z) (see ISO 8855).

The location of the origin of the vehicle axis system (X_V , Y_V , Z_V) is the reference point and shall be thus defined.

6 Variables

The following variables shall be determined:

- yaw velocity, ψ ;
- lateral acceleration, a_Y ;
- steering-wheel angle, δ_H ;
- longitudinal velocity, v_X .

The following variables may be determined:

- lateral deviation, y ;
- roll angle at relevant points, ϕ ;
- steering-wheel torque, M_H ;
- sideslip angle, β .

These variables, all but lateral deviation defined in ISO 8855, are not intended to comprise a complete list.

7 Measuring equipment

7.1 Description

The variables to be determined in accordance with Clause 6 shall be measured by means of appropriate transducers. Their time histories shall be recorded on a multi-channel recording system having a time base.

The typical operating ranges and recommended maximum errors of the transducers and the recording system are given in Table 1.

7.2 Transducer installation

The transducers shall be installed so that the variables corresponding to the terms and definitions of ISO 8855 can be determined.

If the transducer does not measure the variable directly, appropriate transformations into the reference system shall be carried out.

7.3 Data processing

7.3.1 General

The frequency range relevant for this test is between 0 Hz and the maximum utilized frequency of $f_{\max} = 2$ Hz. Depending on the data processing method chosen (analog or digital data processing) the provisions of 7.3.2 or 7.3.3 shall be observed.

For lighter trucks it may be necessary to increase f_{\max} to 3 Hz. In this case, the following requirements concerning the frequency f_{\max} may be modified correspondingly.

7.3.2 Analog data processing

The bandwidth of the entire, combined transducer/recording system shall be no less than 8 Hz.

In order to execute the necessary filtering of signals, low-pass filters of order four or higher shall be employed. The width of the passband (from 0 Hz to frequency f_0 at -3 dB) shall be not less than 9 Hz. Amplitude errors shall be less than $\pm 0,5$ % in the relevant frequency range of 0 Hz to 2 Hz. All analog signals shall be processed with filters having phase characteristics sufficiently similar to ensure that time delay differences due to filtering lie within the required accuracy for time measurement.

NOTE During analog filtering of signals with different frequency contents, phase shifts can occur. Therefore, a digital data processing method, as described in 7.3.3, is preferable.

Table 1 — Variables, their typical operating ranges and recommended maximum errors

Variable	Range	Recommended maximum error of combined transducer and recorder system
Yaw velocity	$- 50^\circ/\text{s}$ to $+ 50^\circ/\text{s}$	$\pm 0,5^\circ/\text{s}$
Lateral acceleration	$- 15 \text{ m/s}^2$ to $+ 15 \text{ m/s}^2$	$\pm 0,15 \text{ m/s}^2$
Steering-wheel angle	$- 360^\circ$ to $+ 360^\circ$	$\pm 2^\circ$ for angles $< 180^\circ$ $\pm 4^\circ$ for angles $> 180^\circ$
Longitudinal velocity	0 m/s to 35 m/s	$\pm 0,35 \text{ m/s}$
Roll angle	$- 15^\circ$ to $+ 15^\circ$	$\pm 0,15^\circ$
Side slip angle	$- 10^\circ$ to $+ 10^\circ$	$\pm 0,3^\circ$
Lateral velocity	$- 10 \text{ m/s}$ to $+ 10 \text{ m/s}$	$\pm 0,1 \text{ m/s}$
Steering-wheel torque		
without power steering	$- 50 \text{ N}\cdot\text{m}$ to $+ 50 \text{ N}\cdot\text{m}$	$\pm 0,5 \text{ N}\cdot\text{m}$
with power steering	$- 20 \text{ N}\cdot\text{m}$ to $+ 20 \text{ N}\cdot\text{m}$	$\pm 0,2 \text{ N}\cdot\text{m}$
Transducers for some of the listed variables are not widely available and are not in general use. Many such instruments are developed by users. If any system error exceeds the recommended maximum value, this and the actual maximum error shall be stated under general data in the test report (see Annex A).		

7.3.3 Digital data processing

7.3.3.1 General considerations

Preparation of analog signals includes consideration of filter amplitude attenuation and sampling rate in order to avoid aliasing errors, and filter phase lags and time delays. Sampling and digitizing considerations include presampling amplification of signals so as to minimize digitizing errors, the number of bits per sample, the number of samples per cycle, sample and hold amplification, and timewise spacing of samples. Considerations for additional phaseless digital filtering include the selection of passbands and stopbands, and the attenuation and allowable ripple in each, as well as correction of anti-alias filter phase lags. Each of these factors shall be considered so that an overall data-acquisition accuracy of $\pm 0,5$ % is achieved.

7.3.3.2 Aliasing errors

In order to avoid uncorrectable aliasing, the analog signals shall be appropriately filtered before sampling and digitizing. The order of the filters used and their passband shall be chosen according to both the required flatness in the relevant frequency range and the sampling rate. The minimum filter characteristics and sampling rate shall be such that

- within the relevant frequency range of 0 Hz to $f_{\text{max}} = 2$ Hz the attenuation is less than the resolution of the data acquisition system, and
- at one-half the sampling rate (i.e. the Nyquist or “folding” frequency) the magnitudes of all frequency components of signal and noise are reduced to less than the system resolution.

For 12-bit data acquisition systems with a resolution of 0,05 % the filter attenuation shall be less than 0,05 % to 2 Hz, and the attenuation shall be greater than 99,95 % at all frequencies greater than one-half the sampling frequency.

NOTE For a Butterworth filter the attenuation is given by

$$A^2 = \frac{1}{1 + \left(\frac{f}{f_0} \right)^{2n}}$$

and

$$A^2 = \frac{1}{1 + \left(\frac{f}{f_N} \right)^{2n}}$$

where

- n is the order of the filter;
- f_{\max} is the relevant frequency range (2 Hz);
- f_0 is the filter cut-off frequency;
- f_N is the Nyquist or "folding" frequency;
- f_s is the sampling frequency = $2 \times f_N$

For example, for a fourth-order filter:

- for $A = 0,999\ 5$, $f_0 = 2,37 \times f_{\max} = 4,74$ Hz;
- for $A = 0,000\ 5$, $f_s = 2 \times (6,69 \times f_0) = 63,4$ Hz.

7.3.3.3 Phase shifts and time delays for anti-aliasing filtering

Excessive analog filtering shall be avoided, and all filters shall have sufficiently similar phase characteristics to ensure that time delay differences lie within the required accuracy for the time measurement.

Phase shifts are especially significant when measured variables are multiplied together to form new variables. This is because, while amplitudes multiply, phase shifts and associated time delays add. Phase shifts and time delays are reduced by increasing f_0 . Whenever equations describing the presampling filters are known, it is practical to remove their phase shifts and time delays by simple algorithms performed in the frequency domain.

NOTE In the frequency range in which the filter amplitude characteristics remain flat, the phase shift, ϕ , of a Butterworth filter can be approximated by

- $\phi = 81^\circ (f/f_0)$ for 2nd order,
- $\phi = 150^\circ (f/f_0)$ for 4th order,
- $\phi = 294^\circ (f/f_0)$ for 8th order.

The time delay for all filter orders is $t = (\phi/360^\circ) \times (1/f_0)$

7.3.3.4 Data sampling and digitizing

At 2 Hz the signal amplitude changes by up to 1,25 %/ms. To limit dynamic errors caused by changing analog inputs to 0,1 %, sampling or digitizing time shall be less than 80×10^{-6} s. All pairs or sets of data samples to be compared shall be taken simultaneously or over a sufficiently short time period.

In order not to exceed an amplitude error of 0,5 % in the relevant frequency range from zero to f_{\max} , the sampling rate, f_s , shall be at least $30 f_{\max}$.

7.3.3.5 Data acquisition system requirements

The data acquisition system shall have a resolution of 12 bits or more ($\pm 0,05$ %) and an accuracy of 2 LSB $\pm 0,1$ %. Anti-aliasing filters shall be of order four or higher and the relevant frequency range shall be from 0 Hz to f_{\max} .

For fourth-order filters, f_0 shall be greater than $2,37 f_{\max}$ if phase errors are subsequently adjusted in digital data processing, and greater than $5 f_{\max}$ otherwise; data sampling frequency f_s shall be greater than $13,4 f_0$.


For filters of orders other than the fourth order, f_0 and f_s shall be selected for adequate flatness and prevention of alias error.

Amplification of the signal before digitizing shall be such that in the digitizing process the additional error is less than 0,2 %. Sampling and digitizing time for each data channel sampled shall be less than 80×10^{-6} s.

7.3.3.6 Digital filtering

For filtering of sampled data in data evaluation, phaseless (zero-phase-shift) digital filters shall be used, in accordance with the following (see Figure 1):

- the passband shall range from 0 Hz to 2 Hz;
- the stopband shall begin at < 6 Hz;
- the filter gain in the passband shall be $1 \pm 0,005$ ($100 \pm 0,5$) %;
- the filter gain in the stopband shall be $\leq 0,01$ (≤ 1 %);
- the filter gain shall fall within the unshaded area of Figure 1.



- X frequency, in Hz
- Y filter gain
- a Passband.
- b Stopband.

Figure 1 — Required characteristics of phaseless digital filters

8 Test conditions

8.1 General

Limits and specifications for the ambient wind and vehicle test conditions in accordance with 8.3 and 8.4 shall be maintained throughout the test. Any deviations shall be shown in the test report (see Annex A), including the individual diagrams of the presentation of results (see Annex B).

8.2 Test track

All standard tests shall be carried out on a smooth, clean, dry and uniform paved road surface. The gradient of the paved surface shall not exceed 2,5 % in any direction when measured over any distance greater than or equal to the vehicle track. In addition, for tests concerned with damping of combination vehicles, the gradient of the test surface shall not exceed 1 % along the path of the vehicle as measured over any distance of 25 m or more. For each test the road surface conditions and paving material shall be recorded in the test report (see Annex A).

8.3 Weather conditions

During the measurements, ambient wind velocity shall not exceed 5 m/s.

For each test procedure, weather conditions shall be recorded in the test report (see Annex A).

Since, in certain cases, ambient temperature can have a significant influence on test results, it should be taken into account when making comparisons between vehicles.

8.4 Test vehicle

8.4.1 General data

Appropriate general data on the test vehicle or vehicle unit shall be presented in the test report in accordance with Annex A.

8.4.2 Tyres

For the standard test conditions, new tyres shall be fitted on the test vehicle according to the vehicle manufacturer's specifications. They shall have a tread depth of at least 90 % of the original value in the principal grooves within 0,75 of the tread breadth (in accordance with specifications for tread-wear indicators given in ECE Regulation No. 30), shall have been stored in accordance with the manufacturer's recommendation and shall not have been manufactured more than two years prior to the test. The date of manufacture shall be noted in the test report (see Annex A).

NOTE The tread breadth is the width of that part of the tread which, with the tyre correctly inflated, is in contact with the road in normal straight-line driving.

If not otherwise specified by the tyre manufacturer, the tyres shall be run in for at least 150 km on the test vehicle or an equivalent vehicle without excessively harsh use such as severe braking, acceleration, cornering or hitting the kerb. After running in, the tyres shall be maintained at the same position on the vehicle throughout the tests.

Tyres shall be inflated to the pressure specified by the vehicle manufacturer for the test vehicle configuration. The tolerance for setting the cold inflation pressure is ± 2 %.

Inflation pressure and tread depth before tyre warm-up and after completion of the test shall be recorded in the test report (see Annex A).

The tests may also be performed with tyres in any state of wear as well as with retreaded or regrooved tyres. The details shall be recorded in the test report (see Annex A). As tread depth or uneven tread wear can have a significant influence on test results, these should be taken into account when making comparisons between vehicles or between tyres.

8.4.3 Other operating components

For the standard test conditions, any operating component likely to influence the results of a test (e.g. shock absorbers, springs and other suspension components and suspension geometry) shall be as specified by the manufacturer. Any deviations from the manufacturer's specification shall be recorded in the test report (see Annex A).

Levelling systems of the chassis and cabin suspension which affect the response behaviour inappropriately should be disabled during steady-state and step-input tests.

8.4.4 Vehicle loading conditions

8.4.4.1 General

The maximum design total mass (Code: ISO-M07) and the maximum design axle load (Code: ISO-M12), in accordance with ISO 1176:1990, 4.7 and 4.12, shall not be exceeded.

The total weight and the centre-of-gravity position (longitudinal, lateral and vertical) can be expected to influence all test results. Moments of inertia can be expected to influence transient test results. For all tests, the total mass and the centre-of-gravity position in three dimensions should be reported for each vehicle unit, and for transient tests, the moment of inertia in yaw should also be reported. Moments of inertia in pitch and roll should be reported if available.

Alternatively, the loading condition of the vehicle shall be described adequately such that these parameters can be reproduced.

Care shall be taken to ensure that the masses, centre-of-gravity positions and moments of inertia of the test vehicle compare closely to those parameters of the vehicle in normal use. The resulting static wheel loads shall be determined and recorded in the test report (see Annex A).

8.4.4.2 Minimum loading condition

For the minimum loading condition, the total mass of the vehicle or combination shall consist of the complete vehicle kerb mass (Code: ISO-M06) in accordance with ISO 1176:1990, 4.6, plus the mass of the instrumentation. In the case of the first vehicle unit, the mass of the driver and, if applicable, the mass of an instrument operator or observer shall be added. The minimum loading condition is optional.

8.4.4.3 Maximum loading condition

For the maximum loading condition, the total mass of a fully laden vehicle or combination shall consist of the complete vehicle kerb mass plus the maximum load of interest (e.g. the legal limit) distributed such that none of the maximum axle loads is exceeded (see ISO 1176). The height of the centre of gravity and the mass distribution of the payload should be established to reflect the application of interest. The maximum loading condition is the standard test condition.

8.4.4.4 Other loading conditions

Other loading conditions, representing special transport conditions, are encouraged.

8.5 Warm-up

All relevant vehicle components shall be warmed up prior to the tests in order to achieve a temperature representative of normal driving conditions. Tyres shall be warmed up prior to the tests to achieve an equilibrium temperature and pressure representative of normal driving conditions.

To warm up the tyres, a procedure by driving at the test speed for a distance of at least 50 km or equivalent to driving 5 km at a lateral acceleration of 1 m/s^2 (left and right turn each) could be appropriate.

The tyre pressures after warm-up may be recorded.

8.6 Test speed


All tests shall be conducted at either 80 km/h, 90 km/h or 100 km/h, depending on the intended use of the vehicle, or at the maximum speed of the vehicle if it is less than 80 km/h. Other test speeds of interest may be used (preferably in 10 km/h steps).

For each test run, the average speed shall be maintained within a tolerance of $\pm 2 \text{ km/h}$ of the selected speed. A deviation of the vehicle speed of $\pm 3 \text{ km/h}$ from the selected speed is permissible.

8.7 Lateral acceleration

IMPORTANT — Stepwise increase of the lateral acceleration and the use of outriggers are strongly recommended in order to prevent rollover.

The lateral acceleration of the vehicle, or first vehicle unit in the case of combinations, shall be appropriate to the particular type of test. For linear tests, the lateral acceleration of all vehicle units shall be small enough to generate only linear vehicle behaviour. For nonlinear tests, the lateral acceleration shall be large enough to have the vehicle show nonlinear behaviour.



Key

- | | | | |
|---|-------------------------|---|-------------------|
| X | time | 3 | steady state |
| 1 | steering-wheel input | 4 | 90 % steady state |
| 2 | vehicle motion response | 5 | 50 % level |
| a | Response time. | | |
| b | Peak response time. | | |

Figure 2 — Response time and peak response time

9.3 Data presentation

9.3.1 General

General data shall be presented in accordance with Annex A.

9.3.2 Time histories

The time histories of variables used in data reduction shall be plotted. If a curve is fitted to any set of data, the method of curve fitting shall be described in the presentation of results in accordance with Annex B.

Plot the time histories of steering-wheel angle, lateral accelerations and yaw velocities for the selected lateral acceleration level, as shown in Figure B.1.

9.3.3 Time-response data summary

Record in accordance with Table B.1, as applicable, the means and standard deviation of the following variables for the selected test speed and the lateral acceleration level:

- a) steady-state yaw velocity response gain, $\left(\frac{\psi}{\delta} \right)_{H_{ss}}$;
- b) steady-state lateral acceleration response gain, $\left(\frac{a_y}{\delta} \right)_{H_{ss}}$;

13.3 Data presentation

13.3.1 General

General data shall be presented in accordance with Annex A.

Time histories of variables used in data reduction shall be plotted. If a curve is fitted to any set of data, the method of curve fitting shall be described in accordance with Annex B.

13.3.2 Frequency response functions

For each pair of input and output variables, mean values and standard deviations of the gain and phase angle shall be presented on a graph as a function of excitation frequency, as shown in Figure B.4. Similar graphs showing mean values and confidence intervals should also be made.

Annex A
(normative)

Test report — General data

A.1 Towing vehicle

A.1.1 Vehicle identification

Make, year, model, type:

Vehicle identification number:

Steering type:

Engine size: cm³

Optional equipment:

Axle 1 (front)

Suspension type:

Tyres

make:

size:

condition:

Number of wheels:

Track width: m

Rim:

Axle 2

Suspension type:

Tyres

make:

size:

condition:

Number of wheels:

Track width: m

Rim:

Axle 3

Suspension type:

Tyres

make:

size:

condition:

Number of wheels:
Track width: m
Rim:

Axle 4

Suspension type:

Tyres

make:
size:
condition:

Number of wheels:
Track width: m
Rim:

Tyre pressure

Cold: Axle 1: Axle 2: Axle 3: Axle 4: kPa

Hot

after warm-up: Axle 1: Axle 2: Axle 3: Axle 4: kPa

after test: Axle 1: Axle 2: Axle 3: Axle 4: kPa

Steering ratio (wheel angle/steering angle):

Axle 1:
Axle 2:
Axle 3:
Axle 4:

Distance between axles:

Axle 1–Axle 2: m
Axle 2–Axle 3: m
Axle 3–Axle 4: m

Distance between Axle 1 and front coupling: m

Distance between Axle 1 and rear coupling: m

Height of coupling (with trailer attached to the towing vehicle or the trailer in front): m

Other data (in particular relevant suspension settings):

.....
.....
.....
.....

A.1.2 Vehicle loading

Vehicle curb mass:

Axle 1 left wheel	kg	+	Right wheel	kg	=	kg	
Axle 2 left wheel(s)	kg	+	Right wheel(s)	kg	=	kg	
Axle 3 left wheel(s)	kg	+	Right wheel(s)	kg	=	kg	
Axle 4 left wheel(s)	kg	+	Right wheel(s)	kg	=	kg	
							Total	kg

Loading condition and location:

Vehicle mass as tested:

Axle 1 left wheel	kg	+	Right wheel	kg	=	kg	
Axle 2 left wheel(s)	kg	+	Right wheel(s)	kg	=	kg	
Axle 3 left wheel(s)	kg	+	Right wheel(s)	kg	=	kg	
Axle 4 left wheel(s)	kg	+	Right wheel(s)	kg	=	kg	
							Total	kg

Maximum permitted static load on the coupling of the towing vehicle: kg

Centre of gravity height: m

A.1.3 Test conditions

Test surface description:

Weather conditions

Temperature: °C

Wind velocity: m/s

Reference point for side slip angle and lateral velocity:

Test method chosen for evaluation

In the time domain:

In the frequency domain:

A.1.4 Test personnel

Driver:

Observer:

Data analyst:

A.1.5 General comments

.....
.....
.....
.....
.....

A.2 Semi- or full trailer

A.2.1 Vehicle identification

Make, year, model, type:

Vehicle number:

Axle 1 (front)

 Suspension type:

 Tyres

 make:

 size:

 condition:

 Number of wheels:

 Track width: m

 Rim:

Axle 2

 Suspension type:

 Tyres

 make:

 size:

 condition:

 Number of wheels:

 Track width: m

 Rim:

Axle 3

 Suspension type:

 Tyres

 make:

 size:

 condition:

 Number of wheels:

 Track width: m

 Rim:

Axle 4

Suspension type:

Tyres

make:

size:

condition:

Number of wheels:

Track width: m

Rim:

Tyre pressure

Cold: Axle 1: Axle 2: Axle 3: Axle 4: kPa

Hot

after warm-up: Axle 1: Axle 2: Axle 3: Axle 4: kPa

after test: Axle 1: Axle 2: Axle 3: Axle 4: kPa

Steering ratio (wheel angle/steering angle):

Axle 1:

Axle 2:

Axle 3:

Axle 4:

Distance between axles:

Axle 1–Axle 2 m

Axle 2–Axle 3 m

Axle 3–Axle 4 m

Distance between Axle 1 and front coupling: m

Distance between Axle 1 and rear coupling: m

Height of coupling (with trailer attached to the towing vehicle or the trailer in front): m

Other data (in particular relevant suspension settings):

.....
.....
.....
.....

A.2.2 Vehicle loading

Vehicle curb mass:

Axle 1 left wheel	kg	+	Right wheel	kg	=	kg	
Axle 2 left wheel(s)	kg	+	Right wheel(s)	kg	=	kg	
Axle 3 left wheel(s)	kg	+	Right wheel(s)	kg	=	kg	
Axle 4 left wheel(s)	kg	+	Right wheel(s)	kg	=	kg	
							Total	kg

Loading condition and location:

Vehicle mass as tested:

Axle 1 left wheel	kg	+	Right wheel	kg	=	kg	
Axle 2 left wheel(s)	kg	+	Right wheel(s)	kg	=	kg	
Axle 3 left wheel(s)	kg	+	Right wheel(s)	kg	=	kg	
Axle 4 left wheel(s)	kg	+	Right wheel(s)	kg	=	kg	
							Total	kg

Maximum permitted static load on the front coupling of the trailer (dolly): kg

Static load on the rear coupling of the trailer: kg

Maximum permitted static load on the rear coupling of the trailer (dolly): kg

Centre of gravity height: m

Annex B
 (normative)

Test report — Presentation of results

B.1 Step input


Test number:.....

$V_X = 80 \text{ km, } 90 \text{ km or } 100 \text{ km/h}$ |..... km/h


$a_Y = 3 \text{ m/s}^2$ |..... m/s²



$\delta_{H,ss}$ =
 50 % $\delta_{H,ss}$ =
 t_0 =



$a_{Y,ss}$ =
 90 % $a_{Y,ss}$ =
 $a_{Y,max}$ =
 T_{aY} =
 $T_{aY,max}$ =



ψ_{ss} =
 90 % ψ_{ss} =
 ψ_{max} =
 T_ψ =
 $T_{\psi,max}$ =

Figure B.1 — Step input — Time histories

Table B.1 — Step input — Response data summary

Parameter	Symbol	Unit	Left turn		Right turn	
			Mean value	Standard deviation	Mean value	Standard deviation
Steady-state yaw velocity response gain	$\left(\frac{\dot{\psi}}{\delta} \right)_{H,ss}$	s ⁻¹				
Lateral acceleration response time	T_{aY}	s				
Yaw velocity response time	T_{ψ}	s				
Lateral acceleration peak response time	$T_{aY,max}$	s				
Yaw velocity peak response time	$T_{\psi,max}$	s				
Overshoot value of lateral acceleration	U_{aY}	—				

Overshoot value of yaw velocity U_{ψ} —

B.2 Sinusoidal input

Test number:

$v_X = 80 \text{ km, } 90 \text{ km or } 100 \text{ km/h}$ | km/h

$a_Y = 3 \text{ m/s}^2$ | m/s²

$f = 0,2 \text{ Hz}$ | Hz




Figure B.2 — Sinusoidal input (one period) — Time histories

Table B.2 — Sinusoidal input (one period) — Response data summary

Parameter	Symbol	Unit	Left turn		Right turn	
			Mean value	Standard deviation	Mean value	Standard deviation
Time lag between steering-wheel angle and lateral acceleration	$T_{\delta - a}(\delta_H - \gamma)$					
Peak 1	$(\delta_H - \gamma)$					
	$T_{\delta - a}(\delta_H - \gamma)$	ms				
Peak 2	$(\delta_H - \gamma)^1$					
	$T_{\delta - a}(\delta_H - \gamma)^2$	ms				
Time lag between steering-wheel angle and yaw velocity	$T(\delta_H - \psi)$					
Peak 1	$T(\delta_H - \psi)$	ms				
Peak 2	$T(\delta_H - \psi)^1$					
	$T(\delta_H - \psi)^2$	ms				

Lateral acceleration gain a_Y (m/s²)/°

δ_H

Yaw velocity gain ψ s⁻¹

δ_H

B.3 Random/pulse¹⁾ input

Test number:

$v_X = 80 \text{ km/h, } 90 \text{ km/h or } 100 \text{ km/h}$ | km/h

$a_Y = 2 \text{ m/s}^2 \text{ or } 3 \text{ m/s}^2$ | m/s²




Figure B.3 — Random/pulse input — Harmonic content of steering-wheel angle


1) Delete as applicable.

B.4 Random/pulse/continuous²⁾ sinusoidal input

Test number:

$v_x = 80 \text{ km/h, } 90 \text{ km/h or } 100 \text{ km/h}$ |..... km/h

$a_y = 2 \text{ m/s}^2 \text{ or } 3 \text{ m/s}^2$ |..... m/s²



Variable ψ, a_y : Averaging function:
 Number of data sequences: Windowing function:
 Length of data sequences: Digitization rate:

Figure B.4 — Random/pulse/continuous sinusoidal input —
 Transient response to steering-wheel angle

2) Delete as applicable.

Bibliography

- [1] ISO 7401, Road vehicles — Lateral transient response test methods — Open-loop test methods
- [2] ISO 14791, Road vehicles — Heavy commercial vehicle combinations and articulated buses — Lateral stability test methods
- [3] EC Council Directive No. 92/53/EEC Annex II, Definition of vehicle categories and vehicle types
- [4] UNECE Regulation No. 13, Uniform provisions concerning the approval of vehicles of categories M, N and O with regard to braking

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With British Standards Online (BSOL) you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a BSI Subscribing Member.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a Multi-User Network Licence (MUNL) you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person

or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs

and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK



...making excellence a habit.™