


# INTERNATIONAL STANDARD

**Radio data system (RDS) –VHF/FM sound broadcasting in the frequency range  
from 64,0 MHz to 108,0 MHz –  
Part 9: RBDS – RDS variant used in North America**





**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2021 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembé  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

**About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

**About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

**IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

**IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

**IEC online collection - [oc.iec.ch](http://oc.iec.ch)**

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.



IEC 62106-9

Edition 1.0 2021-05

# INTERNATIONAL STANDARD

---

**Radio data system (RDS) –VHF/FM sound broadcasting in the frequency range  
from 64,0 MHz to 108,0 MHz –  
Part 9: RBDS – RDS variant used in North America**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 33.060.01; 33.160.20; 33.170

ISBN 978-2-8322-9785-8

**Warning! Make sure that you obtained this publication from an authorized distributor.**





## CONTENTS

FOREWORD .....	3
INTRODUCTION .....	5
1 Scope .....	6
2 Normative references .....	6
3 Terms, definitions and abbreviated terms .....	6
3.1 Terms and definitions .....	6
3.2 Abbreviated terms .....	7
4 Coding of information .....	7
4.1 General .....	7
4.2 Exceptions .....	7
4.2.1 PI coding .....	7
4.2.2 PTY coding .....	7
4.2.3 PS .....	7
Annex A (normative) PI coding for North America .....	8
A.1 General .....	8
A.2 Call letter conversion .....	8
A.2.1 Conversion method to be used .....	8
A.2.2 Examples of assigning PI codes from call letters .....	12
A.3 Application: receiver functionality to PI code assignments .....	13
A.4 Optional – modifying PI code for use with traffic information systems .....	14
A.5 PI codes for FM translators .....	14
Annex B (normative) PTY coding .....	16
Bibliography .....	19
Table A.1 – Letter to decimal value conversion .....	8
Table A.2 – PI code possibilities .....	10
Table A.3 – Nationally/regionally-linked radio stations code .....	11
Table A.4 – 3-letter only call signs .....	12
Table A.5 – Receiver checking method for PI 0x1 nibble 1 substitution .....	14
Table B.1 – Programme type codes and corresponding terms for display .....	16
Table B.2 – Definition of the terms used to denote programme type – PTY .....	17
Table B.3 – PTY code descriptions and abbreviations in Spanish .....	18

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

**RADIO DATA SYSTEM (RDS) –  
VHF/FM SOUND BROADCASTING IN THE FREQUENCY  
RANGE FROM 64,0 MHz TO 108,0 MHz –****Part 9: RBDS –  
RDS variant used in North America****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62106-9 has been prepared by technical area 1: Terminals for audio, video and data services and contents, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This first edition, together with IEC 62106-1, IEC 62106-2, IEC 62106-3, IEC 62106-4, IEC 62106-5, IEC 62106-6 and IEC 62106-10, cancels and replaces IEC 62106:2015, and constitutes a technical revision.

IEC 62106-9 cancels and replaces US NRSC-4-B, National Radio Systems Committee – United States RBDS standard, published in 2011.

The text of this International Standard is based on the following documents:

Draft	Report on voting
100/3399/CDV	100/3553/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 62106 series, published under the general title *Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*, can be found on the IEC website.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/standardsdev/publications](http://www.iec.ch/standardsdev/publications).

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

## INTRODUCTION

Since the mid-1980s, a fascinating development has taken place. Most of the multimedia applications and standards have been created or redefined significantly. Hardware has become extremely powerful with dedicated software and middleware. In the mid-1980s, Internet as well as its protocols did not exist. Navigation systems became affordable in the late 1990s, and a full range of attractive smartphones now exist. The computing power of all these new products is comparable with that of the mainframe installations in that era.

Listener expectations have grown faster than the technology. Visual experience is now very important, like the Internet look and feel. Scrolling text or delivering just audio is nowadays perceived as insufficient for FM radio, specifically for smartphone users. New types of radio receivers with added value features are therefore required. RDS has so far proven to be very successful.

FM radio with RDS is an analogue-digital hybrid system, which is still a valid data transmission technology and only the applications need adaptation. Now the time has come to solve the only disadvantage, the lack of sufficient data capacity. With RDS2, the need to increase the data capacity can be fulfilled.

RDS was introduced in the early 1980s. During the introductory phase in Europe, the car industry became very involved and that was the start of an extremely successful roll-out. Shortly afterwards, RDS (RBDS) was launched in the USA. [1, 2, 3, 4, 5, 6, 7] <sup>1</sup>

The RDS Forum has investigated a solution to the issue of limited data capacity. For RDS2, both sidebands around the RDS 57 kHz subcarrier can be repeated a few times, up to three, centred on additional subcarriers higher up in the FM multiplex while still remaining compatible with the ITU Recommendations.

The core elements of RDS2 are the additional subcarriers, which will enable a significant increase of RDS data capacity to be achieved and then only new additional data applications will have to be created, using the RDS-ODA feature, which has been part of the RDS standard IEC 62106 for many years.

In order to update IEC 62106:2015 to the specifications of RDS2, the original document has been restructured as follows:

Part 1: RDS system: Modulation characteristics and baseband coding

Part 2: RDS message format, coding and definition of RDS features

Part 3: Coding and registration of Open Data Applications ODAs

Part 4: Registered code tables

Part 5: Marking of RDS and RDS2 devices

Part 6: Compilation of technical specifications for Open Data Applications in the public domain

Part 9: RBDS – RDS variant used in North America

Part 10: Universal Encoder Communication Protocol UECP

The original specifications of the RDS system have been maintained and the extra functionalities of RDS2 have been added.

Obsolete or unused functions from the original RDS standard have been deleted.

---

<sup>1</sup> Numbers in square brackets refer to the Bibliography.



# **RADIO DATA SYSTEM (RDS) – VHF/FM SOUND BROADCASTING IN THE FREQUENCY RANGE FROM 64,0 MHz TO 108,0 MHz –**

## **Part 9: RBDS – RDS variant used in North America**

### **1 Scope**

This part of IEC 62106 specifies the Radio Broadcast Data System (RBDS), which is an RDS-compatible variant used in countries of North America. RBDS was first standardized by the U.S. National Radio Systems Committee (NRSC) in 1993 and subsequently revised in 1998, 2004, 2005 and 2011<sup>2</sup>. With the publication of this edition of IEC 62106, the RDS and RBDS standards are now harmonized into a single document.

The frequency range of operation (64,0 MHz to 108,0 MHz as indicated by the title of this document) varies according to regional regulatory authority. The U.S. range is 88 MHz to 108 MHz, as set by the U.S. Federal Communications Commission. [8]

### **2 Normative references**

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62106 (all parts), *Radio Data System (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz*

IEC 62106-2:2021, *Radio data system (RDS) – VHF/FM sound broadcasting in the frequency range from 64,0 MHz to 108,0 MHz – Part 2: Message format: coding and definition of RDS features*

### **3 Terms, definitions and abbreviated terms**

#### **3.1 Terms and definitions**

For the purposes of this document, the terms and definitions given in IEC 62106-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

---

<sup>2</sup> The NRSC ([www.nrsstandards.org](http://www.nrsstandards.org)) is jointly sponsored by the National Association of Broadcasters (NAB) and the Consumer Technology Association (CTA). Its purpose is to study and make recommendations for technical standards that relate to radio broadcasting and the reception of radio broadcast signals. See [www.nrsstandards.org](http://www.nrsstandards.org).

### **3.2 Abbreviated terms**

For the purposes of this document, the abbreviated terms given in IEC 62106-1 and the following apply.

CBC	Canadian Broadcasting Corporation
NPR	National Public Radio (USA)
NRSC	National Radio Systems Committee (USA)
RBDS	Radio Broadcast Data System

## **4 Coding of information**

### **4.1 General**

The RBDS standard uses the same data modulation as in IEC 62106-1. It also uses the same RDS features and group type coding as in IEC 62106-2. Open Data Applications coding and registration for application identification are specified in IEC 62106-2 and IEC 62106-3, respectively. Any exceptions for RBDS to these specifications are described in 4.2.

### **4.2 Exceptions**

#### **4.2.1 PI coding**

The PI code nibbles are composed differently. The methods used are described in Annex A.

#### **4.2.2 PTY coding**

The 5-bit PTY codes are defined with a different meaning in RBDS. The code definitions given in Annex B shall be used for RBDS.

#### **4.2.3 PS**

For RBDS, there is no prohibition on using PS for displaying sequential information and there is no requirement that PS be static. For RBDS, there are no restrictions on the content or update rate of the PS field.

## Annex A (normative)

### PI coding for North America

#### A.1 General

PI codes in North America are issued and used differently than in the rest of the world. In areas licensed by the U.S. Federal Communications Commission (except Guam), PI codes are calculated by the station's call letters. <sup>3</sup> Stations in Canada and Mexico use PI codes starting with 0xC and 0xF, respectively (except for certain CBC FM stations in Canada as indicated in Table A.2). This gives each station a unique PI code without the need for any outside coordination.

These PI codes do not make use of coverage area codes (IEC 62106-2). Coverage area codes are only valid for PI codes with nibble 1 being "B" or "E". (PI codes with nibble 1 being "D" were repurposed for AM and HD multicast on FM translators in 2017; see Table A.2 through Table A.4). Broadcasters and receiver manufacturers shall take note of this subtle, yet significant, difference of RBDS.

An optional method for forming PI codes is given in Clause A.4, which can be useful for broadcasters that are providing traffic information using RDS.

Because of this optional method, broadcasters should be aware that PI codes cannot be used in receivers for decoding call letters for display. The PS (program service) data field or the RT+ field STATIONNAME.SHORT may be transmitted instead. [7]

#### A.2 Call letter conversion

##### A.2.1 Conversion method to be used

- 1) Assign decimal values to last 3 letters of call letters using values from Table A.1.

**Table A.1 – Letter to decimal value conversion**

Letter	Decimal value	Letter	Decimal value
A	0	N	13
B	1	O	14
C	2	P	15
D	3	Q	16
E	4	R	17
F	5	S	18
G	6	T	19
H	7	U	20
I	8	V	21
J	9	W	22
K	10	X	23
L	11	Y	24
M	12	Z	25

<sup>3</sup> Excluding FM translators, see Clause A.5. Note: some broadcasters may elect to substitute 0x1 for the first nibble of the PI code to support RDS TMC traffic data transmission. See Clause A.4 for additional information.

- 2) Calculate a weighted decimal value ( **call it "<VAL>"** ) for the last 3 letters of the call sign, according to each letter's position, and add together to obtain this decimal value (see exception for 3-letter call signs below).

## EXAMPLE 1

K	<3rd letter position>	<2nd letter position>	<1st letter position>
W	<3rd letter position>	<2nd letter position>	<1st letter position>

$$\begin{aligned}
 & \text{<3rd letter position value> } \times 676 \\
 + & \text{<2nd letter position value> } \times 26 \\
 + & \text{<1st letter position value>} \\
 & \text{decimal value for 3 letters} = \text{<VAL>}
 \end{aligned}$$

- 3) If station call sign begins with K, add <VAL> to (decimal) 4096 and convert the result to hexadecimal (HEX {<VAL> + 4 096}) to obtain four digit PI code. However, if call sign begins with W, add <VAL> to (decimal) 21 672 and convert to hexadecimal (HEX {<VAL> + 21 672}) to obtain four digit PI code.

IF K... HEX{<VAL> + 4 096} = FOUR DIGIT PI CODE

IF W... HEX{<VAL> + 21 672} = FOUR DIGIT PI CODE

Exceptions to above assignments:

- a) Call letters that map to PI codes = \_ 0 \_ \_

RDS receivers conforming to the PI coding specified in IEC 62106-2 will treat a PI code that has nibble 2 of zero as a local station (unique broadcast) and will not AF switch. If a station's call letters map to a PI code = \_ 0 \_ \_ , the PI code assignment needs to be reassigned into the A \_ \_ \_ group as follows:

P1 0 P3 P4 → A P1 P3 P4

EXAMPLE 2 1045 → A145; 30F2 → A3F2; 80A1 → A8A1; etc.

- b) Call letters that map to PI codes = \_ \_ 0 0

If station's PI code ends with 00, the PI code will be reassigned into the A F \_ \_ group as follows:

P1 P2 0 0 → A F P1 P2

EXAMPLE 3 1C00 → AF1C; 3200 → AF32; 8C00 → AF8C; etc.

NOTE 1 For 9 special cases – 1000, 2000, ..., 9000 – a double mapping occurs, using exceptions 1 and 2: 1000 → A100 → AFA1; 2000 → A200 → AFA2; ...; 8000 → A800 → AFA8; 9000 → A900 → AFA9

- c) Two stations carry identical programming

These stations will need to assign the same PI code for both stations. The radio will need an identical PI code match to switch to the alternate frequency. The call letters can still be displayed independently with the PS information.

EXAMPLE 4 If WYAY and WYAI have identical programming, either the mapping of WYAY (PI code = 0x4F78) or WYAI (PI code = 0x4F68) will need to be used.

- d) 3-letter-only call letters

For 3-letter call sign stations, a mapping of pre-assigned PI codes is shown in Table A.4, 3-letter only call signs. The mapping of 3-letter-only call letters is reserved in PI codes ranging from 0x9950 to 0x9EFF.

- e) Nationally linked radio stations carrying different call letters

These stations will need to be assigned a PI code with a nibble 1 of 0xB (B\_01 to B\_FF and E\_01 to E\_FF; note that the "0xD" range of D\_01 to D\_FF was repurposed in 2017 for AM and HD multicast on FM translators in 2017; see Table A.3).

NOTE 2 Nibble 2 can only be filled with 1 through F. If a 0 is used, some receivers may not switch to alternate frequencies.



**Table A.2 – PI code possibilities**

NOTE 1 Some broadcasters may elect to substitute 0x1 for nibble 1 of the PI code to support RDS TMC traffic data transmission. See Clause A.4 for additional information.

NOTE 2 PI codes within the range Hex [0000-0FFF] are RESERVED and not to be used.

CALL LETTERS (K)	<VAL> + 4096 (decimal)	FOUR DIGIT PI CODE (hex)
KAAA	0 + 4 096 = 4 096	HEX{4096} = 1000
KAAB	1 + 4 096 = 4 097	HEX{4097} = 1001
:	:	:
:	:	:
KZZY	17 574 + 4 096 = 21 670	HEX{21670} = 54A6
KZZZ	17 575 + 4 096 = 21 671	HEX{21671} = 54A7

CALL LETTERS (W)	<VAL> + 21672 (decimal)	FOUR DIGIT PI CODE (hex)
WAAA	0 + 21 672 = 21 672	HEX{21672} = 54A8
WAAB	1 + 21 672 = 21 673	HEX{21673} = 54A9
:	:	:
:	:	:
WZZY	17 574 + 21 672 = 39 246	HEX{39246} = 994E
WZZZ	17 575 + 21 672 = 39 247	HEX{39247} = 994F

CALL LETTERS MAPPING TO _ 0 _ _	FOUR DIGIT PI CODE (hex)
1000	A100
1001	A101
:	:
:	:
90FF	A9FF

CALL LETTERS MAPPING TO _ _ 0 0	FOUR DIGIT PI CODE (hex)
1000, A100	AFA1
1100	AF11
1200	AF12
:	:
:	:
1F00	AF1F
2000, A200	AFA2
2100	AF21
2200	AF22
:	:
:	:
AF00	AFAF

**Table A.3 – Nationally/regionally-linked radio stations code**

<b>NATIONALLY/REGIONALLY-LINKED RADIO STATIONS CODE <sup>a,b</sup></b>	<b>FOUR DIGIT PI CODE (hex)</b>
NPR-1	B_01
CBC English – Radio One	B_02
CBC English – Radio Two	B_03
CBC French => Radio-Canada - Première Chaîne	B_04
CBC French => Radio-Canada - Espace Musique	B_05
CBC (reserved)	B_06
CBC (reserved)	B_07
CBC (reserved)	B_08
CBC (reserved)	B_09
NPR-2	B_0A
NPR-3	B_0B
NPR-4	B_0C
NPR-5	B_0D
NPR-6	B_0E
(not currently assigned)	B_0F
:	:
(not currently assigned)	B_FF
Reserved for AM and HD multicast on FM translators	D_01
:	:
Reserved for AM and HD multicast on FM translators	D_FF
(not currently assigned)	E_01
(not currently assigned)	E_02
:	:
(not currently assigned)	E_FF
<sup>a</sup> In the United States, these codes will be allocated by the administrators of the NRSC. The nibble 2 of each four digit hex code shall be determined by the broadcaster using the rules for coverage area codes defined in IEC 62106-2:2021, Table 5.	
<sup>b</sup> The scheme outlined in this table will map all possible K____, W____, 3-LETTER-ONLY CALL LETTERS, CALL LETTERS MAPPING TO _0_ , CALL LETTERS MAPPING TO __00, and NATIONALLY-LINKED RADIO STATIONS into a four digit hex PI code.	

### Table A.4 – 3-letter only call signs

3-LETTER ONLY CALL SIGNS							
CALL	FOUR DIGIT PI CODE (hex)		CALL	FOUR DIGIT PI CODE (hex)		CALL	FOUR DIGIT PI CODE (hex)
KBW	99A5		KOY	9992		WHO	9978
KCY	99A6		KPQ	9993		WHP	999C
KDB	9990		KQV	9964		WIL	999D
KDF	99A7		KSD	9994		WIP	997A
KEX	9950		KSL	9965		WIS	99B3
KFH	9951		KUJ	9966		WJR	997B
KFI	9952		KUT	9995		WJW	99B4
KGA	9953		KVI	9967		WJZ	99B5
KGB	9991		KWG	9968		WKY	997C
KGO	9954		KXL	9996		WLS	997D
KGU	9955		KXO	9997		WLW	997E
KGW	9956		KYW	996B		WMC	999E
KGY	9957		WBT	9999		WMT	999F
KHQ	99AA		WBZ	996D		WOC	9981
KID	9958		WDZ	996E		WOI	99A0
KIT	9959		WEW	996F		WOL	9983
KJR	995A		WGH	999A		WOR	9984
KLO	995B		WGL	9971		WOW	99A1
KLZ	995C		WGN	9972		WRC	99B9
KMA	995D		WGR	9973		WRR	99A2
KMJ	995E		WGY	999B		WSB	99A3
KNX	995F		WHA	9975		WSM	99A4
KOA	9960		WHB	9976		WWJ	9988
KOB	99AB		WHK	9977		WWL	9989

### A.2.2 Examples of assigning PI codes from call letters

EXAMPLE 1: call sign KGTB

$$\begin{array}{rcl} G & = 6 \times 676 & = 4\,056 \\ T & = 19 \times 26 & = 494 \\ B & = 1 & = 1 \\ \hline & & = 4\,551 \quad (= \text{<VAL>}) \end{array}$$

Since call sign begins with K:  $4\,551 + 4\,096 = 8\,647$  (STATION DECIMAL VALUE) = HEX [8647] = 0x21C7 = KGTB's PI code.

EXAMPLE 2: call sign WKTI

$$\begin{array}{rcl} K & = & 10 \times 676 = 6\,760 \\ T & = & 19 \times 26 = 494 \\ I & = & 8 = 9 \\ \hline & & = 7\,262 \quad (= <VAL>) \end{array}$$

Since call sign begins with W:  $7\ 262 + 21\ 672 = 28\ 934$  (STATION DECIMAL VALUE) = HEX [28934] = 0x7106 = WKTl's PI code.

### EXAMPLE 3: Checking hex code

To check hex code:

$$\begin{array}{r}
 \text{4th digit} \times 4\,096 \\
 + \text{ 3rd digit} \times 256 \\
 + \text{ 2nd digit} \times 16 \\
 + \text{ 1st digit} \times 1 \\
 \hline
 \text{(should equal) STATION DECIMAL VALUE}
 \end{array}$$

For call sign KGTB:

PI code = 21C7, from STATION DECIMAL VALUE of 8 647

$$\begin{array}{r}
 2 \times 4\,096 \\
 + 1 \times 256 \\
 + 12 \times 16 \\
 + 7 \times 1 \\
 \hline
 = 8\,647 = \text{STATION DECIMAL VALUE}
 \end{array}$$

For call sign WKTl:

PI code = 7 106, from STATION DECIMAL VALUE of 28 934

$$\begin{array}{r}
 7 \times 4\,096 \\
 + 1 \times 256 \\
 + 0 \times 16 \\
 + 6 \times 1 \\
 \hline
 = 28\,934 = \text{STATION DECIMAL VALUE}
 \end{array}$$

### A.3 Application: receiver functionality to PI code assignments

Within North America, coverage area codes are recognized only in the following PI code blocks:

- 0xB\_01 to 0xB\_FF
- 0xE\_01 to 0xE\_FF

Historically, the range 0xD\_01 to 0xD\_FF was also considered as a valid PI code range with coverage area code recognition for nationally/regionally linked stations. However, the D-block PI codes have been repurposed for FM translators in North America as managed by the NAB on behalf of the NRSC. The D-block should no longer be used for ad-hoc assignment.

All other PI codes do not make use of coverage area codes and shall be handed as such within the receiver.

RDS receivers conforming to the PI coding specified in IEC 62106-2 store PI codes into presets in addition to storing frequencies into presets. This function is to recognize the broadcast first by program rather than frequency. Thus, if a preset is pushed and the PI code has changed, the RDS receivers would not recognize the new PI code and go into a PI search.

EBU DOC TECH 3260 January 1990 Chapter 4 page 49 states [9]:

"If however the PI code changes completely, the receiver should initiate a PI search for a frequency whose PI code exactly matches the PI code of the original tuned frequency. Failing an exact PI code match, the receiver should search for a PI code differing only in the regional element (bits 5-8) from the original PI code. If neither of these criteria are met, the receiver should remain on the original tuned frequency."

Therefore, in North America, since call letters are used to create the PI code, the receiver would have to do a PI search every time a station would change call letters or a preset is pushed in a new listening area having a station at the same frequency as the preset station. For PI codes < 0xB000, future receivers could check the AF list associated to a preset and, if no AF's are acceptable, a PI search could be initiated. If no identical PI is found, the receiver should return to the original tuned frequency and accept the new PI code.



If a PI search is performed, the regional variant search (the second search to match PI codes differing only in bits 5-8) should be eliminated in a PI search if the tuned PI is below 0xB000, or within the ranges of 0xC000 to 0xDFFF, and 0xF000 to 0xFFFF.

If a feature similar to the regional variants as specified for the PI code in IEC 62106-2 is desired, a grouping of PI codes starting with the B and E nibble 1 could be designated as follows:

- If NPR broadcasts break off national programming to go local for a period of time, it could be assigned a PI of 0xB\_01 (cannot use 0 as nibble 2 because current receivers will not search for AF's: therefore, use 4-F for indication of a variant.).
- If no AFs or identical PIs are found via the AF list or an identical PI search, the receiver could, while tuned to NPR station 1 (PI=0xB101), accept a variant NPR station 2 whose PI varies only in nibble 2 (bits 5-8). Thus 0xB201, 0xB301, 0xB401, ... could be accepted.

PI codes starting with the B and E nibbles yield 510 possibilities for "regional" programming. These PI codes will be shared by the United States, Canada, and Mexico. The problem here becomes that a registry needs to be kept; however, there should not be too many broadcasts that fit in this category and not many would be used.

#### A.4 Optional – modifying PI code for use with traffic information systems

Broadcasters who are transmitting traffic information using the TMC ODA may want to substitute 0x1 for the nibble 1 (bits b<sub>15</sub> to b<sub>12</sub> shown in Figure 17 of IEC 62106-2:2021) of the PI code. Doing so will make the TMC transmission compatible with a greater variety of traffic information receivers, because many such receivers interpret a nibble 1 of 0x1 as an indication that the receiver is in North America, consistent with the location table definition contained in the TMC specification. Note, however, that this may also cause some receivers that use the PI code to determine the station call sign (by "back calculation") to behave incorrectly [7]. 4

One method that a receiver can use to try and establish whether a 0x1 first nibble substitution has been made is to check for the presence of the TMC ODA in the RDS transmission, as shown in Table A.5.

**Table A.5 – Receiver checking method for PI 0x1 nibble 1 substitution**

Nibble 1 of PI code	TMC ODA data present	Receiver interpretation
0x1	No	PI code has been calculated using method described in Clause A.2, without a nibble 1 substitution. Approximately 16 % of the radio stations in the Western half of the U.S. have a calculated nibble 1 of 0x1, and none of the stations in the Eastern half of the U.S. do. 5
0x1	Yes	A first nibble substitution of 0x1 can have been done on the PI code, or, a station that has a calculated nibble 1 of 0x1 is transmitting TMC ODA information.
(any other value)	Yes or No	PI code has been calculated using method described in A.2, without a nibble 1 substitution.

#### A.5 PI codes for FM translators

FM translators that are licensed by the U.S. Federal Communications Commission have a six-character call sign (unlike a full-power station, which has a four-character call sign) and as such

<sup>4</sup> See NRSC-G300, *RDS Usage Guideline*, for additional information on the impact of the first nibble substitution discussed in this Section.

<sup>5</sup> Statistics from RDS-TMC (ISO-14819-1) and PI Code Issue: Summary of the problem and the path to a solution, presented to the NRSC RBDS Subcommittee on September 23, 2009.

the method for determining PI codes defined above cannot be applied to FM translators. If an FM translator is simply re-broadcasting (simulcasting) the audio program of a full-power FM station, then that translator should use the PI code of the full-power station being simulcast.

For cases where the FM translator is not simulcasting a full-power FM station, the NRSC has developed a method for assigning PI codes that is described in NRSC-G300 [6]. These cases include when a translator is broadcasting the content from an HD Radio multicast channel, or the audio program of an AM radio station (a so-called "cross-service" translator).

The PI code assignments for these stations can be accessed at <https://picodes.nrscstandards.org> [10].

## Annex B (normative)

### PTY coding

PTY programme type codes with the corresponding terms to be displayed on a receiver are listed in Table B.1. They serve as an identification of specific programme items, whose meaning is defined as listed below.

Spanish language PTY code translations are shown in Table B.3.

NOTE For code 00000, the PTY display should be kept blank.

**Table B.1 – Programme type codes and corresponding terms for display**

Number	Code	Programme type	8-character display <sup>a</sup>	16-character display <sup>a</sup>
0	00000	No program type or undefined		
1	00001	News	News	News
2	00010	Information	Inform	Information
3	00011	Sports	Sports	Sports
4	00100	Talk	Talk	Talk
5	00101	Rock	Rock	Rock
6	00110	Classic Rock	Cls Rock	Classic Rock
7	00111	Adult Hits	Adlt Hit	Adult Hits
8	01000	Soft Rock	Soft Rck	Soft Rock
9	01001	Top 40	Top 40	Top 40
10	01010	Country	Country	Country
11	01011	Oldies	Oldies	Oldies
12	01100	Soft	Soft	Soft
13	01101	Nostalgia	Nostalgia	Nostalgia
14	01110	Jazz	Jazz	Jazz
15	01111	Classical	Classicl	Classical
16	10000	Rhythm and Blues	R & B	Rhythm and Blues
17	10001	Soft Rhythm and Blues	Soft R&B	Soft R & B
18	10010	Foreign Language	Language	Foreign Language
19	10011	Religious Music	Rel Musc	Religious Music
20	10100	Religious Talk	Rel Talk	Religious Talk
21	10101	Personality	Persnlty	Personality
22	10110	Public	Public	Public
23	10111	College	College	College
24	11000	Spanish Talk	Habl Esp	Hablar Espanol
25	11001	Spanish Music	Musc Esp	Musica Espanol
26	11010	Hip-Hop	Hip-Hop	Hip-Hop
27	11011	Unassigned		
28	11100	Unassigned		
29	11101	Weather	Weather	Weather
30	11110	Emergency Test	Test	Emergency Test
31	11111	Emergency	ALERT !	ALERT! ALERT!

<sup>a</sup> These short terms are recommended for the 8- or 16-character display of the radio.

Table B.1 defines the meaning of the terms used in Table B.2 to denote programme type. These definitions can slightly differ between various language versions.

**Table B.2 – Definition of the terms used to denote programme type – PTY**

1	<b>News</b>	News reports, either local or network in origin.
2	<b>Information</b>	Programming that is intended to impart advice.
3	<b>Sports</b>	Sports reporting, commentary, and/or live event coverage, either local or network in origin.
4	<b>Talk</b>	Call-in and/or interview talk shows either local or national in origin.
5	<b>Rock</b>	Album cuts.
6	<b>Classic Rock</b>	Rock oriented oldies, often mixed with hit oldies, from a decade or more ago.
7	<b>Adult Hits</b>	An up-tempo contemporary hits format with no hard rock and no rap.
8	<b>Soft Rock</b>	Album cuts with a generally soft tempo.
9	<b>Top 40</b>	Current hits, often encompassing a variety of rock styles.
10	<b>Country</b>	Country music, including contemporary and traditional styles.
11	<b>Oldies</b>	Popular music, usually rock, with 80% or greater non-current music.
12	<b>Soft</b>	A cross between adult hits and classical, primarily non-current soft-rock originals.
13	<b>Nostalgia</b>	Big-band music.
14	<b>Jazz</b>	Mostly instrumental, includes both traditional jazz and more modern "smooth jazz".
15	<b>Classical</b>	Mostly instrumentals, usually orchestral or symphonic music.
16	<b>Rhythm and Blues</b>	A wide range of musical styles, often called "urban contemporary".
17	<b>Soft Rhythm and Blues</b>	Rhythm and blues with a generally soft tempo.
18	<b>Foreign Language</b>	Any programming format in a language other than English.
19	<b>Religious Music</b>	Music programming with religious lyrics.
20	<b>Religious Talk</b>	Call-in shows, interview programs, etc. with a religious theme.
21	<b>Personality</b>	A radio show where the on-air personality is the main attraction.
22	<b>Public</b>	Programming that is supported by listeners and/or corporate sponsors instead of advertising.
23	<b>College</b>	Programming produced by a college or university radio station.
24	<b>Spanish Talk</b>	Call-in shows, interview programs, etc. in the Spanish language.
25	<b>Spanish Music</b>	Music programming in the Spanish language.
26	<b>Hip-Hop</b>	Popular music incorporating elements of rap, rhythm-and-blues, funk, and soul.
27	<b>Unassigned</b>	
28	<b>Unassigned</b>	
29	<b>Weather</b>	Weather forecasts or bulletins that are non-emergency in nature.
30	<b>Emergency Test</b>	Broadcast when testing emergency broadcast equipment or receivers. Not intended for searching or dynamic switching for consumer receivers.. Receivers may, if desired, display "TEST" or "Emergency Test".
31	<b>Emergency</b>	Emergency announcement made under exceptional circumstances to give warning of events causing danger of a general nature. Not to be used for searching - only used in a receiver for dynamic switching.



**Table B.3 – PTY code descriptions and abbreviations in Spanish**

	English	Spanish	Spanish	Spanish
Number	Programme type	Tipo de programa	Pantalla de 8 caracteres <sup>a</sup>	Pantalla de 16 caracteres <sup>a</sup>
0	No program type or undefined	No se indica el tipo programa		
1	News	Noticias	Noticias	Noticias
2	Information	Información	Info	Información
3	Sports	Deportes	Deportes	Deportes
4	Talk	Hablar	Hablar	Hablar
5	Rock	Rock	Rock	Rock
6	Classic Rock	Rock Clásico	RockCls	Rock Clásico
7	Adult Hits	Exitos de Adultos	Exit Adul	Exito de Adultos
8	Soft Rock	Rock Suave	RockSve	RockSuave
9	Top 40	Top 40	Top 40	Top 40
10	Country	Country	Country	Country
11	Oldies	Oldies	Oldies	Oldies
12	Soft	Suave	Suave	Suave
13	Nostalgia	Nostalgia	Nostalgia	Nostalgia
14	Jazz	Jazz	Jazz	Jazz
15	Classical	Clásica	Clásica	Clásica
16	Rhythm and Blues	Ritmo y Blues	R & B	Ritmo y Blues
17	Soft Rhythm and Blues	Suave Ritmo y Blues	Suave R&B	Suave R & B
18	Foreign Language	Idioma Extranjero	Idioma	Idioma Extranjero
19	Religious Music	Musica Religiosa	Mus Rel	Musica Religiosa
20	Religious Talk	Charla Religiosa	Mus Char	Charla Religiosa
21	Personality	Personalidad	Prsnldad	Personalidad
22	Public	Público	Público	Público
23	College	Universidad	Unvsdad	Universidad
24	Spanish Talk	Hablar Espanol	Habl Esp	Hablar Espanol
25	Spanish Music	Musica Espanol	Musc Esp	Musica Espanol
26	Hip-Hop	Hip-Hop	Hip-Hop	Hip-Hop
27	Unassigned	No se indica el tipo programa		
28	Unassigned	No se indica el tipo programa		
29	Weather	Información Metereológica	Meteo	Metereológica
30	Emergency Test	Prueba de Emergencia	Prueba	Preube de Emergencia
31	Emergency	Emergencia	Alarma	Emergencia

<sup>a</sup> These short terms are recommended for the 8- or 16-character display of the radio.

## Bibliography

- [1] EBU, Specifications of the radio data system RDS for VHF/FM sound broadcasting. Doc. Tech 3244 and Supplements 1 to 4. European Broadcasting Union, 1984
  - [2] WRIGHT, S., The Broadcaster's Guide to RDS. Focal Press, Boston, Oxford, Johannesburg, Melbourne, New Delhi, Singapore, 1997, ISBN 0-240-80278-0
  - [3] KOPITZ, D. and MARKS, B., RDS – The Radio Data System. Artech House Publishers, Boston and London, 1999, ISBN 0-89006-744-9
  - [4] EN 50067:1998, Specification of the radio data system (RDS for VHF/FM sound broadcasting in the frequency range from 87,5 to 108,0 MHz
  - [5] US NRSC-4-B, United States RBDS standard – Specification of the radio broadcast data system (RBDS), 2011
  - [6] National Radio Systems Committee, NRSC-G300-C, *Radio Data System (RDS) Usage Guideline*, available at <https://www.nrscstandards.org/standards-and-guidelines/standards-and-guidelines.asp>
  - [7] National Radio Systems Committee, NRSC-G200, *Harmonization of RDS and IBOC Program Service Data (PSD) Guideline*, available at <https://www.nrscstandards.org/standards-and-guidelines/standards-and-guidelines.asp>
  - [8] US Code of Federal Regulations (CFR) 47 §73.201 – Numerical designation of FM broadcast channels.
  - [9] EBU DOC TECH 3260, *Guidelines for the implementation of the RDS system*, chapter 4, pg. 49, January 1990.
  - [10] National Radio Systems Committee, *FM PI Code Allocations*, available at <https://picodes.nrscstandards.org>.
-









