

PC37.30.5™/D1.2

Draft Standard for Definitions for AC High-Voltage Air Switches Rated Above 1000 V

Sponsor

Switchgear Committee
of the
IEEE Power & Energy Society

Approved <Date Approved>

IEEE-SA Standards Board

Copyright © 2017 by The Institute of Electrical and Electronics Engineers, Inc.
Three Park Avenue
New York, New York 10016-5997, USA

All rights reserved.

This document is an unapproved draft of a proposed IEEE Standard. As such, this document is subject to change. USE AT YOUR OWN RISK! IEEE copyright statements SHALL NOT BE REMOVED from draft or approved IEEE standards, or modified in any way. Because this is an unapproved draft, this document must not be utilized for any conformance/compliance purposes. Permission is hereby granted for officers from each IEEE Standards Working Group or Committee to reproduce the draft document developed by that Working Group for purposes of international standardization consideration. IEEE Standards Department must be informed of the submission for consideration prior to any reproduction for international standardization consideration (stds.ipr@ieee.org). Prior to adoption of this document, in whole or in part, by another standards development organization, permission must first be obtained from the IEEE Standards Department (stds.ipr@ieee.org). When requesting permission, IEEE Standards Department will require a copy of the standard development organization's document highlighting the use of IEEE content. Other entities seeking permission to reproduce this document, in whole or in part, must also obtain permission from the IEEE Standards Department.

IEEE Standards Department
445 Hoes Lane
Piscataway, NJ 08854, USA

Abstract: The terms and definitions in this standard cover all high-voltage enclosed and non-enclosed, indoor and outdoor air switches rated in excess of 1000 V used primarily in connection with generation, transmission, distribution, and conversion of electric power. This includes such switch types as disconnect, horn gap, fault initiation, and ground for manual or power operation. The following switch types are not covered by this standard: distribution cutouts fitted with disconnecting blades, and switches used in metal enclosed and pad mounted switchgear. This standard also does not apply to load break separable insulated connectors, circuit breakers, circuit switchers, or reclosers.

Keywords: definitions, terms

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2017 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published <Date Published>. Printed in the United States of America.

IEEE is a registered trademark in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-0-XXXX-XXXX-X STDXXXXX
Print: ISBN 978-0-XXXX-XXXX-X STDPDXXXXX

IEEE prohibits discrimination, harassment, and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatisthis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

49 **Important Notices and Disclaimers Concerning IEEE Standards Documents**

50 IEEE documents are made available for use subject to important notices and legal disclaimers. These
51 notices and disclaimers, or a reference to this page, appear in all standards and may be found under the
52 heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Standards
53 Documents.”

54 **Notice and Disclaimer of Liability Concerning the Use of IEEE Standards** 55 **Documents**

56 IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are
57 developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards
58 Association (“IEEE-SA”) Standards Board. IEEE (“the Institute”) develops its standards through a
59 consensus development process, approved by the American National Standards Institute (“ANSI”), which
60 brings together volunteers representing varied viewpoints and interests to achieve the final product.
61 Volunteers are not necessarily members of the Institute and participate without compensation from IEEE.
62 While IEEE administers the process and establishes rules to promote fairness in the consensus development
63 process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the
64 soundness of any judgments contained in its standards.

65 IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and
66 expressly disclaims all warranties (express, implied and statutory) not included in this or any other
67 document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness
68 for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness
69 of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort.
70 IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

71 Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there
72 are no other ways to produce, test, measure, purchase, market, or provide other goods and services related
73 to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved
74 and issued is subject to change brought about through developments in the state of the art and comments
75 received from users of the standard.

76 In publishing and making its standards available, IEEE is not suggesting or rendering professional or other
77 services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any
78 other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his
79 or her own independent judgment in the exercise of reasonable care in any given circumstances or, as
80 appropriate, seek the advice of a competent professional in determining the appropriateness of a given
81 IEEE standard.

82 IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
83 EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO:
84 PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS;
85 OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
86 WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
87 OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE
88 UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND
89 REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

90 **Translations**

91 The IEEE consensus development process involves the review of documents in English only. In the event
92 that an IEEE standard is translated, only the English version published by IEEE should be considered the
93 approved IEEE standard.

94 **Official statements**

95 A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board
96 Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its
97 committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures,
98 symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall
99 make it clear that his or her views should be considered the personal views of that individual rather than the
100 formal position of IEEE.

101 **Comments on standards**

102 Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of
103 membership affiliation with IEEE. However, IEEE does not provide consulting information or advice
104 pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a
105 proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a
106 consensus of concerned interests, it is important that any responses to comments and questions also receive
107 the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and
108 Standards Coordinating Committees are not able to provide an instant response to comments or questions
109 except in those cases where the matter has previously been addressed. For the same reason, IEEE does not
110 respond to interpretation requests. Any person who would like to participate in revisions to an IEEE
111 standard is welcome to join the relevant IEEE working group.

112 Comments on standards should be submitted to the following address:

113 Secretary, IEEE-SA Standards Board
114 445 Hoes Lane
115 Piscataway, NJ 08854 USA

116 **Laws and regulations**

117 Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with
118 the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory
119 requirements. Implementers of the standard are responsible for observing or referring to the applicable
120 regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not
121 in compliance with applicable laws, and these documents may not be construed as doing so.

122 **Copyrights**

123 IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws.
124 They are made available by IEEE and are adopted for a wide variety of both public and private uses. These
125 include both use, by reference, in laws and regulations, and use in private self-regulation, standardization,
126 and the promotion of engineering practices and methods. By making these documents available for use and
127 adoption by public authorities and private users, IEEE does not waive any rights in copyright to the
128 documents.

129 **Photocopies**

130 Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to
131 photocopy portions of any individual standard for company or organizational internal use or individual,
132 non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance
133 Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission
134 to photocopy portions of any individual standard for educational classroom use can also be obtained
135 through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA Website at <http://ieeexplore.ieee.org/xpl/standards.jsp> or contact IEEE at the address listed previously. For more information about the IEEE-SA or IEEE's standards development process, visit the IEEE-SA Website at <http://standards.ieee.org>.

Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

170 Participants

171 At the time this draft Standard was completed, the Definitions for AC High-Voltage Air Switches Rated
172 Above 1000 V Working Group had the following membership:

173 **Carl D. Reigart**, *Chair*
174 **Jacob W. Blake**, *Vice Chair*

175			
176	Roy Alexander	181	Ken Harless
177	Chris Ambrose	182	Danny Hoss
178	Frank DeCesaro	183	James Houston
179	Glenn Dorsey	184	Bill Hurst
180	John Hall	185	Peter M. Kowalik

189

190 The following members of the <individual/entity> balloting committee voted on this standard. Balloters
191 may have voted for approval, disapproval, or abstention.

192 *[To be supplied by IEEE]*

193	Balloter1	196	Balloter4	199	Balloter7
194	Balloter2	197	Balloter5	200	Balloter8
195	Balloter3	198	Balloter6	201	Balloter9

202

203 When the IEEE-SA Standards Board approved this standard on <Date Approved>, it had the following
204 membership:

205 *[To be supplied by IEEE]*

206 **<Name>**, *Chair*
207 **<Name>**, *Vice Chair*
208 **<Name>**, *Past Chair*
209 **Konstantinos Karachalios**, *Secretary*

210	SBMember1	213	SBMember4	216	SBMember7
211	SBMember2	214	SBMember5	217	SBMember8
212	SBMember3	215	SBMember6	218	SBMember9

219 *Member Emeritus

220

221 Also included are the following nonvoting IEEE-SA Standards Board liaisons:

222 **<Name>**, *DOE Representative*
223 **<Name>**, *NIST Representative*
224
225 **<Name>**
226 *IEEE-SA Content Production and Management*
227 **<Name>**
228 *IEEE-SA Technical Program Operations*
229
230

231

232 Introduction

233 This introduction is not part of PC37.30.5/D1.2, Draft Standard for Definitions for AC High-Voltage Air Switches
234 Rated Above 1000 V.

235 This standard constitutes a compilation of terms and definitions relating to high-voltage air switches, and
236 should be considered to reflect common and current usage of that industry. The size of this standard has
237 been kept to a minimum by omitting all terms satisfactorily covered in readily available dictionaries. In
238 some instances, terms and definitions of related products exhibiting minor variations have been combined
239 for greater clarity. Specifications and ratings have been excluded from definitions. This information is
240 included in standards covering specific product types. This standard contains, in addition to many additions
241 and modifications, the relevant terms from IEEE Std C37.100, which is scheduled to be withdrawn when its
242 validity expires in 2018.

243 **Contents**

244	1. Overview	1
245	1.1 Scope	1
246	1.2 Purpose	1
247	2. Definitions	2
248	Annex A (informative)	8
249		

Draft Standard for Definitions for AC High-Voltage Air Switches Rated Above 1000 V

IMPORTANT NOTICE: IEEE Standards documents are not intended to ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

1. Overview

1.1 Scope

The terms and definitions in this standard cover all high-voltage enclosed and non-enclosed, indoor and outdoor air switches rated in excess of 1000 V used primarily in connection with generation, transmission, distribution, and conversion of electric power. This includes such switch types as disconnect, horn-gap, fault-initiation, and ground for manual or power operation.

The following switch types are not covered by this standard: interrupter switches, distribution cutouts fitted with disconnecting blades, and switches used in metal-enclosed and pad-mounted switchgear. This standard also does not apply to load-break separable insulated connectors, circuit-breakers, circuit-switchers, or reclosers.

1.2 Purpose

The definitions of terms and explanatory notes relating thereto contained in this standard are not intended to encompass all possible meanings of the terms. They are intended for the sole purpose of establishing only those meanings of terms used in standards for switchgear assemblies. They do not purport to encompass other meanings that the terms may properly have when used in connection with other subjects.

278 In some instances, terms and definitions that are not identical to those in this standard have been developed
279 by other branches of industry. Where this situation exists, the definitions in this standard shall be used for
280 AC High-Voltage Air Switches Rated Above 1000 V covered by the C37 series of standards.

281 2. Definitions

282 For the purposes of this document, the following terms and definitions apply. The *IEEE Standards*
283 *Dictionary Online* should be consulted for terms not defined in this clause.¹

284 **accessories:** Devices that perform a secondary or minor duty as an adjunct or refinement to the primary or
285 major duty of a unit of equipment.

286 **air switch:** A switching device designed to close and open one or more electric circuits by means of guided
287 separable contacts that separate in air.

288 **arc reach:** The distance from a point midway between the arc extremities to the most remote point of the
289 arc at the time of its maximum length.

290 **arcing horn:** One of a pair of diverging electrodes on which an arc is extended to the point of extinction
291 after the main contacts of the switching device have parted.

292 **attachments:** Accessories to be attached to switchgear apparatus, as distinguished from auxiliaries.

293 **bell crank:** A lever with two arms placed at an angle diverging from a given point, thus changing the
294 direction of motion of a mechanism.

295 **bell crank hanger:** A support for a bell crank.

296 **blade (disconnecting blade) (of a switching device):** The moving contact member that enters or embraces
297 the contact clips.

298 **blade guide (switch):** An attachment to help assist in proper alignment of the blade and contact clip when
299 closing the switch.

300 **blade latch:** A latch used on a switch to hold the switch blade in the closed position.

301 **break distance (of a switching device):** The minimum open-gap distance between the main-circuit
302 contacts, or live parts connected thereto, when the contacts are in the open position.

303 **bus support:** An insulating support for a bus. It includes one or more insulator units with fittings for
304 fastening to the mounting structure and for receiving the bus.

305 **center break switching device:** A mechanical switching device in which both contacts are moveable and
306 engage at a point substantially midway between their supports.

307 **clips:** *See:* **contact clips (of a mechanical switching device)**

308 **closing operating time (of a switch):** The interval during which the contacts move from the fully open
309 position to the fully closed position.

¹IEEE Standards Dictionary Online subscription is available at:
http://www.ieee.org/portal/innovate/products/standard/standards_dictionary.html.

- 310 **conducting mechanical joint:** The juncture of two or more conducting surfaces held together by
311 mechanical means.
- 312 **conductive outrigger (of a switching device terminal):** An attachment that is fastened to and extends the
313 terminal pad of a switching device to maintain electrical clearance between the conductor and other parts.
- 314 **connecting rod or shaft:** A component of a switch operating mechanism designed to transmit motion from
315 an offset bearing or bell crank to a switch pole unit.
- 316 **contact:** A conducting part that coacts with another conducting part to make or break a circuit.
- 317 **contact clip (of a mechanical switching device):** The clip that the blade enters or embraces.
- 318 **contact position indicator:** A device that is located at or near the operating mechanism to indicate whether
319 the main contacts are in the closed or open position. Typically colors are used to indicate a closed or open
320 position; red will typically signify closed and green will typically signify open.
- 321 **contact surface:** That surface of a contact through which current is transferred to the coacting contact.
- 322 **creepage distance:** The shortest distance between two conducting parts measured along the surface or
323 joints of the insulating material between them.
- 324 **current-carrying part:** A conducting part intended to be connected in an electric circuit to a source of
325 voltage.
- 326 **direct operation:** Operation by means of a mechanism connected directly to the main operating shaft or an
327 extension of the same.
- 328 **disconnecting blade:** *See:* **blade (disconnecting blade) (of a switching device).**
- 329 **disconnecting or isolating switch (disconnecter, isolator):** A mechanical switching device used for
330 changing the connections in a circuit, or for isolating a circuit or equipment from the source of power.
- 331 **double break switch:** A mechanical switching device that opens a conductor of a circuit at two points.
- 332 **enclosed switches, indoor or outdoor:** Switches designed for service within a housing restricting heat
333 transfer to the external medium.
- 334 **fault initiating switch:** A mechanical switching device used in applied fault protection to place a short
335 circuit on an energized circuit and to carry the resulting current until the circuit has been de-energized by
336 protective operation.
- 337 **grounded parts:** Parts that are intentionally connected to ground.
- 338 **grounding switch:** A mechanical switching device by means of which a circuit or piece of apparatus may
339 be electrically connected to ground.
- 340 **group operation:** The operation of all poles of a multipole switch device by one operating mechanism.
- 341 **high speed grounding switch:** *See:* **fault initiating switch.**
- 342 **high speed short circuiting switch:** *See:* **fault initiating switch.**
- 343 **hinge clip (of a switching device):** The clip to which the blade is movably attached.

- 344 **horn-gap switch:** A switch provided with arcing horns.
- 345 **hook ring (air switch):** A ring provided on a switch blade for operation of the switch with an insulated
346 switch (hook) stick.
- 347 **hook stick:** *See:* **switch stick (switch hook).**
- 348 **ice proof:** So constructed or protected that ice of a specified composition and thickness will not interfere
349 with successful operation.
- 350 **ice tests:** Design tests made to determine the rated ice-breaking capability of the switching equipment.
- 351 **indirect manual operation (of a switching device):** Operation by hand through an operating handle,
352 mounted at a distance from and connected to the switching device by mechanical linkage.
- 353 **indirect operation (of a switching device):** Operation by means of an operating mechanism connected to
354 the main operating shaft or an extension of it, through offset linkages and bearings.
- 355 **indoor:** Designed for use only inside buildings, or weather-resistant enclosures.
- 356 **interlock:** A device actuated by the operation of some other device with which it is directly associated, to
357 govern succeeding operations of the same or allied devices.
- 358 NOTE — An interlock system is a series of interlocks applied to associated equipment in such a manner as to allow
359 operation of the equipment only in a prearranged sequence. Interlocks are classified into three main divisions:
360 mechanical interlocks, electrical interlocks, and key interlocks, based on the type of interconnection between the
361 associated devices.
- 362 **interphase rod or shaft:** A component of a switch-operating mechanism designed to connect two or more
363 poles of a multipole switch for group operation.
- 364 **interrupter:** An element designed to interrupt specified currents under specified conditions.
- 365 **interrupter blade (of an interrupter switch):** A component used in the interrupter for breaking the
366 circuit.
- 367 **interrupter switch:** An air switch, equipped with an interrupter, for making or breaking specified currents,
368 or both.
- 369 **interrupting aid:** A current interrupting device that can be attached to an air switch to improve its
370 interrupting capability.
- 371 **interrupting (breaking) current:** The current in a pole of a switching device at the instant of the initiation
372 of the arc.
- 373 **interrupting tests:** Tests that are made to determine or check the interrupting performance of a switching
374 device.
- 375 **isolator:** *See:* **disconnecting or isolating switch**
- 376 **leakage distance of external insulation:** *See:* **creepage distance.**
- 377 **lifting insulator switch:** A mechanical switching device in which one or more insulators remain attached
378 to the blade, move with it, and lift it to the open position.

- 379 **load interrupter switch:** An interrupter switch designed to interrupt a specified steady state current.
- 380 **manual operation:** Operation by hand without the use of any other source of power.
- 381 **mechanical operation (of a switch):** Operation by means of an operating mechanism connected to the
382 switch by mechanical linkage.
- 383 **mechanism (of a switching device):** The complete assembly of levers and other parts that actuates the
384 moving contacts of a switching device.
- 385 **minimum clearance between poles (phases):** The shortest distance between any live parts of adjacent
386 poles (phases).

387 **CAUTION**

388 Differentiation should be made between clearance and spacing or center-to-center distance.

- 389
- 390 **minimum clearance to ground:** The shortest distance between any live part and adjacent grounded parts.
- 391 **moving contact:** A conducting part that bears a contact surface arranged for movement to and from the
392 stationary contact.
- 393 **nonenclosed switches, indoor or outdoor:** Mechanical switching devices designed for service without a
394 housing restricting heat transfer to the external medium.
- 395 **offset (outboard) bearing (air switch):** A component of a switch-operating mechanism designed to
396 provide support for a torsional operating member and a crank that provides reciprocating motion for switch
397 operation.
- 398 **open operation (of a switching device):** The movement of the contacts from the normally closed to the
399 normally open position.
- 400 **opening operating time (of a switch):** The interval of time it takes during switch operation to move from
401 the fully closed to the fully open position.
- 402 **opening operation (of a switching device):** *See: open operation (of a switching device).*
- 403 **outrigger (of a switching device terminal):** An attachment that is fastened to or adjacent to the terminal
404 pad of a switching device to maintain electrical clearance between the conductor and other parts or, when
405 fastened adjacent, to relieve mechanical strain on the terminal, or both.
- 406 **overhead line charging current:** Current supplied to an unloaded overhead line.
- 407 **parallel connected capacitance (as applied to interrupter switches):** Capacitances are defined to be
408 parallel connected when the crest value of inrush current to the capacitance being switched exceeds the
409 switch inrush current capability for single capacitance.
- 410 **phase spacing (of a switching device):** The distance between center-lines of the current carrying parts of
411 the adjacent poles of the switching device.
- 412 **protective gap:** A gap placed between live parts and ground to limit the maximum overvoltage that may
413 occur.

- 414 **quick break:** A term used to describe a device that has a high contact opening speed independent of the
415 operator.
- 416 **quick make:** A term used to describe a device that has a high contact closing speed independent of the
417 operator.
- 418 **remote manual operation:** *See:* **indirect manual operation (of a switching device).**
- 419 **resistant (used as a suffix):** So constructed, protected, or treated that damage will not occur readily when
420 the device is subjected to the specified material or condition.
- 421 **rotating insulator switch:** A mechanical switching device in which the opening and closing travel of the
422 blade is accomplished by the rotation of one or more insulators supporting the conducting parts of the
423 switch.
- 424 **selector switch:** A switch arranged to permit connecting a conductor to any one of a number of other
425 conductors.
- 426 **short-time current:** The current carried by a device, an assembly, or a bus for a specified short-time
427 interval.
- 428 **shunt (air switch):** A flexible electrical conductor comprised of braid, cable, or flat laminations designed
429 to conduct current around the mechanical joint between two conductors.
- 430 **side break switch:** A mechanical switching device in which the travel of the blade is in a plane parallel to
431 the base of the switch.
- 432 **single break switch:** A mechanical switching device that opens each conductor of a circuit at one point
433 only.
- 434 **single capacitance (as applied to interrupter switches):** A capacitance is defined to be a single
435 capacitance when the crest value of its inrush current does not exceed the switch inrush current capability
436 for single capacitance.
- 437 **sleet hood (of a switch):** A cover for the contacts to minimize the possibility of sleet or ice interfering with
438 successful operation of the switch.
- 439 **stationary contact member:** A conducting part having a contact surface that remains substantially
440 stationary.
- 441 **stick (hook) operation:** Manual operation of a switching device by means of an insulated switch (hook)
442 stick.
- 443 **switch inrush current capability for single capacitance (as applied to interrupter switches):** This
444 capability is a function of the rated switching current for single capacitance, the rated differential
445 capacitance voltage (minimum) and the maximum design voltage of the switch.

446 NOTE - This can be calculated from the equation:

447 Capability, in Peak Amperes =

448
$$\sqrt{2I_C} \sqrt{1 + \frac{0.8160E_m}{\Delta V_{\min}}}$$

449 where

- 450 $I_C =$ Rated switching current for single capacitance
451 $\Delta V_{min} =$ Rated differential capacitance voltage, minimum
452 $E_m =$ Switch rated maximum voltage, in volts, rms
- 453 **switch stick (switch hook):** A device with an insulated handle and a hook or other means for performing
454 stick operation of a switching device.
- 455 **switching device (switch):** *See: non-mechanical switching device, mechanical switching device:* A
456 device designed to close or open, or both, one or more electric circuits.
- 457 NOTE - The term *switch* in international (IEC) practice refers to a mechanical switching device capable of opening and
458 closing rated continuous load current.
- 459 **terminal pad:** A usually flat conducting part of a device to which a terminal connector is fastened.
- 460 **tilting-insulator switch:** A mechanical switching device in which the opening and closing travel of the
461 blade is accomplished by a tilting movement of one or more of the insulators supporting the conducting
462 parts of the switch.
- 463 **torsional mechanism:** An operating mechanism that transfers rotary motion from the operating means
464 through a pipe or shaft to open or close the switching device.
- 465 **transfer switch (a high-voltage switch):** A mechanical switching device arranged to permit transferring a
466 conductor connection from one circuit to another without interrupting the current.
- 467 1) A tandem transfer switch is a switch with two blades, each of which can be moved into
468 or out of only one contact.
- 469 2) A double-blade double-throw transfer switch is a switch with two blades, each of
470 which can be moved into or out of either of two contacts.
- 471 **trussed blade (of a switching device):** A blade that is reinforced by truss construction to provide stiffness.
- 472 **vertical break switch:** A mechanical switching device in which the travel of the blade is in a plane
473 perpendicular to the plane of the mounting base. The blade in the closed position is parallel to the mounting
474 base.
- 475 **vertical reach switch:** A mechanical switching device in which the stationary contact is supported by a
476 structure separate from the hinge-mounting base. The blade in the closed position is perpendicular to the
477 hinge-mounting base.
- 478 **vertical rod or shaft:** A component of a switch-operating mechanism designed to transmit motion from an
479 operating handle or power operator to a switch offset bearing or bell crank, or a direct drive.
- 480 **visible corona:** A luminous discharge due to ionization of the air surrounding a device, caused by voltage
481 gradient exceeding a certain critical value.

482 **Annex A**

483 (informative)

484 **Bibliography**

485 Bibliographical references are resources that provide additional or helpful material but do not need to be
486 understood or used to implement this standard. Reference to these resources is made for informational use
487 only.

488 [B1] IEEE Std C37.100TM-1992 (R 2001), IEEE Standard Definitions for Power Switchgear